Ball Valve Lockout Devices

- · Ball valves regulating hydraulic, pneumatic, and chemical energy can be locked out quickly and easily
- · Constructed of rugged polypropylene providing strength, durability, and added security
- Accommodates valve diameters ranging from .25 inches (6.35mm) to 3.00 inches (76.20mm)



Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
PSL-BV1	Ball valve lockout, accommodates .25" - 1.00" valve pipe diameter.	1	10
PSL-BV2	Ball valve lockout, accommodates 1.25" - 3.00" valve pipe diameter.	1	10
PSL-BV3	Ball valve lockout, accommodates 2.00" - 8.00" valve pipe diameter.	1	10
PSL-BFV	Butterfly valve lockout, accommodates most butterfly valve handles.	1	10

Multiple Lockout Device

· Device can be used alone as a lockout hasp or with provided 0.19 inches (4.8mm) diameter cable to lockout electrical disconnects, gate valves, or large cumbersome devices

- · Compact and easy to install
- · Constructed of rugged polycarbonate and stainless steel providing strength, durability, added security and corrosion resistance

|--|

Part Number	Part Description	Qty.	Qty.
PSL-MLD	Multiple lockout device; includes lockout hasp and 6.0' (1.8m) vinyl coated galvanized steel cable with loophole.	1	20
PSL-MLDH-X	Multiple lockout device (hasp only).	10	_
PSL-MLDC	6.0' (1.8m) vinyl coated galvanized steel cable with loophole (cable only).	1	5
PSL-MLDC200	200.0' (61.0m) vinyl coated galvanized steel cable on roll without loophole (cable only).	1	—
PSL-MLDCT	6.0' (1.8m) nylon coated high temperature rating galvanized steel cable with loophole (cable only).	1	_
PSL-MLD-CRIMP	Additional crimps for creating cable loopholes.	10	20
PSL-MLD-TOOL	Tool for installing crimps on custom-length cables using the PSL-MDLC200.	1	6



Lockout single or multiple electrical disconnects

Lockout gate valves



A 1 **A** 1

Std. Std.

Pkg. Ctn.

Immobilize large or cumbersome devices. such as forklifts

- Pneumatic Energy Lockout Device
- Pneumatic energy devices can be locked out guickly and easily without costly tool modifications or inconvenient in-line valves
- When installed on the male pneumatic fitting, prevents the ability to engage into the female fitting
- Universal compact design makes the pneumatic lockout device easy to transport and install on almost any fitting, even in tight spaces
- Rugged stainless steel construction offers superior strength, durability, added security and corrosion resistance

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
PSL-PEL	Pneumatic energy lockout device, 3.50" (88.9mm) diameter x 0.10" (2.54mm) thick.	1	20

- **C**4. Cable Management D1. Terminals
- D2. Power Connectors

A. System **Overview**

B1.

Cable Ties

B2. Cable Accessories

B3. Stainless **Steel Ties**

> **C**1. Wiring Duct

C2. Surface

Raceway

C3.

Abrasion Protection

- D3. Grounding Connectors
- E1. Labeling Systems E2. Labels E3. **Pre-Printed**
- & Write-On Markers E4. Permanent Identification

Lockout/ Tagout & Safety



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for PPE Safety Equipment / Lockout Tagout category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

 AB12-SF1260
 GPSL-6KA
 GPSL-8MKEY
 35035
 50585
 70220-1302
 740053624
 702201756
 PSL-PC38-33
 7100078986
 132231
 44-809

 G3000NUV-VI-R
 STC1165
 CP010006
 CP010010
 CP010013
 CP010702
 CP010712
 DAF010701
 GRP010704S
 WC000003
 2890S

 SF407XSGAF-BLU-EU
 SF202AS/AF-EU
 RIMFIMI
 RIMFIPO
 VULC2NOFU
 509-0015
 509-0019
 509-0020
 509-0021
 509

 0022
 509-0003
 509-0006
 109-0920
 109-0917
 109-0918
 109-0919
 DYC200-01-01-9-DYCLEAN-S
 109-0027
 X2A
 26702
 28774

 SFTY PADLOCK NYLON 38MM SHA YELLOW 6/PAC
 30-551-3040
 30-552-6012
 30-560-0039
 30-560-0039