

| PANDUIT PART NUMBER | | STUD SIZE | DIMENSIONS in. | | | | |
|---------------------|----------|-----------|----------------|---------------|---------------|----------------|---------------|
| | | | A ±.03 | W ±.01 | C ±.02 | M ±.03 | H ±.01 |
| PV10-6R | -L -D | #6 | 1.05 (26.7) | .31 (7.9) | .31 (7.9) | .89 (22.6) | .15 (3.8) |
| PV10-8R | -L -D | #8 | 1.05 (26.7) | .31 (7.9) | .31 (7.9) | .89 (22.6) | .17 (4.3) |
| PV10-10R | -L -D | #10 | 1.05 (26.7) | .31 (7.9) | .31 (7.9) | .89 (22.6) | .20 (5.1) |
| PV10-14R | -L -D | 1/4" | 1.23 (31.2) | .52 (13.2) | .38 (9.7) | .97 (24.6) | .27 (6.9) |
| PV10-56R | -L -D | 5/16" | 1.23 (31.2) | .52 (13.2) | .38 (9.7) | .97 (24.6) | .33 (8.4) |
| PV10-38R | -L -D | 3/8" | 1.31 (33.3) | .58 (14.7) | .41 (10.4) | 1.02 (25.9) | .39 (9.9) |
| PV10-12R | -L -Q | 1/2" | 1.46 (37.1) | .72 (18.3) | .53 (13.5) | 1.10 (27.9) | .52 (13.2) |

NOTES:

- UL LISTED AND CSA CERTIFIED FOR:
 - 600V. MAX. BLDG WIRE
(1000 V. MAX IN SIGNS, FIXTURES & LUMINAIRES), AND 14-10 AWG SOLID OR STRANDED COPPER WIRE, & 221°F (105°C MAX) TEMP RATING WITH THE CT-550 INSTALLATION TOOL #12 STR OR SOL & #10 STR W/ CT-1550, CT-1551 INSTALLATION TOOLS.
 - 300 V. MAX BLDG WIRE, 12-10 AWG SOLID OR STRANDED COPPER WIRE, & 167°F (75°C) MAX TEMP RATING WITH THE CT-100 INSTALLATION TOOLS.
- MATERIAL:
 - STAMPING - .04" (1.0) THK COPPER, TIN PLATED
 - HOUSING - VINYL, YELLOW
- STRIP LENGTH - 5/16 ^{+1/32} 0
- PACKAGE QTY:
 - STD PKG. -Q=25
 - STD PKG. -L=50
 - BULK PKG. -D=500
- DIMENSIONS IN BRACKETS ARE IN MILLIMETERS



CERTIFIED
LR31212



LISTED
587H
E52164

| | | | | | | | |
|-----|------|-----|-----|--|-------|------|-----|
| 06 | 8/09 | SRB | | Added -Q- packaging code to PV10-12R | | | |
| 05 | 2/02 | SAC | | FOR PV10-12R DIM A WAS 1.47 & DIM M WAS 1.11 | | | |
| 04 | 5/02 | SRB | SKB | CHANGED (DIMS) TO 1 PL DECIMAL | 10231 | LA | TRO |
| 03 | 4/02 | SRB | SKB | ADDED PV10-12R | 10171 | LA | TRO |
| REV | DATE | BY | CHK | DESCRIPTION | ECN # | CUST | PM |

PANDUIT CORP.

TINLEY PARK, ILLINOIS

2PC. VINYL INSULATED,
#12-10 BARREL, RINGS

DRAWN BY FES CHK'D SCALE NONE DRAWING NO. A41187

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NL](#) [F14-10C](#) [F-1M](#) [751-250](#) [76650-5002](#) [76828-149](#)