PANDUIT®

Product Bulletin

Arc Flash Labeling Solutions

Panduit Arc Flash Labeling Solutions are designed to comply with the latest regulations including the 2015 NFPA 70E Standard, also called Electrical Safety in the Workplace. Panduit solutions provide comprehensive identification of hazardous energy throughout the infrastructure to protect employees and equipment. Labels are available in pre-printed, print-on-demand, and custom printed versions for flexibility in indoor and outdoor applications.



New Standards and Requirements

Standards	2015 NFPA 70E	2014 NEC	2012 CSA Z462 4.3.5.4
Requirements	 130.5 (D) – Equipment Labeling. Electrical equipment such as switchboards, panel boards, industrial control panels, meter socket enclosures, and motor control centers that are in other than dwelling units and are likely to require examination, adjustment, servicing, or maintenance while energized shall be field-marked with a label containing all the following information: Nominal system voltage Arc flash boundary At least one of the following: Available incident energy and the corresponding working distance, or the arc flash PPE category in Table 130.7(C)(15)(A) (b) or Table 130.7(C)(15)(B) for the equipment, but not both Minimum arc rating of clothing Site-specific level of PPE Exception: Labels applied prior to September 30, 2011, are acceptable if they contain the available incident energy or required level of PPE. The method of calculating and the data to support the information for the label shall be documented. NFPA 70E 130.7 (E) (1) – Safety Signs and Tags Safety signs, safety symbols, or accident prevention tags shall be used where necessary to warn employees about electrical hazards that might endanger them.	110.16 Arc-Flash Hazard Warning. Electrical equipment, such as switchgear, panel boards, industrial control panels, meter socket enclosures, and motor control centers, that are in other than dwelling units, and are likely to require examination, adjustment, servicing, or maintenance while energized, shall be field or factory marked to warn qualified persons of potential electric arc flash hazards. The marking shall meet the requirements in 110.21(B) and shall be located so as to be clearly visible to qualified persons before examination, adjustment, servicing, or maintenance of the equipment.	 "Equipment Labeling. Electrical equipment* shall be field marked with a label containing all the following information. (a) at least one of the following: (i) available incident energy and the corresponding working distance; (ii) minimum arc-rating of PPE; or (iii) required level of PPE; or (iv) highest hazard/risk category for the equipment; (b) nominal system voltage; (c) arc flash boundary; and (d) date of the hazard analysis. The method of calculating and data to support the information for the label shall be documented. Labels applied prior to the effective date of this edition of this Standard are acceptable if they contain the available incident energy or required level of PPE."

*Electrical equipment, such as switchboards, panel boards, industrial motor control panels, meter socket enclosures, and motor control centers, that are in other than dwelling occupancies, and are likely to require examination, adjustment, servicing, or maintenance while energized.

Key Features	Benefits
Complies with the latest NFPA standards and meets OSHA requirements**	Mitigates the risk of fines and accidents by increasing workplace visual communication
Personal Protective Equipment (PPE) listing and pictogram labels	Provide quick visual identification of needed PPE along with required technical information in one label to aid in compliance with the NFPA 70E standards
Bilingual label formats available	Two languages on one label; English and Spanish or English and French to ensure employee safety in a multiple language environment
Raised Panel Labels	Crisp, clear, and durable legends; ideal for extended use in harsh environments
Complete system for arc flash labeling includes software, printers, and labels	Allows user the ease and flexibility to create and print the desired labels on-demand
Highly visible colors and headers with universal hazard symbols displaying critical information	Provide employees the highest degree of safety through proper identification and communication

** 2015 NFPA 70E and 2014 NEC.

www.panduit.com

NEC Warning Labels aid in compliance with Article 110.16 of the National Electric Code by providing clearly visible hazard information to warn qualified persons of potential electric arc flash hazards.



Basic



Part Number	Part Description	Pkg. Qty.	Ctn. Qty.
Basic			
PPS0204W2100	4.50" x 2.25" (114.3mm x 57.2mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard.	5	100
PPS0204W2100-F	$4.50"\ x\ 2.25"\ (114.3mm\ x\ 57.2mm),\ black/orange,\ adhesive\ polyester\ sign,\ "WARNING". Potential Arc Flash Hazard, written in French.$	5	100
PPS0305W2100	3.50" x 5.00" (88.9mm x 127.0mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard.	5	50
PPS0507W2100	5.00" x 7.00" (127.0mm x 177.8mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard.	5	50
PPS0507W2100-F	5.00" x 7.00" (127.0mm x 177.8mm), black/orange, adhesive polyester sign, "WARNING". Potential Arc Flash Hazard, written in French.	5	50
Standard			
PVS0305W2102Y	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". ARC Flash and Shock Hazard.	5	50
PVS0305W2102Y-S	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". ARC Flash and Shock Hazard. Written in Spanish.	5	50
PVS0305W2102Y-F	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". ARC Flash and Shock Hazard. Written in French.	5	50

Std.

Std.

NFPA 70E Arc Flash Labels

NFPA 70E Arc Flash Labels provide all the detailed information needed for compliance with the 2015 NFPA 70E standard. These labels are available with WARNING or DANGER headers, universal hazard symbols and clear, concise, hazard descriptions. Labels are constructed of vinyl material (PVS) that accepts handwritten hazard information by using Panduit permanent black marking pens (PFX-0).

AWA	RNING
	Shock Hazard PPE Required
ARC FLASH PROTECTION Arc Flash Hazard Category	SHOCK PROTECTION Wikage Stock Hurani Limited Approach Boundary Prohibited Approach Boundary Prohibited Approach Boundary

🛦 DA	NGER
Energized We	PE Exists ork Prohibited
ARC FLASH PROTECTION Arc Flash Hasard Galagery Incident Energy (cm/sr ²) Othersting Distance Arc Flash Boundary	SHOCK PROTECTION Values Shock Iteand Linded Ageneth Deandary Prohibited Ageneth Deandary Prohibited Ageneth Deandary

Detailed





Compact



Detailed Bilingual

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
Detailed			
PVS0305W2103Y	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Potential Arc Flash and Shock Hazard with detailed write-on area.	5	100
PVS0305W2110-F	3.50" x 5.00" (88.9mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Electrically Interlocked Handle, written in French.	5	50
PVS0305D2101Y	3.50" x 5.00" (88.9mm x 127.0mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area.	5	50
PVS0507W2103Y	5.00" x 7.00" (127.0mm x 177.8mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Potential Arc Flash and Shock Hazard with detailed write-on area.	5	100
PVS0507D2101Y	5.00" x 7.00" (127.0mm x 177.8mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area.	5	50
PVS0305W2101Y-F	5.00" x 7.00" (127.0mm x 177.8mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area. Written in French.	5	50
PVS0305W2103-F	5.00" x 7.00" (127.0mm x 177.8mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area. Written in French.	5	100
PVS0507W2101Y-F	5.00" x 7.00" (127.0mm x 177.8mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area. Written in French.	5	50
Compact			
PVS0204W2103Y	2.25" x 4.50" (57.2mm x 114.3mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Potential Arc Flash and Shock Hazard with detailed write-on area.	5	100
PVS0204D2101Y	2.25" x 4.50" (57.2mm x 114.3mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Potential Arc Flash Exists with detailed write-on area.	5	100
Detailed Bilingual			
PVS0705W2105Y-S	7.00" x 5.00" (177.8mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Arc Flash and Shock Hazard, with detailed write-on area. Written in English and Spanish.	5	100
PVS0705D2105Y-S	7.00" x 5.00" (177.8mm x 127.0mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Arc Flash and Shock Hazard, with detailed write-on area. Written in English and Spanish.	5	100
PVS0705W2105Y-F	7.00" x 5.00" (177.8mm x 127.0mm), WARNING (Header) orange and black, adhesive vinyl sign, "WARNING". Arc Flash and Shock Hazard, with detailed write-on area. Written in English and French.	5	100
PVS0705D2105Y-F	7.00" x 5.00" (177.8mm x 127.0mm), DANGER (Header) red and white, adhesive vinyl sign, "DANGER". Arc Flash and Shock Hazard, with detailed write-on area. Written in English and French.	5	100

Arc flash labels with detailed PPE information that is compliant with the 2015 NFPA 70E standard. These labels provide a helpful guide for employees to select PPE appropriate to the electrical hazard. PPE information is customized based on the specific hazard risk category. Labels are constructed of vinyl material (PVS) that accepts handwritten hazard information by using Panduit permanent black marking pens (PFX-0).

Ar Pash & Shock Hazard Appropriate DPE Required The Hard Column 1 Marg Book Internet Internet Column 1 Marg Book Internet Internet Column 1 Marg Book Internet Internet Column 1 Marg Book Internet Marg Book Internet Internet Marg Book Internet Internet	Part Number	Part Description	Std. Pkg. Qty.	Ct
PHS-Ass Riach Massed Company 1 Ing	Detailed with PPE P	Pictograms		
	PVS0507W2104Y-0	PPE Pictograms for Hazard Risk Category 0.	5	J. Ctn. 7. Qty. 100 100 100 100 100 100 100 100 100
PE	PVS0507W2104Y-1	PPE Pictograms for Hazard Risk Category 1.	5	Ctn. Qty. 100 100 100 100 100 100 100 100 100
PE	PVS0507W2104Y-2	PPE Pictograms for Hazard Risk Category 2.	5	100
	PVS0507W2104Y-3	PPE Pictograms for Hazard Risk Category 3.	5	100
r	PVS0507W2104Y-4	PPE Pictograms for Hazard Risk Category 4.	5	Ctn Qty 100 100 100 100 100 100 100 100 100 10
	Detailed with PPE L	isting		
	PVS0507W2106Y-0	PPE Listing for Hazard Risk Category 0.	5	100
	PVS0507W2106Y-1	PPE Listing for Hazard Risk Category 1.	5	Ctn. Qty. 100 100 100 100 100 100 100 100 100
iller Bol	PVS0507W2106Y-2	PPE Listing for Hazard Risk Category 2.	5	100
	PVS0507W2106Y-3	PPE Listing for Hazard Risk Category 3.	5	100
Έ	PVS0507W2106Y-4	PPE Listing for Hazard Risk Category 4.	5	100

Arc Flash Print On-Demand Labels

Panduit offers a variety of durable polyester label options for use with the TDP43ME Printer to create customized Arc Flash labels. If additional protection is desired for printed Arc Flash labels due to harsh environments or UV fading, clear overlaminate sheets (T200X000YK1, T225X000YK1, T400X000YK1, and T425X000YK1) are also available.



		Std. Pkg.	Std. Ctn.
Part Number	Part Description	Qty.	Qty.
C200X400A51	2.00" x 4.00" (50.8mm x 101.6mm), polyester safety label, WARNING (Header) orange and black, 250 labels per roll.	1	4
C200X400YZ1	2.00" x 4.00" (50.8mm x 101.6mm), polyester safety label, DANGER (Header) red and white, 250 labels per roll.	1	4
C400X400A51	4.00" x 4.00" (101.6mm x 101.6mm), polyester safety label, WARNING (Header) orange and black, 250 labels per roll.	1	4
C400X400YZ1	4.00" x 4.00" (101.6mm x 101.6mm), polyester safety label, DANGER (Header) red and white, 250 labels per roll.	1	4
C400X600A51	4.00" x 6.00" (101.6mm x 152.4mm), polyester safety label, WARNING (Header) orange and black, 100 labels per roll.	1	4
C400X600YX1	4.00" x 6.00" (101.6mm x 152.4mm), polyester arc flash label, orange header, 100 labels per roll.	1	4
C400X600YZ1	4.00" x 6.00" (101.6mm x 152.4mm), polyester safety label, DANGER (Header) red and white,100 labels per roll.	1	4
Arc Flash Print On-D	emand Continuous Tape		
T400X000A91	4.00" x 50.00' (101.6mm x 15.2m), polyester arc flash tape, red header.	1	4
T400X000YX1	4.00" x 50.00' (101.6mm x 15.2m), polyester arc flash tape, orange header.	1	4

TDP43ME Thermal Transfer Desktop Printer



The TDP43ME desktop printer, designed to work with Panduit labeling software and media, quickly creates high-quality printed identification for Industrial Automation, Network Infrastructure, OEM, MRO, and Construction applications. This easy to set-up and operate printer, produces crisp, clear, durable printed legends on wire and cable markers, terminal block labels, conduit and voltage markers, control panel labels, patch panel labels, safety signs, pipe markers and arc flash labels.

Part Number	Part Description	Pkg. Qty.
TDP43ME	300 dpi printer; includes printer, Panduit [®] Easy-Mark [™] Labeling Software, RMEH4BL hybrid black ribbon, AC power adapter with US power cord, USB cable, user manual, quick start card, and driver disk.	1

Ctd

Easy-Mark[™] Labeling Software simplifies label creation for the specific needs of your applications. Intuitive interview process allows automatic generation of arc flash labels as well as other signs and markers. Software selects and formats the optimum label for your specific project. WYSIWYG (What You See Is What You Get) user interface, alpha/numeric serialization, data import, symbol import.



Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
PROG-EMCD3	Easy-Mark [™] Labeling Software, CD-ROM.	1	10
PROG-EM2GO	Easy-Mark [™] Portable Application, USB Flash Drive.	1	10

Arc Flash Labeling Applications Using TDP43ME and Easy-Mark[™] Labeling Software

		RNIN	G
	RIATE	HOCK HAZAR	D
Arc Flash Hazard Category Incident Energy @ Working Distance Arc Flash Boundary	1 2.7 (cal/cm²) 36 inches 82 inches	Voltage Shock Hazard Limited Approach Boundary Restricted Approach Boundary Prohibited Approach Boundary Glove Class	4160 VAC 60 inches 26 inches
Equipment ID: Created of	on EasyMark	Date: 1/1/2012	By: Pandu

Detailed arc flash template from Easy-Mark[™] Labeling Software using C400X600A51 label.

A	WA	RN	N	G
	FLASH &			

e:1/1/2012 By: TDP43ME	PANDU
Glove Class	00
Prohibited Approach Boundary	1 inches
Restricted Approach Boundary	12 inches
Limited Approach Boundary	42 inches
Voltage Shock Hazard	480 VAC
Arc Flash Boundary	55 inches
Incident Energy @ 18 inches	7 ca/clm
Arc Flash Hazard Category	2

Compact and Logo arc flash template from Easy-Mark[™] Labeling Software using C400X400A51 label.

ARC FLASH & SHOO				
NO SAFE PPE EXISTS				
Arc Flash Hazard Category	Dangerous			
Incident Energy @ 18 inches	136 cal/cm²			
Arc Flash Boundary	323 inches			
Voltage Shock Hazard	480 VAC			
Limited Approach Boundary	42 inches			
Restricted Approach Boundary	12 inches			
	1 inch			
Prohibited Approach Boundary				

Compact arc flash template from Easy-Mark[™] Labeling Software using C400X400YZ1 label.

A			
	ARC FLASH & SHOCK HAZARD	Ð	(POSION ELECTRICA Y RIES DE DESCARGA ELECTRIC)
	Arc Flash Hazard Category	2	Categoría Peligro de explosión elé
	Incident Energy @ 18in.	7.5cal/cm²	Energía incidente presente @ 45cr
	Arc Flash Boundary	55 inches	Límite de explosión eléctrica
	Voltage Shock Hazard	480 VAC	Peligro de descarga de voltaje
	Limited Approach Boundary	42 inches	Límite de Acercamiento Limitado
	Restricted Approach Boundary	12 inches	Limite de Acercamiento Restringido
	Prohibited Approach Boundary	1 inch	Limite de Acercamiento Prohibido
	Glove Class	00	Clase de guante

Detailed Bilingual arc flash template from Easy-Mark[™] Labeling Software using C400X600YX1 label.

Custom Printed Arc Flash Labels

If your application demands custom printed information for your arc flash labeling, Panduit offers many options of custom printed arc flash labels. Fill out the custom arc flash label order form with your specific values, information, and even a company logo, and Panduit will create and print the specified label. Look for the icon below at **www.panduit.com/safety** to download electronic copies of the Custom Arc Flash Label order form.



WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA Markham, Ontario cs-cdn@panduit.com Phone: 800.777.3300 PANDUIT EUROPE LTD. London, UK cs-emea@panduit.com Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD. Republic of Singapore cs-ap@panduit.com Phone: 65.6305.7575 PANDUIT JAPAN P Tokyo, Japan G cs-japan@panduit.com C Phone: 81.3.6863.6000 P

PANDUIT LATIN AMERICA Guadalajara, Mexico cs-la@panduit.com Phone: 52.33.3777.6000 PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia cs-aus@panduit.com Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty



For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com or by phone: 800.777.3300 ©2016 Panduit Corp. ALL RIGHTS RESERVED. Printed in the U.S.A. Product Bulletin Number IDCB61--SA-ENG replaces SA-IDCB53 2/2016

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Identification category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

 CU6337-000
 CU6342-000
 FCA-410-12
 11631010
 1-1768037-1
 1-1768037-2
 1-1768050-0
 PXLK-VI
 Q62184-1
 A64304-000

 HK032WE1NF038B
 1330-0519-10
 1395200-1
 1395202-1
 DMVF050WE-30086
 D-SCE-1K-2.4-50-4-CS7834
 1538738-1
 E90935-000

 EC1238-000
 EC1465-000
 EC1855-000
 EC1859-000
 EC1863-000
 EC5415-000
 EC7352-000
 EC7603-000
 EC7707-000

 EC7735-000
 EC7768-000
 EC7828-000
 EC7952-000
 EC8128-000
 1768037-8
 1768041-7
 NC-127191-10-9

 HS048WE2NF038B
 C03232-000
 HTCM-SCE-14-4H-9
 HTMS-3/16-9
 HT-SCE-1/4-2.0-4
 HT-SCE-3/16-2.0-4
 HTTMS-1/2-1.50-9
 HTTMS

 CM-1/2-4H-9
 HX-SCE-19.0-50-9
 HX-SCE-6.4-50-4
 C25254-000
 CA5939-000
 CA7155-000