PHYSICAL INFRASTRUCTURE SYSTEMS

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

> G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

> N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index

PanZone® NEMA 4X/IP66 Rated Wireless Access Point Enclosures

- NEMA 4X and IP66 rating protects against corrosion, windblown dust and rain, splashing water and hose-directed water
- Universal design accommodates the most popular Wireless Access Points including Cisco Aironet[^] 1200, 1230, 1240, 1250, and 1300 Series
- Fiberglass construction and aluminum mounting plate allows quick and easy access point installation
- UL508A Listed and approved
- Include pre-configured mounting template

- Provisions for padlocks to protect against tampering and theft
- Optional NEMA 4X rated fittings available in various sizes
- Optional NEMA 4X drain and vent kit
- Connectivity accessory kit (included): 2-position outlet box, Mini-Com® TX6™ PLUS Jack Module, TX6™ PLUS Patch Cord, silicone sealant and grounding cable
- · Shielded connectivity accessory kit also available



PZNWE12



PZNWE14

P	art Number	Part Description	Std. Pkg. Qty.		
PanZone® NEMA 4X/IP66 Rated Wireless Access Point Enclosures					
P	ZNWE12	Wireless enclosure designed for Power over Ethernet applications. Includes UTP connectivity kit. External dimensions: 13.56"H x 13.47"W x 6.56"D (344.4mm x 342.1mm x 166.6mm). Internal dimensions: 11.70"H x 11.70"W x 6.29"D (297.2mm x 297.2mm x 159.8mm).	1		
P	ZNWE12S	Wireless enclosure designed for Power over Ethernet applications. Includes shielded connectivity kit. External dimensions: 13.56"H x 13.47"W x 6.56"D (344.4mm x 342.1mm x 166.6mm). Internal dimensions: 11.70"H x 11.70"W x 6.29"D (297.2mm x 297.2mm x 159.8mm).	1		
P	ZNWE14	Wireless enclosure designed for traditional AC power applications. Includes UTP connectivity kit. External dimensions: 15.50"H x 13.50"W x 6.25"D (393.7mm x 342.9mm x 158.8mm). Internal dimensions: 13.53"H x 11.55"W x 5.94"D (343.7mm x 293.4mm x 150.9mm).	1		
P	ZNWE14S	Wireless enclosure designed for traditional AC power applications. Includes shielded connectivity kit. External dimensions: 15.50"H x 13.50"W x 6.25"D (393.7mm x 342.9mm x 158.8mm). Internal dimensions: 13.53"H x 11.55"W x 5.94"D (343.7mm x 293.4mm x 150.9mm).	1		

NEMA 4X Rated Fittings and Accessories

PZNF1	NEMA 4X rated compression fitting, ideal for cable diameters of .115" to .250" (2.82mm to 6.35mm).	1
PZNF2	NEMA 4X rated compression fitting, ideal for cable diameters of .230" to .395" (5.84mm to 10.03mm).	1
PZNF3	NEMA 4X rated compression fitting, ideal for cable diameters of .170" to .450" (4.32mm to 11.43).	1
PZNDVK	NEMA 4X drain and vent kit.	1

[^]Cisco and Aironet are registered trademarks of Cisco Systems, Inc.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Enclosures, Boxes, & Cases category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

CR-425 PAINTED 585-R-WH-PK M-10-PLATED 60221-01 60566-01-000 HPL-9VB BATT DOOR M-16-LID-PLATED M18-PLTD M-21-LID-PLATED M-21-PLATED M-23-PLATED CU-281-MB 6711GSKT 71884-29-028 LH45-100 Black 7200B 72868-510-000 CNS-0000 Black 72883-510-000 CNS-0101 Black 72906-510-000 CNS-0407 Black 73091-510-000 CNM-0000-BLACK Kit 73092-510-000 CNM-0101 Black 73108-510-000 CNL-0303 Black 73395-510-039 CNS-0006 Bone 74257-510-000 CNL-0004 MDC-1183-PLAIN-ALUM MDC-1183-PTD MDC-13104-PLAIN-ALUM MDC-211 - PAINTED IVORY/BEIGE MDC-321-PTD MDC-432-PLAIN-ALUM MDC-973-PTD 76 77153-01-028 FLX6030 83535-01-508 PS-11296-G PS-11298-B 116-508 120-407 120-412 120-909 120-455 R272-100-000 120-910 R501-001-010 R508-080-000 R508-160-000 R530-120-000 R530-122-000 R530-200-000 R531-160-000 R531-200-000 R582-080-100