## PHYSICAL INFRASTRUCTURE SYSTEMS

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

> G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

> N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index

## PanZone® NEMA 4X/IP66 Rated Wireless Access Point Enclosures

- NEMA 4X and IP66 rating protects against corrosion, windblown dust and rain, splashing water and hose-directed water
- Universal design accommodates the most popular Wireless Access Points including Cisco Aironet<sup>^</sup> 1200, 1230, 1240, 1250, and 1300 Series
- Fiberglass construction and aluminum mounting plate allows quick and easy access point installation
- UL508A Listed and approved
- Include pre-configured mounting template

- Provisions for padlocks to protect against tampering and theft
- Optional NEMA 4X rated fittings available in various sizes
- Optional NEMA 4X drain and vent kit
- Connectivity accessory kit (included): 2-position outlet box, Mini-Com® TX6™ PLUS Jack Module, TX6™ PLUS Patch Cord, silicone sealant and grounding cable
- · Shielded connectivity accessory kit also available



PZNWE12



PZNWE14

P	art Number	Part Description	Std. Pkg. Qty.		
PanZone® NEMA 4X/IP66 Rated Wireless Access Point Enclosures					
P	ZNWE12	Wireless enclosure designed for Power over Ethernet applications. Includes UTP connectivity kit.  External dimensions: 13.56"H x 13.47"W x 6.56"D (344.4mm x 342.1mm x 166.6mm).  Internal dimensions: 11.70"H x 11.70"W x 6.29"D (297.2mm x 297.2mm x 159.8mm).	1		
P	ZNWE12S	Wireless enclosure designed for Power over Ethernet applications. Includes shielded connectivity kit.  External dimensions: 13.56"H x 13.47"W x 6.56"D (344.4mm x 342.1mm x 166.6mm).  Internal dimensions: 11.70"H x 11.70"W x 6.29"D (297.2mm x 297.2mm x 159.8mm).	1		
P	ZNWE14	Wireless enclosure designed for traditional AC power applications. Includes UTP connectivity kit.  External dimensions: 15.50"H x 13.50"W x 6.25"D (393.7mm x 342.9mm x 158.8mm).  Internal dimensions: 13.53"H x 11.55"W x 5.94"D (343.7mm x 293.4mm x 150.9mm).	1		
P	ZNWE14S	Wireless enclosure designed for traditional AC power applications. Includes shielded connectivity kit.  External dimensions: 15.50"H x 13.50"W x 6.25"D (393.7mm x 342.9mm x 158.8mm).  Internal dimensions: 13.53"H x 11.55"W x 5.94"D (343.7mm x 293.4mm x 150.9mm).	1		

## **NEMA 4X Rated Fittings and Accessories**

PZNF1	NEMA 4X rated compression fitting, ideal for cable diameters of .115" to .250" (2.82mm to 6.35mm).	1
PZNF2	NEMA 4X rated compression fitting, ideal for cable diameters of .230" to .395" (5.84mm to 10.03mm).	1
PZNF3	NEMA 4X rated compression fitting, ideal for cable diameters of .170" to .450" (4.32mm to 11.43).	1
PZNDVK	NEMA 4X drain and vent kit.	1

<sup>^</sup>Cisco and Aironet are registered trademarks of Cisco Systems, Inc.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Enclosures, Boxes & Cases category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

585-R-WH-PK M-10-PLATED 60221-01 60566-01-000 HPL-9VB BATT DOOR M18-PLTD M-21-PLATED 63310-01-000 6711GSKT 71884-29-028 LH45-100 Black 72868-510-000 CNS-0000 Black 72883-510-000 CNS-0101 Black 72906-510-000 CNS-0407 Black 73092-510-000 CNM-0101 Black 73105-510-000 CNL-0101 Black 73108-510-000 CNL-0303 Black 73395-510-039 CNS-0006 Bone 74257-510-000 CNL-0004 MDC-1183-PLAIN-ALUM MDC-1183-PTD MDC-13104-PTD MDC-321-PTD MDC-973-PTD 76 77153-01-028 FLX6030 83535-01-508 90026-501-000 PS36-200 116-508 120-407 120-910 127-908 130-008 1301170079 1322GSKTEP 1325GSKT3 1434-1210 EAS-500 (BLACK ANO) 1804RP-RB-PK 190-005 2202307 KAB3321 BLACK KAB3421 2697466 S52213 2901123 2901699 A0645271 A20P20 2106-IR PERF-850-PLN