

| 2                                      |                                 |                           |                     |   | 1  |                        |                                       |  |
|--|---------------------------------|---------------------------|---------------------|---|--|------------------------|---------------------------------------|--|
| THIS COPY I                            | S PROVIDED                      | ON A RESTRICTED BASIS AND | IS NOT TO BE US     | SED IN ANY '                              | WAY DETRIMENTAL -  | TO THE INTERESTS       | OF PANDUIT CORP.                      |  |
|  | CATEGORY                        | 6A STP PLUG-TO-PLUG 2     | ZONE CORDS          |   |  |                        |                                       |  |
|  | SZH                             |                           |                     |   |  |                        |                                       |  |
| PART NUMBERS PART NUMBERS              |                                 | PART NUMBERS              |                     | LSZH OFFERED WITH WHITE CABLE.            |  | NHITE CABLE.           |                                       |  |
| SAPLWH**M                              |                                 | SAPPBU**                  | SAPRBU**            |   | (METERS ONLY)  |                        |                                       |  |
|  |                                 |                           |                     |   | CMP & CMR OFFERED WITH BLUE CABLE.   |                        | NITH BLUE CABLE.                      |  |
|  | RS (158"                        |                           | 10 FEET (           |   | (FEET ONLY)  |                        |                                       |  |
|  | RS (197"                        |                           | 15 FEET (180")      |   | STRAIN RELIEF BOOTS AVAILABLE IN   |                        |                                       |  |
| 6 METE                                 | RS (237"                        | ) 20 FEET (240")          | 20 FEET (2          | 240 "" )                                  | BLACK  | UNLY.                  |                                       |  |
| B 7 METE                               | RS (276"                        | ) 25 FEET (300")          | 25 FEET (:          | 300")                                     | **=LEN   | IGTH (SEE FIGU         | JRE 2, SHEET 1)                       |  |
| 8 METE                                 | RS (315"                        | ) 30 FEET (360")          | 30 FEET (3          | 360")                                     |  |                        |                                       |  |
| 9 METE                                 | RS (355"                        | ) 35 FEET (420")          | 35 FEET (*          | 420")                                     |  |                        |                                       |  |
| 10 METE                                |                                 |                           | 40 FEET (·          | 480")                                     |  |                        |                                       |  |
|  | RS (434"                        |                           |                     | 540")                                     |  |                        |                                       |  |
|  | RS (473"                        |                           |                     | 600")                                     |  |                        |                                       |  |
|  | RS (512"                        |                           | -                   | 560")                                     |  |                        |                                       |  |
|  | RS (552"                        |                           | -                   | 720")                                     |  |                        |                                       |  |
|  | RS (591"                        |                           |                     | 780")                                     |  |                        |                                       |  |
|  | RS (630"                        |                           | -                   | 340")                                     |  |                        |                                       |  |
| 18 METE                                |                                 |                           |                     | 900")                                     |  |                        |                                       |  |
| Κ Ι Ι                                  | <u>RS (788''</u>                |                           |                     | 960")                                     |  |                        |                                       |  |
| ·                                      | <u>RS (867''</u>                |                           |                     | 1020")                                    |  |                        |                                       |  |
|  | RS (945"                        |                           |                     | 1080")                                    |  |                        |                                       |  |
|  | <u>RS (1024</u><br>RS (1103     |                           |                     | 1140")                                    |  |                        |                                       |  |
|  | RS (1103                        |                           |                     | 1320")                                    |  |                        |                                       |  |
|  | RS (1260                        |                           |                     | 1440")                                    |  |                        |                                       |  |
| 34 METE                                |                                 |                           |                     | 1560")                                    | PART NUMBER  | PRODU                  | JCT SPEC/PKG SPEC                     |  |
| 36 METE                                |                                 |                           |                     | 1680")                                    | SAP * S  |                        |                                       |  |
|  | RS (1497                        |                           | 150 FEET (          |   | N//  |                        | NZA                                   |  |
|  | RS (1575                        |                           |                     |   | TITLE  | I                      |                                       |  |
| 42 METE                                | RS (1654                        | <sup>vv</sup> )           |                     | TX6A 1GIG SHIELDED PLUG-TO-PLUG ZONE CORD |  |                        |                                       |  |
| <b>A</b> 44 METE                       | RS (1733                        | ×× )                      |                     |   |  |                        |                                       |  |
| 46 METERS (1812")<br>48 METERS (1890") |                                 |                           |                     |   | CUSTOMER DRAWING   |                        |                                       |  |
|  |                                 |                           |                     |   |  |                        |                                       |  |
| 50 METE                                | RS (1969                        | ** )                      |                     |   | DATASET FILE NAME<br>M02678BJ_DC10/00E   |                        | PANDUIT                               |  |
|  |                                 |                           |                     |   | UNLESS OTHER   | NISE SPECIFIED,        | MATERIAL:                             |  |
|  |                                 |                           |                     |   | DIMENSIONAL TOLERANCES ARE: IN [mm]<br>.x ± .1 [2.54] .xxx ± .005 [.127] SEE NOTES |                        | SEE NOTES                             |  |
|  |                                 |                           | EET 1 FOR REVISIONS |   | .XX ± .01 [.25] ANGLES ± 5 °<br>THIRD ANGLE<br>PROJECTION                          |                        |                                       |  |
| <sup>†</sup> 4 12–17–13 BJN            | EJH EJH                         | SEE SHEET 1 FOR REVISIONS |                     |   |  |                        | DRAWING NUMBER:<br>02678-10           |  |
| 12-17-13 BJN   REV DATE BY             | REV DATE BY CHK APR DESCRIPTION |                           |                     |   |  | CHK SCALE<br>RJDU NONE | SHT 2 OF 2                            |  |
| - <u> </u>                             | · ·                             | 2                         |                     |   |  | 1                      | · · · · · · · · · · · · · · · · · · · |  |

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ethernet Cables / Networking Cables category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

0152660053 60302002 73-7797-25 73-8890-10 73-8890-14 73-8891-14 73-8891-25 73-8892-50 73-8894-10 73-8894-3 73-8895-14 73-8896-7 MCJB2-10P6Q7-120 84909-0204 9QA0-111-12-3.00 1200650742 1200700174 1200860368 1200650013 1201080008 1-21919-1 1300500373 1300101844 1300101845 130050-0004 1300500014 1410147 E16A06002M030 E200102-009-S1 MT14-187L 17-103530 NK5EPC18RDY NK5EPC18VLY NK5EPC18YLY NK5EPC1GRY NK5EPC30BLY NK5EPC30VLY NK5EPC30YLY NK5EPC4Y NK5EPC6YLY NK5EPC8BLY NK5EPC9YLY NK6PC30BUY NK6PC30GRY NK6PC30RDY NK6PC30YLY 1969343-6 C501100010 C501106002