

## COPPER CABLING SOLUTIONS

### UL SP PAN-PLUG™ High Performance Modular Plugs

- Unique tangle free plug latch prevents snags and provides easy release, saving time on frequent moves, adds and changes
- Exceeds FCC Part 68 and IEC 603-7 specifications
- Used in UTPCH series patch cords providing Category 5 Powersum performance
- Simplifies termination due to a unique process which requires no loading bar. Guide ramp facilitates easy conductor insertion and termination. Simplified termination design means fewer pieces required and reduces handling of small parts.
- Contacts plated with 50 microinches of gold



MP588-L



WPT-8

- Arranges all eight conductors in the proper sequence
- Provides an easy way to cut conductors to the required length



CT5-8

- Required for PAN-PLUG Modular Plug termination

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	-------------	----------------	----------------

#### PAN-PLUG Modular Plugs

MP588-L	8 Position, 8 Wire Modular Plug featuring tangle free latch. Terminates 24 gauge stranded or solid conductor with max. conductor insulation diameter of 1.02mm. CT5-8 Crimp Tool required for termination.	50	250
---------	--	----	-----

#### Wire Prep Tool

WPT-8	Wire Prep Tool	1	10
-------	----------------	---	----

#### PAN-PLUG Installation Tools

CT5-8	Crimp tool and die for PAN-PLUG Modular Plug	1	—
CD5-8	Crimp die only	1	—

### UL SP TX-6™ Patch Cords

- Features Next Generation stranded cable and enhanced performance modular plugs with GIGA-TX™ Technology for superior performance
- Offered in a variety of sizes and colours to meet individual length and colour coding requirements



Part Number	Description	Cable Colour‡	Length (m)	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	-------------	---------------	------------	----------------	----------------

#### TX-6 Patch Cords

UTPCTG1M	Patch Cords for use with TX-6 Modules (CJ688T & CJ688T3).	Off White	1	1	10
UTPCTG2M		Off White	2		
UTPCTG3M		Off White	3		
UTPCTG4M		Off White	4		
UTPCTG5M		Off White	5		
UTPCTG10M		Off White	10		

‡For other cable colours add suffix BL (Black), BU (Blue), GR (Green), RD (Red) and YL (Yellow) after part number.

### TX-6 Shielded Patch Cords



Part Number	Description	Boot Colour	Length (m)	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	-------------	-------------	------------	----------------	----------------

#### TX-6 Shielded Patch Cords

STPCTG1MBBL	Shielded Patch Cords for use with TX-6 Shielded Modules (CJS688T & CJS688T3).	Black	1	1	10
STPCTG2MBBL		Black	2	1	10
STPCTG3MBBL		Black	3	1	10
STPCTG5MBBL		Black	5	1	10

Note: For other boot colours replace BL (Black) with suffix BU (Blue), GR (Green), RD (Red) and YL (Yellow).

Patch Panels can be found on pages 54-57

For Technical Assistance, refer to inside back cover for your local PANDUIT™ Sales Office.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Ducting](#) category:*

*Click to view products by [Panduit](#) manufacturer:*

Other Similar products are found below :

[66200A-10](#) [CVED32VEPG](#) [CVED40VEPG](#) [F512D5-5F140Y](#) [F512D5-5F200Y](#) [F512D5-5F26Y](#) [F512D5-5F30Y](#) [F512D5-5F33Y](#) [F512D5-5F34Y](#) [F512D5-5F45Y](#) [F512D5-5F50Y](#) [F512D5-5F54Y](#) [F512D5-5F66Y](#) [F512D5-5F70Y](#) [F512D5-5F75Y](#) [F512D5-5F90Y](#) [F612D5-5F100Y](#) [F612D5-5F130Y](#) [F612D5-5F50Y](#) [F612D5-5F56Y](#) [F612D5-5F58Y](#) [F6L12D5-5F46](#) [F912D5-5F11Y](#) [F912D5-5F170Y](#) [F912D5-5F175Y](#) [F912D5-5F230Y](#) [F912D5-5F300Y](#) [F912D5-5F55Y](#) [F912D5-5F56Y](#) [F912D5-5F63Y](#) [F912D5-5F6Y](#) [F912D5-5F75Y](#) [F912D5-5F85Y](#) [F912D5-5F86Y](#) [F912D5-5F88Y](#) [F912D5-5F96Y](#) [FAP0047WBLMTP](#) [FAP12WBRDRDDLZ](#) [FAP12WDYLYLDLZ](#) [FAP12WEORORDLZ](#) [FAP6WEORORDLZ](#) [FAP6WFDBDBDLZ](#) [FAP8WEORORDLZ](#) [FCE2UWCL](#) [800A-LB](#) [802A-ECSP](#) [802I-ICSP](#) [FJQADH](#) [FJQFXT](#) [PED10](#)