



Search within category

GO

BUY NOW

DESIGN / INSTALL



TM1S6-C0

The cable tie mount in black is applied with a #6 (M3) screw and is 0.32" (8.1 mm) wide. It is made of weather-resistant nylon 6.6, which increases mechanical strength, heat and wear resistance, and stiffness in outdoor environments. It comes in packages of 100.

Specs

Packaging Details

Documents

★ Add to Favorites

🛒 Add to BOM

Compatible Cable Tie	M
Mount Method	#6 (M3) Screw
Material	Weather Resistant Nylon 6.6
Overall Length (In.)	0.51
Overall Length (mm)	16
Overall Width (In.)	0.32
Overall Width (mm)	10.8
Environment	Outdoor
Color	Black
Flammability Rating	UL94V-2
CE Compliant	Yes
UL Recognized (File #E136577)	Yes
Hole Diameter (In.)	0.14
Hole Diameter (mm)	3.7
Screw Size	#6 (M3)
Counterbore Diameter In.	0.28
Counterbore Diameter mm	7.0
Temperature Range	-40°F - 185°F (-40°C - 85°C)
UL Recognized	E136577
RoHS Compliancy Status	Compliant
Min. Order Qty.	100
Product Type	Cable Tie Mounts - Screw Applied

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Tie Mounts](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[3-350087-0](#) [CTB75X75BKA-C](#) [561-EZAB580T](#) [561-EZS375B40](#) [561-TA250125](#) [08443-0](#) [10035-0](#) [561-TA00600](#) [1689174-1](#) [08445-0](#)
[10351-0](#) [561-TA250125B](#) [20015-0](#) [10350-0](#) [10029-0](#) [08484-0](#) [08446-0](#) [08318-0](#) [PAM075NY-A-C](#) [MTH1-3](#) [10044](#) [151-01802](#) [151-11319](#)
[151-11819](#) [PLWP1SB-D](#) [PLWP1M-C](#) [PLWP2SA-D](#) [PLWP2SB-D](#) [PLWP2S-C](#) [PLWP1S-D](#) [PLWP1M-D](#) [TA1S8-C](#) [ABM3H-A-L](#) [ABM3H-](#)
[AT-T0](#) [EMS-A-C0](#) [EMSK3-1-3-0](#) [10079](#) [10030](#) [151-10930](#) [151-10920](#) [3590](#) [151-28320](#) [151-28349](#) [151-28530](#) [151-10914](#) [151-10904](#) [151-](#)
[10915](#) [151-10916](#) [151-10906](#) [115-06960](#)