# PHYSICAL INFRASTRUCTURE SYSTEMS



A. System

**Overview** 

### C. Fiber Optic Systems

D. Power over Ethernet

Ε. Zone Cabling

E. Wireless



H. Media Distribution

**UICBXH6IW-A** 

Ι. Physical Infrastructur Management

J. Overhead & Underfloor Routing

> K. Surface Raceway

(ŸL)

L. Cabinets, Racks & Cable

Management Μ.

Grounding 8 Bonding

N. Industrial



P. Cable Management Accessories



- Mini-Com<sup>®</sup> Ultimate ID<sup>®</sup> Hybrid Box
- Ultimate ID<sup>®</sup> components are part of a complete system for identification designed to efficiently support TIA/EIA-606-A standard labeling requirements and TIA/EIA-568-B MUTOA requirements
- Accepts Mini-Com<sup>®</sup> Modules for STP and UTP, fiber optic, and audio/video, which snap in and out for easy moves, adds, and changes
- · Provides independent access to copper and fiber optic connections
- Mounts to single gang, double gang, or DIN opening
- A retention block snaps to the base and accepts any single gang faceplate (up to six ports)

UICBXH

Base accepts up to six Mini-Com<sup>®</sup> Fiber Optic Modules

- . Manages up to 12 meters of buffered fiber optic cable that is secured in place by cable tie mounting loops
- Cover snaps to base and is secured with a screw; includes a 6-position Ultimate ID® Label Pocket to identify fiber optic connections; a clear screw cover is included for station identification
- Can be clearly identified with PanTher<sup>™</sup> LS8E or Cougar<sup>™</sup> LS9 Hand-Held Thermal Transfer Printers
- Non-adhesive computer printable label sheets for printers and write-on labels available
- Optional cover extension provides additional security of fiber connections
- Heat shrink tubing included



IECIW	Part Number	Part Description	Color‡	Labels Required*	Used with Pan-Way <sup>®</sup> Raceway	Std. Pkg. Qty.	
	UICBXH6IW-A	Hybrid box with cover accepts up to six Mini-Com® Modules in a single gang Mini-Com® Faceplate, and up to six Mini-Com® Fiber Optic Modules in the base.	Off White	One 1-Port One 6-Port	LD3, LD5	1	10
	UICBXHC6IW-A	Hybrid box with cover and cover extension accepts up to six Mini-Com <sup>®</sup> Modules in a single gang Mini-Com <sup>®</sup> Faceplate, and up to six Mini-Com <sup>®</sup> Fiber Optic Modules in the base.	Off White	One 1-Port One 6-Port	LD3, LD5	1	10
	UICBXHECIW	Cover extension for hybrid box.	Off White	_	_	1	10

‡ For other colors replace suffix IW (Off White) with EI (Electric Ivory) or WH (White). \*Ultimate ID® Labels can be found on pages 0.11 and 0.19.

## Mini-Com<sup>®</sup> Ultimate ID<sup>®</sup> Surface Mount Boxes

- Ultimate ID<sup>®</sup> components are part of a complete system for identification designed to efficiently support TIA/EIA-606-A standard labeling requirements; reference page A.17 for a complete system overview
- Accept Mini-Com<sup>®</sup> Modules for STP and UTP, fiber optic. and audio/video, which snap in and out for easy moves, adds, and changes
- · Supplied with color coordinated screw cover and clear station and port label covers, labels sold separately
- · 4-port box includes adjustable mounting tabs that enable a range of modular furniture partitions to be used for mounting the box, maximum panel thickness 0.08"
- Can be clearly identified with PanTher<sup>™</sup> LS8E or Cougar<sup>™</sup> LS9 Hand-Held Thermal Transfer Printers
- Non-adhesive computer printable label sheets for desktop printers and write-on labels available
- · Replacement screw covers and label covers available
- Optional icons available
- Custom mounting screws included
- · Mount easily with supplied mounting screws, adhesive tape, or optional magnet



UICBX2IW-A	

**UICBX4IW-A** 

Part Number	Part Description	Color‡	Labels Required*	Used with Pan-Way <sup>⊗</sup> Raceway		
UICBX2IW-A	Surface mount box accepts two Mini-Com® Modules. Dimensions: 1.06"H x 1.95"W x 3.65"L (26.92mm H x 49.53mm W x 92.71mm L).	Off White	One 1-Port One 2-Port	LD3	1	10
UICBX4IW-A	Surface mount box accepts four Mini-Com® Modules. Dimensions: 1.06"H x 3.69"W x 4.59"L (26.92mm H x 93.73mm W x 116.59mm L).	Off White	One 1-Port One 4-Port	LD3, LD5	1	10

‡For other colors replace suffix IW (Off White) with IG (International Gray), WH (White), or EI (Electric Ivory). Part number UICBX2IW-A compatible with CBM-X magnet, UICBX4IW-A compatible with CSBM-X magnet. \*Ultimate ID® Labels can be found on pages O.11 and O.19 of SA-NCCB51.

Order number of pieces required, in multiples of Standard Package Quantity.

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Ducting & Raceways category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

 800A-LB
 801I-LSP
 802A-ECSP
 802I-ICSP
 923223-000
 PRAF6WH-X
 A0405538
 1301150342
 1301160034
 1301170070
 1301180011

 1301230083
 1301230153
 1301240273
 1301250006
 1302261238
 1302261321
 1302262552
 1302263103
 1302263178
 1302263259

 1302263816
 1302263860
 1302264375
 1302264390
 1301150343
 1301160030
 1301170051
 1301170061
 1301180013

 1301230086
 1301230130
 1301240054
 1302260055
 1302260376
 1302261343
 1302262674
 1302263095
 1302263166

 1302263209
 1302263513
 1302263870
 1302264137
 1302264218
 DD1/J
 AX101472
 AX102007