THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. NOTES: TWIST TIE -1. CAT6A (10GIG) UTP PATCH CORDS 2. 100% FACTORY PERFORMANCE TESTED 3. EXCEEDS ANSI/TIA 568-C.2 CAT6A AND ISO11801 CLASS Ea REQUIREMENTS T568B WIRING SCHEME 4. C(UL)US LISTED, FILE NUMBER E129886 5. SEE CATALOG FOR A COMPLETE LIST PLUG POSITION: CABLE WIRE: OF PARTS APPLICABLE FOR USE WHITE/ORANGE WITH THIS PART. ORANGE 6. NOMINAL CABLE JACKET DIAMETER IS WHITE/GREEN .275in. (7.0mm)**BLUE** 56 WHITE/BLUE GREEN WHITE/BROWN **BROWN** SEE SHEET 2 FOR PATCH CORD LENGTHS AND PART NUMBERS PLUG POSITION 1 MODEL FILENAME SIZE DRAWING FILENAME M02998BE_DC07/00C TX6A 10GIG CM PATCH CORDS CUSTOMER DRAWING I.I. NUMBER PRODUCT SPEC/ PKG SPEC TINLEY PARK, IL 60487 ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED, ASSY METHOD/ TEST METHOD DIMENSIONAL TOLERANCES ARE: SCALE (.X) ±.03 (.XXX) ±.005 NONE THIRD ANGLE PROJECTION (.XX) ±.01 ANGLES ± 1° DRAWN BY REVIEW DRAWING NUMBERS PART NO. BJN UTP6A** DATE BJN WFMI WFMI 3-2-12 RELEASED TO PRODUCTION 02998-07 EJH 3-17-09 DRAWING NO. MAT*L 02998-07 CHK 'D REV SUP DATE BY CHK DESCRIPTION ECN -R CUST ОТН SHEET 1 OF 3 MKY

3-2-12

DATE

BJN WFMI

CHK

BY

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PATCHCORD BART NUMBER	CUT LENGTH (BEFORE STRIPPING)	MINIMUM ("L")	WE I GHT
PART NUMBER		LENGTH	(APPROX.)
UTP6A3**	40"	3 FT.(36") .91M	.217 LB (99g)
UTP6A4**	52"	4 FT.(48") 1.22M	.255 LB (116g)
UTP6A5++	64"	5 FT.(60") 1.52M	.293 LB (133g)
UTP6A6++	76"	6 FT.(72") 1.83M	.331 LB (150g)
UTP6A7**	88"	7 FT.(84") 2.13M	.369 LB (168g)
UTP6A8++	100"	8 FT.(96") 2.44M	.407 LB (185g)
UTP6A9**	112"	9 FT.(108") 2.74M	.446 LB (202g)
UTP6A10**	124"	10 FT.(120") 3.05M	.484 LB (219g)
UTP6All**	136"	11 FT.(132") 3.35M	.522 LB (237g)
UTP6A12**	148"	12 FT.(144") 3.66M	.560 LB (254g)
UTP6A13**	160"	13 FT.(156") 3.96M	.598 LB (271g)
UTP6A14**	172"	14 FT.(168") 4.27M	.636 LB (288g)
UTP6A15**	184"	15 FT.(180") 4.57M	.674 LB (306g)
UTP6A16++	196"	16 FT.(192") 4.88M	.712 LB (323g)
UTP6A17**	208"	17 FT.(204") 5.18M	.750 LB (340g)
UTP6A18**	220"	18 FT.(216") 5.49M	.788 LB (357g)
UTP6A19**	232"	19 FT.(228") 5.79M	.826 LB (375g)
UTP6A20**	244"	20 FT.(240") 6.10M	.864 LB (392g)
UTP6A25**	304"	25 FT.(300") 7.62M	1.054 LB (478g)
UTP6A30++	364"	30 FT.(360") 9.14M	1.244 LB (564g)
UTP6A35++	424"	35 FT.(420") 10.67	1.434 LB (651g)
UTP6A40++	484 "	40 FT.(480") 12.19M	1.625 LB (737g)
UTP6A45**	544 "	45 FT.(540") 13.72M	1.815 LB (823g)
UTP6A50++	604"	50 FT.(600") 15.24M	2.005 LB (909g)
UTP6A1M**	43"	1 M.(39.4") 3.28FT.	.228 LB (103g)
UTP6Al.5M**	63"	1.5 M.(59.1") 4.92FT.	.290 LB (132g)
UTP6A2M++	83"	2 M.(78.8") 6.56FT.	.353 LB (160g)
UTP6A3M**	122"	3 M.(118.2") 9.84FT.	.478 LB (217g)
UTP6A4M**	162"	4 M.(157.7") 13.12FT.	.602 LB (273g)
UTP6A5M**	201"	5 M.(196.9") 16.40FT.	.727 LB (330g)
UTP6A6M**	240"	6 M.(236.4") 19.69FT.	.852 LB (386g)
UTP6A7M++	280"	7 M.(275.8") 22.97FT.	.977 LB (443g)
UTP6A10M++	398"	10 M.(393.7") 32.81FT.	1.351 LB (613g)
UTP6A15M++	595 "	15 M.(590.6") 49.21FT.	1.975 LB (896g)
UTP6A20M++	791 "	20 M.(787.4") 65.62FT.	2.599 LB (117.9g)
UTP6A25M++	988"	25 M.(984.3") 82.02FT.	3.223 LB (146.2g)
UTP6A30M**	1185"	30 M.(1181.1") 98.43FT.	3.847 LB (174.5g)

SEE SHEET I FOR REVISIONS

DESCRIPTION

** = COLOR OF CABLE BLANK = OFF-WHITE

BU = BLUE RD = RED YL = YELLOW BL = BLACK OR = ORANGE GR = GREEN VL = VIOLET GY = GRAY

NOTE - STRAIN RELIEF BOOTS AVAILABLE IN CLEAR ONLY

MODEL FILENAME SIZE DRAWING FILENAME M02998BE_DC07/00C TX6A lOGIG CM PATCH CORDS CUSTOMER DRAWING I.I. NUMBER PRODUCT SPEC/ PKG SPEC TINLEY PARK, IL 60487 ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED, ASSY METHOD/ TEST METHOD DIMENSIONAL TOLERANCES ARE: SCALE (.X) ±.03 (.XXX) ±.005 NONE (.XX) ±.01 ANGLES ± 1° DRAWN BY REVIEW DRAWING NUMBERS PART NO. BJN UTP6A** DATE 3-17-09 MAT L DRAWING NO. 02998-07 CHK 'D SHEET 2 OF 3 MKY



EJH

02998-07

ECN -

WFMI

R



SUP

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. CONDUCTOR INSULATION CONDUCTOR WIRES FILLER --LASER TAPE <u>Pair P</u>i PAIR P2 PAIR P4 INNER JACKET -OUTER JACKET PAIR P3 MODEL FILENAME SIZE DRAWING FILENAME M02998BE_DC07/00C TX6A lOGIG CM PATCH CORDS CUSTOMER DRAWING I.I. NUMBER PRODUCT SPEC/ PKG SPEC TINLEY PARK, IL 60487 ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED, ASSY METHOD/ TEST METHOD CROSS-SECTIONAL VIEW OF CABLE DIMENSIONAL TOLERANCES ARE: SCALE (.X) ±.03 (.XXX) ±.005 NONE (.XX) ±.01 ANGLES ± 1° PART NO. DRAWN BY REVIEW DRAWING NUMBERS BJN UTP6A** DATE BJN WFMI 02998-07 WFMI 3-2-12 SEE SHEET I FOR REVISIONS EJH 3-17-09 MAT'L DRAWING NO. 02998-07 REV DATE BY DESCRIPTION CUST SUP CHK ECN - R SHEET 3 OF 3 MKY

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ethernet Cables / Networking Cables category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

0152660053 603020002 73-7797-25 73-8890-10 73-8890-14 73-8891-14 73-8891-25 73-8892-50 73-8894-10 73-8894-3 73-8895-14 73-8896-7 MCJB2-10P6Q7-120 84909-0204 9QA0-111-12-3.00 1200650742 1200700174 1200860368 1200650013 1201080008 1-21919-1 1300500373 1300101844 1300101845 130050-0004 1300500014 1410147 E16A06002M030 E200102-009-S1 MT14-187L 17-103530 NK5EPC18RDY NK5EPC18VLY NK5EPC18YLY NK5EPC1GRY NK5EPC30BLY NK5EPC30VLY NK5EPC30YLY NK5EPC4Y NK5EPC6YLY NK5EPC9YLY NK6PC30BUY NK6PC30GRY NK6PC30RDY NK6PC30YLY 1969343-6 C501100010 C501106002