
ANDUT[®] PHYSICAL INFRASTRUCTURE SYSTEMS

Copper Systems

. (TX6A[™] 10Gig[™] UTP Patch Cords with MaTriX Technology

- Exceed requirements of ANSI/TIA-568-C.2 Category 6A, IEEE 802.3an-2006, and ISO 11801 Class E_A channel standards
- Meet requirements of IEEE 802.3af and IEEE 802.3at for PoE applications
- MaTriX Technology provides superior suppression of alien crosstalk (PSANEXT and PSAACRF)
- Superior headroom warranty provides the highest margins above the industry standard for both electrical and alien crosstalk performance
- Color-coded, keyed modular plugs mechanically and visually distinguish connections to prevent unintentional mating with unlike keyed or non-keyed jack modules accommodating more discrete networks
- Each patch cord is 100% performance tested and wired to T568B
- TX6A[™] 10Gig[™] constructed of 24 AWG stranded copper cable (nominal cable diameter 0.275 in.) and TX6[™] PLUS Modular Plugs for superior performance
- TX6A-SD[™] 10Gig[™] constructed of 26 AWG stranded copper cable (nominal cable diameter 0.240 in.) and TX6 PLUS Modular Plugs for superior performance

- Plug meets all applicable ANSI/TIA-968-A requirements and exceeds IEC 60603-7 specifications
- Slender strain relief boot provides easy access in high density applications
- Plug uses an integral pair manager to optimize performance and consistency by reducing untwisting of conductors within the plug
- Plug performance in center of TIA/EIA component range, ensuring interoperability and 10GBASE-T Ethernet channel performance
- Labels on patch cords provide identification of performance level, length, and quality control number
- Patented tangle-free latch prevents snags and provides easy release, saving time on frequent moves, adds, and changes
- Optional patch cord color bands snap on and off individual patch cables offering endless color-coding options
- Optional RJ45 lock-in device blocks unauthorized removal of cable, IP phone, other networking equipment, or critical connection



Part Number	Part Description	Length (Ft.)	Cable Color		
TX6A [™] 10Gig [™]	UTP Patch Cord (up to 100 meter solution)		-		
UTP6A3^	Category 6A, 10 Gb/s UTP patch cord with TX6A [™] 10Gig [™] Modular Plugs on each end. Includes patent pending MaTriX Tape Technology.	3	Blue	1	10
TX6A-SD™ 10Gi	g [™] UTP Patch Cord (up to 70 meter solution	n)			
UTP6ASD3‡	Category 6A (SD), 10 Gb/s UTP patch cord with TX6A [™] 10Gig [™] Modular Plugs on each end. Includes patent pending MaTriX Tape Technology.	3	Blue	1	50
Keyed TX6A [™] 1	OGig [™] UTP Patch Cord (up to 100 meter sol	ution)			
UTPK6A3BL*	Keyed, Category 6A, 10Gb/s UTP patch cord with TX6A [™] 10Gig [™] Keyed Modular Plug on one end and TX6A [™] 10Gig [™] Non-Keyed Modular Plug on the other end. Includes patent pending MaTriX Tape Technology.	3	Black	1	10
part number to the de RD (Red), YL (Yellow example, the part num ‡For lengths 3 to 20 i part number to the de RD (Red), YL (Yellow part number for a blu *For lengths other tha length. For standard d YL (Yellow), GR (Gre	feet (increments of one foot) and 25, 30, 35, 40 feet, change esired length. For standard cable colors other than Off White), GR (Green), YL (Yellow), OR (Orange), VL (Violet), or GY mber for a blue, 15-foot patch cord is UTP6A15BU. feet (increments of one foot) and 25, 30, 35, 40 feet, change ssired length. For standard cable colors other than Off White), GR (Green), YL (Yellow), OR (Orange) or VL (Violet) to the e, 15-foot patch cord is UTP6ASD15BU. In 3 feet (5, 7, 10, 14 feet), change the length designation in cable colors other than BL (Black), replace suffix BL (Black) en), or OR (Orange), each color representing a different key universal reference patch cords	, add suffix (Gray) to th the length , add suffix part numb the part nu with BU (Bl	BL (Black ne part nu designati BL (Black per. For ex umber to t ue), RD (<), BU mber. I on in th <), BU (ample the des Red),	(Blue) For ne (Blue) , the

Patch cord color bands available on page B.91 of SA-NCCB51. RJ45 plug lock-in device available on page B.89 of SA-NCCB51.

Must be installed as part of a complete TX6A[™] 10Gig[™] Copper Cabling System in order to achieve 10GBASE-T certified performance.

Reference page B.30 of SA-NCCB51 for appropriate labeling solution.

Fiber Optic Systems

C.

D. Power over Ethernet

E. Zone Cabling

F. Wireless

G. Outlets

H. Media Distribution

l. Physical Infrastructure Management

J. Overhead & Underfloor Routing

> K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ethernet Cables / Networking Cables category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

 73-6670-7
 73-6680-15
 73-7797-25
 MCJB2-10P6Q7-120
 84909-0204
 1200700174
 1200860368
 E16A06002M030
 E200102-009-S1

 AX105346-EW
 MT14-187L
 17-103530
 ERWPAB3002M005
 190-038045-01
 NK5EPC18RDY
 NK5EPC18VLY
 NK5EPC18YLY

 NK5EPC1GRY
 NK5EPC4Y
 NK5EPC6YLY
 NK5EPC8BLY
 NK5EPC9YLY
 1969343-6
 C501100010
 C501106002
 C501106007

 C501106015
 C501106025
 C601102010
 C601104010
 C601106007
 C601106015
 2142758-2
 2168427-2
 CAT1106007
 21949-1
 2J1866A

 RJF SFTP 5E 0500
 AX100351
 MN14CEC/ST
 C501106004
 C501106010
 C551108007
 C601104004
 C601106004

 CA21106004
 CA21106010
 CA21106015
 CA21109007
 C601104004
 C601106004