



PJMBZ5V6 SERIES

DUAL TVS FOR ESD / TRANSIENT PROTECTION

VOLTAGE 5.6 to 6.8 Volts **POWER** 150 Watts

SOT-23

Unit : inch(mm)

FEATURES


- Working Peak Reverse Voltage Range - 5.6 to 6.8V
- Maximum Leakage Current of 5uA
- IEC61000-4-2 Compliance 15kV Air, 8kV Contact Discharge
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)

APPLICATIONS

- Data Transmission Line Ports
- Computer Monitor Interface Port Protection
- Portable Consumer Electronics
- Instrumentation Equipment

MECHANICAL DATA

- Case: SOT-23, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Apporx. Weight: 0.0003 ounces, 0.0084 grams



MAXIMUM RATINGS (TA=25°C unless otherwise noted)

PARAMETER	Symbol	Value	Units
Peak Pulse Power 8x20 usec Waveform	P _{PP}	150	W
Peak Pulse Power 10x1000 usec Waveform		30	
ESD per IEC61000-4-2 (Air)	V _{PP}	+/-15	kV
ESD per IEC61000-4-2 (Contact)		+/-8	kV
Lead Soldering Temperature (max 10 secs)	T _L	260	°C
Operating Junction Temperature and Storage Temperature Range	T _J ,T _{STG}	-55 to +150	°C




Fig.25



PJMBZ5V6 SERIES

ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

PJMBZ5V6 Marking UA						
PARAMETER	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Stand-Off Voltage	V _{RWM}		-	-	3.3	V
Reverse Breakdown Voltage	V _{BR}	I _{BR} =1.0 mA I _{BR} =20 mA	5.13 5.32	5.4 5.6	5.67 5.88	V
Reverse Leakage Current	I _R	V _R =3.3V	-	-	5.0	μA
Clamping Voltage (8x20 usec)	V _{CL}	I _{PP} =20 Amps	-	-	9.0	V
Clamping Voltage (10x1000 usec)	V _{CL}	I _{PP} =5.0 Amps	-	-	7.0	V
Off State Junction Capacitance	C _J	0 Vdc Bias f=1MHz Between I/O pins and pin 3	-	-	90	pF

PJMBZ6V2 Marking UB						
PARAMETER	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Stand-Off Voltage	V _{RWM}		-	-	4.3	V
Reverse Breakdown Voltage	V _{BR}	I _{BR} =1.0 mA I _{BR} =20 mA	5.89	6.2	6.51	V
Reverse Leakage Current	I _R	V _R =4.3V	-	-	0.5	μA
Clamping Voltage (8x20 usec)	V _{CL}	I _{PP} =20 Amps	-	-	9.5	V
Clamping Voltage (10x1000 usec)	V _{CL}	I _{PP} =4.0 Amps	-	-	7.5	V
Off State Junction Capacitance	C _J	0 Vdc Bias f=1MHz Between I/O pins and pin 3	-	-	70	pF

PJMBZ6V8 Marking UC						
PARAMETER	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Stand-Off Voltage	V _{RWM}		-	-	5.0	V
Reverse Breakdown Voltage	V _{BR}	I _{BR} =1.0 mA I _{BR} =20 mA	6.46	6.8	7.14	V
Reverse Leakage Current	I _R	V _R =5.0V	-	-	0.5	μA
Clamping Voltage (8x20 usec)	V _{CL}	I _{PP} =20 Amps	-	-	10	V
Clamping Voltage (10x1000 usec)	V _{CL}	I _{PP} =4.0 Amps	-	-	8.5	V
Off State Junction Capacitance	C _J	0 Vdc Bias f=1MHz Between I/O pins and pin 3	-	-	100	pF



PJMBZ5V6 SERIES

RATING AND CHARACTERISTIC CURVES




Fig.1 8/20µs Peak Pulse Current Waveform




Fig.2 10/1000µs Peak Pulse Current Waveform




Fig.3 Non-Repetitive Peak Pulse Power vs Pulse Time




Fig.4 Capacitance vs. Biasing Voltage @1MHz




Fig.5 8x20µsec Surge Waveform





Fig.6 10x1000µsec Waveform



PJMBZ5V6 SERIES

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel



PJMBZ5V6 SERIES

Part No_packing code_Version

PJMBZ5V6_R1_00001

PJMBZ5V6_R2_00001

For example :

RB500V-40_R2_00001



Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



PJMBZ5V6 SERIES

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ESD Suppressors / TVS Diodes](#) category:

Click to view products by [Panjit](#) manufacturer:

Other Similar products are found below :

[NTE4902](#) [P4SMAJ15A](#) [P4SMAJ26A](#) [SMAJ400CA-TP](#) [TGL34-47CA](#) [ESDAULC45-1BF4](#) [SM1605E3/TR13](#) [SMF20A-TP](#) [P4SMAJ12A](#)
[CPDUR24V-HF](#) [CPDQC5V0USP-HF](#) [CPDQC5V0-HF](#) [MPLAD30KP45CAE3](#) [MMBZ27VCLQ-7-F](#) [MMAD1108/TR13](#) [MPLAD30KP24A](#)
[ACPDQC5V0R-HF](#) [DFLT170A-7](#) [NTE4900](#) [NTE4926](#) [NTE4938](#) [SMF22A-TP](#) [SMF12A-TP](#) [SLVU2.8-TP](#) [SMLJ6.5CA-TP](#) [SMAJ6.5CA-](#)
[TP](#) [MMAD1108E3/TR13](#) [D5V0M1U2LP3-7](#) [SMAJ400A-TP](#) [AOZ8811DT-03](#) [AOZ8831DI-05](#) [AOZ8831DT-03](#) [SMAJ188CA](#) [3SMC33CA](#)
[BK](#) [CPDQC3V3C-HF](#) [CPDQC12VE-HF](#) [MPLAD30KP170CA](#) [82357120100](#) [5.0SMLJ15CA-TP](#) [5KP18A-TP](#) [P6KE8.2A-TP](#)
[MPLAD30KP43CAE3](#) [SMAJ43A-TP](#) [D5V0F6U8LP33-7](#) [TVS5501V10MUT5G](#) [5.0SMLJ24CA-TP](#) [SMAJ110CA-TP](#) [MPLAD15KP75CAE3](#)
[MMAD1103e3/TR13](#) [DFLT40AQ-7](#)