

**100V N-Channel Enhancement Mode MOSFET**

<b>Voltage</b>	<b>100 V</b>	<b>R<sub>DS(ON)</sub></b>	<b>9.4 mΩ</b>
<b>Current</b>	<b>61 A</b>	<b>Q<sub>G</sub> (TYP)</b>	<b>19 nC</b>

**Feature**


- R<sub>DS(ON)</sub> < 9.4 mΩ at V<sub>GS</sub> = 10 V, I<sub>D</sub> = 30 A
- R<sub>DS(ON)</sub> < 14.3 mΩ at V<sub>GS</sub> = 6 V, I<sub>D</sub> = 15 A
- High switching speed
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard
- 100% UIS / Rg test in mass production

**Mechanical Data**

- Case: DFN5060-8L Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 94 mg

**Application**

- Brick Power. DC/DC converter. SR of Industrial PSU.



**Absolute Maximum Ratings** (T<sub>A</sub> = 25 °C unless otherwise specified)

PARAMETER		SYMBOL	LIMIT	UNITS	
Drain-Source Voltage		V <sub>DS</sub>	100	V	
Gate-Source Voltage		V <sub>GS</sub>	±20		
Continuous Drain Current (Note 3)	T <sub>C</sub> =25 °C	I <sub>D</sub>	61	A	
	T <sub>C</sub> =100 °C		43		
Pulsed Drain Current		T <sub>C</sub> =25 °C	I <sub>DM</sub>	244	A
Single Pulse Avalanche Current (Note 5)		I <sub>AS</sub>	28	A	
Single Pulse Avalanche Energy (Note 5)		E <sub>AS</sub>	98	mJ	
Power Dissipation	T <sub>C</sub> =25 °C	P <sub>D</sub>	75	W	
	T <sub>C</sub> =100 °C		37.5		
Operating Junction and Storage Temperature Range		T <sub>J</sub> , T <sub>STG</sub>	-55~175	°C	

**Thermal Characteristics**

PARAMETER	SYMBOL	VALUES			UNITS	
		MIN.	TYP.	MAX.		
Thermal Resistance	Junction-to-Case (Bottom)	R <sub>θJC</sub>	-	1.3	2.0	°C/W
	Junction-to-Ambient (Note 4)	R <sub>θJA</sub>	-	-	50	°C/W

## Electrical Characteristics (T<sub>A</sub> = 25 °C unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0 V, I <sub>D</sub> =250 μA	100	-	-	V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =115 μA	1.8	2.8	3.8	
Drain-Source On-State Resistance (Note 1)	R <sub>DS(on)</sub>	V <sub>GS</sub> =10 V, I <sub>D</sub> =30 A	-	8.4	9.4	mΩ
		V <sub>GS</sub> =6 V, I <sub>D</sub> =15 A	-	11.0	14.3	
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =100 V, V <sub>GS</sub> =0 V	-	-	1	μA
Gate-Source Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> =±20 V, V <sub>DS</sub> =0 V	-	-	±100	nA
Transfer characteristics (Note 1)	g <sub>fs</sub>	V <sub>DS</sub> =10 V, I <sub>D</sub> =30 A	-	45	-	S
<b>Dynamic Characteristics (Note 6)</b>						
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> =50 V, I <sub>D</sub> =30 A, V <sub>GS</sub> =10 V	-	19	25	nC
Gate-Source Charge	Q <sub>gs</sub>		-	7.6	-	
Gate-Drain Charge	Q <sub>gd</sub>		-	3.0	-	
Gate Plateau Voltage	V <sub>plateau</sub>		-	5.4	-	V
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> =50 V, V <sub>GS</sub> =0 V, f=250 kHz	-	1370	1780	pF
Output Capacitance	C <sub>oss</sub>		-	460	600	
Reverse Transfer Capacitance	C <sub>rss</sub>		-	10	-	
Output Charge	Q <sub>oss</sub>	V <sub>DS</sub> =50 V, V <sub>GS</sub> =0 V	-	34	44	nC
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> =50 V, I <sub>D</sub> =30 A, V <sub>GS</sub> =10 V, R <sub>G</sub> =3.0 Ω (Note 2)	-	6.2	-	ns
Rise Time	t <sub>r</sub>		-	3.3	-	
Turn-Off Delay Time	t <sub>d(off)</sub>		-	10.4	-	
Fall Time	t <sub>f</sub>		-	3.3	-	
Gate Resistance	R <sub>g</sub>	f =1.0 MHz	-	1.1	2.2	Ω
<b>Drain-Source Diode</b>						
Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> =30 A, V <sub>GS</sub> =0 V	-	0.9	1.2	V
Reverse Recovery Charge	Q <sub>rr</sub>	I <sub>F</sub> =30 A, V <sub>DD</sub> =50 V, di/dt=100 A/μs	-	45	-	nC
Reverse Recovery Time	T <sub>rr</sub>		-	41	-	ns

### NOTES :

1. Pulse width ≤ 300 μs, Duty cycle ≤ 2 %
2. Essentially independent of operating temperature typical characteristics.
3. The maximum drain current calculated by maximum junction temperature and thermal impedance. It can be varied by application and environment.
4. R<sub>θJA</sub> is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch<sup>2</sup> with 2oz.square pad of copper.
5. E<sub>AS</sub> is calculated based on the condition of L = 1.0 mH, I<sub>AS</sub> = 14 A, V<sub>DD</sub> = 50 V, V<sub>GS</sub> = 10 V. 100% test at L = 0.1 mH, I<sub>AS</sub> = 28 A in production.
6. Guaranteed by design, not subject to production testing.

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 Capacitance vs. Drain-Source Voltage




Fig.6 On-Resistance vs. Gate-Source Voltage

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Source-Drain Diode Forward Voltage




Fig.11 Maximum Safe Operating Area





Fig.12 Normalized Transient Thermal Impedance


**Product and Packing Information**

Part No.	Package Type	Packing Type	Marking
PSMQC094N10NS2	DFN5060-8L	3000pcs / 13" reel	094N10NS

**Packaging Information & Mounting Pad Layout**



**Marking Diagram**



- Y** = Year Code
- W** = Week Code (A~Z)
- LL** = Lot Code (00~99)
- x** = Production Line Code

## Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc.
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFETs](#) category:*

*Click to view products by [Panjit](#) manufacturer:*

Other Similar products are found below :

[MCH6422-TL-E](#) [IRFD120](#) [IRFY240C](#) [JANTX2N5237](#) [2SJ277-DL-E](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#)  
[IRFS350](#) [VN1206L](#) [NDP4060](#) [IPS70R2K0CEAKMA1](#) [AON6932A](#) [2N4352](#) [TS19452CS RL](#) [TK31J60W5,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#)  
[2SK2614\(TE16L1,Q\)](#) [JANTX2N6798](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [DMN1053UCP4-7](#) [SCM040600](#) [NTE2384](#) [2N7000TA](#)  
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)  
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [DMN2990UFB-7B](#)  
[2N7002W-G](#) [MCAC30N06Y-TP](#) [MCQ7328-TP](#) [IPB45P03P4L11ATMA2](#) [BXP2N20L](#) [BXP2N65D](#) [BXT330N06D](#) [TSM60NB380CP](#) [ROG](#)  
[RQ7L055BGTGR](#) [SLF10N65ABV2](#)