

Atlas LCR45

passive component impedance meter

Model: LCR45

PEAK
electronic design ltd

PRODUCT BRIEF

Advanced Maths

The LCR45 builds on the success of the LCR40 Passive Component Analyser. With a new micro, including 12 bit ADCs and new software written from the ground up, the LCR45 is more than just evolution.

This new instrument incorporates advanced maths, based on Complex Impedance analysis. This allows for enhanced component value measurement as well as a comprehensive and detailed impedance display.

Auto and Manual Modes

Now you have the benefit of speed and simplicity with the fully automatic mode combined with the flexibility of manual modes.

The LCR45 can automatically determine the component type being tested, alternatively, you can select the component type manually. This is particularly useful for components that may have more unusual characteristics. The test frequency can be left in automatic mode, yielding the best possible measurement resolution. For some components you may want to specify the test frequency yourself.

Flexible Measurement Display

The detailed measurements can be presented in a variety of ways. The first measurement display is the summary of the component type and its value(s). The second screen is the full complex impedance value (shown as a complex number). Finally, the impedance can be seen in polar form, of magnitude and phase.

Component Summary

Inductor \square 23.6 Ω \square
L=123.4 μ H \square 200k Ω

Complex Impedance

Impedance 200k Ω
+25.6 +j155.1 Ω

Magnitude and Phase

Mag/Phase 200k Ω
157.2 Ω +80.6 $^\circ$



Continuous measurements with hold function

Main Features

- Supplied with gold plated removable hook probes.
- Fluid measurements with hold function.
- Automatic or manual component type.
- Automatic or manual test frequency, DC, 1kHz, 15kHz or 200kHz.
- Enhanced measurement resolution: 0.2 μ H, 0.2pF and 0.2 Ohms.
- Easy menu system for user settings.
- Enhanced compensation for component parasitics and losses (such as core losses etc).
- Automatic or manual power-off.

Please note that specifications of our products are subject to change without notice. E&OE.

10/13

Parameter		Min	Typ	Max
Resistance	range	0 Ω		2M Ω
	resolution	0.1 Ω	0.2 Ω	
	accuracy	Typically \pm 1.0% \pm 0.6 Ω		
Capacitance	range	0pF		10,000 μ F
	resolution	0.1pF	0.2pF	
	accuracy	Typically \pm 1.5% \pm 0.6pF		
Inductance	range	0 μ H		10H
	resolution	0.1 μ H	0.2 μ H	
	accuracy	Typically \pm 1.5% \pm 0.6 μ H		
Passive Component Impedance	Re & Im	Typically \pm 1.5% \pm 10 LSD		
	Magnitude	Typically \pm 1.5% \pm 10 LSD		
	Phase	Typically \pm 5 $^\circ$		
Measurement Sample Rate		0.5Hz	1.5Hz	2Hz
Peak test voltage (across O/C)		-1.05V		+1.05V
Peak test current (thru S/C)		-3.25mA		+3.25mA
Test frequency accuracy	1kHz	Typically \pm 0.5%		
	14.9254kHz			
	200kHz			
Sine purity		Typically -60dB 3 rd harmonic		
Operating temperature range		10 $^\circ$ C		40 $^\circ$ C
Battery operating voltage		8.5V		13V

Peak Electronic Design Limited

Atlas House, 2 Kiln Lane, Harpur Hill Business Park, Buxton, Derbyshire, SK17 9JL. Tel.+44 (0)1298 70012, Fax. +44 (0)1298 70046
www.peakelec.co.uk sales@peakelec.co.uk

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Peak Electronic Design](#) manufacturer:

Other Similar products are found below :

[PAT02](#) [PTPM](#) [CRC01](#) [UTP05](#) [UTP05E](#) [ATC55](#) [IDT8B](#) [IDT8C](#) [IDTN](#) [SCR100](#) [ATC02](#) [ZEN50](#) [SMD03M](#) [UPS56](#) [PCA23](#) [ENP90](#)
[LCR45](#) [ESRLHP2](#) [LCR40+DCA55+ATC55](#) [SMD03](#) [ATPK3](#) [DCA55T](#) [ATLAS IT](#) [ESR70](#) [LCR-40](#) [DCA75](#)