



37W LED Driver with 4 Channel Constant Current Outputs PDA037W LED Power Supply with 0-10V Dimming



Features

- 4 Channel Output
- OVP, Short & Open Circuit, OTP & Brownout Protection
- Class 2 Output per UL1310
- UL8750 Compliant
- AC input: 108-304VAC
- ≥ 0.9 Power Factor Correction & THD <20%
- IP65 Rated

Applications

- Indoor Lighting
- Linear Fluorescent Replacement
- Outdoor Lighting

Safety Approvals

- cUL/UL

Mechanical Characteristics

- Length: 242mm (9.5in)
- Width: 43.5mm (1.7in)
- Height: 30.5mm (1.2in)
- Weight: 675g (1.5lbs)

Output Specifications

Channel 1~4

Model	DC Output Voltage Range			Output Current Range		
	Min.	Typ.	Max.	Min.	Typ.	Max.
PDA037W-350G	22V	24.5V	26.5V	333mA	350mA	368mA

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:

AC Input Voltage
108 to 304V AC

Nominal AC Input Voltage
120~277VAC

Leakage Current
<3.5mA at 277VAC – Case to Ground
<0.25mA at 277VAC – Outputs to Ground

Maximum Input Current
0.55A (RMS) at 108VAC, 60Hz

AC Inrush Current
<30A at 277VAC, 60Hz

OUTPUT:

Total Output Power
Maximum output should be <52W

Efficiency
>82% at 120VAC, >84% at 277VAC

Standby Power
<2.5W maximum

Power Factor
≥0.9 at nominal input voltage, full load

Ripple (CH1~CH4)
240mA p-p

Turn on/off Time
0.5 seconds maximum at nominal AC input

ENVIRONMENTAL:

Operating Temperature 0 to +50°C
Storage Temperature -40 to +85°C

Operating Humidity 10 to 95%
Storage Humidity 5 to 95%

Case Temperature
Case may not exceed 70°C at ambient 50°C

Dimming

Dimming	Min.	Typ.	Max.	Remarks
Dim Voltage-1	-	-	1V	Cut off Current at 1.V Dim. Voltage
Dim Voltage-2	-	-	1.2V	Output Current ≤14mA
Dim Voltage-3	-	5.5V	-	Driver shall provide 95mA ± 10% Current
Dim Voltage-4	-	-	10V	Driver 10V shall provide 100% Output (350mA ± 5%)
Sink Current	-	-	1mA	

100% brightness without dimmer: Open state for dimming port

EMC

FCC 47 Part 15 Class A

Immunity

EN61000-4-2 Criteria B
EN61000-4-3
EN61000-4-4
EN61000-4-5 Criteria B
EN61000-4-6
EN61000-4-8
EN61000-4-11
EN61000-3-2 Class C

Isolation Test

Primary to Secondary: 3000VAC, <5mA, 1 minute

Insulation Resistance

Primary to Secondary: 500VDC, >5M ohm, 1 minute

FEATURES:

Input Over Current Protection

The input power line will be fused with a 2A/300V fuse resistor

Short Circuit Protection

Auto restart without damage

Output Overvoltage Protection

Output should not exceed 39V, auto shut down

Open Circuit Protection

Once the circuit is opened, the output voltage should be less than 39V at nominal AC input conditions

Wires

Input	Gauge	Length
Black (live)	UL1316 AWG18	453mm
White (neutral)	UL1316 AWG18	453mm
Ground		
Green/Yellow (GND)	UL1316 AWG18	220mm
Output		
Red (LED CH1~4+)	UL1569 AWG22	76mm
Black (GND CH1~4-)	UL1569 AWG22	76mm
Dimming		
Violet (Dimmer +)	UL1316 AWG18	127mm
Gray (Dimmer-)	UL1316 AWG18	127mm

Output Connector


Molex 8 pin p/n – 09-50-1081 mate p/n – 09-65-2088

Ingression Protection

IP65

Warranty

5 Years



Output Connection:

Pin Number	Connection
Pin 1	V+
Pin 2	GND
Pin 3	GND
Pin 4	V+
Pin 5	V+
Pin 6	GND
Pin 7	GND
Pin 8	V+

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Power Supplies](#) category:

Click to view products by [Phihong](#) manufacturer:

Other Similar products are found below :

[ESS015W-1000-12](#) [PDA-WIFI](#) [PIFC-K250F](#) [PITB-K222A](#) [ALD-514012PJ134](#) [LB240S24KH](#) [LMH020-SPLC-0000-0000001](#) [LMD600-0100-C1A7-7030000](#) [79534](#) [79535](#) [EUG-200S210DT](#) [ESS030W-1050-21](#) [ESS030W-0900-32](#) [BPOXL 4-12-035](#) [ESS010W-0350-24](#) [ESM060W-1400-42](#) [PDA080B-1A0G](#) [PDA150B-S1A5G](#) [ZPS-20](#) [SLM140W-1.05-130-ZA](#) [ESS015W-0700-18](#) [EUD-150S350DVA](#) [LWA320-C420-ARK-B](#) [HVG-240-48AB](#) [HVG-320-36AB](#) [HVG-320-54AB](#) [ELG-240-C1400AB](#) [EUK-150S105DV](#) [BXCS-12Z-N2P-B1-A](#) [BXPR-WN-01-A](#) [LN1224CV](#) [BXCS-12W-N2P-01-A](#) [HBG-160-24AB](#) [980100001200394](#) [980060001200376](#) [LC 14W 250-350MA FLEXC R ADV2](#) [LC 24W 500-600MA FLEXC R ADV2](#) [LC 36W 850-900MA FLEXC R ADV2](#) [LC 18W 24V ONE4ALL SC PRE](#) [LC 50W 200-350ML 170V FLEXC LP SNC4](#) [LC 25W 200-350ML 70V FLEXC LP SNC4](#) [LCBI 10W 350MA PHASE-CUT/1-10V LP](#) [LC 13W 300MA FIXC C SNC](#) [LC 10W 250MA FIXC SC SNC2](#) [LC 35W 800MA FIXC SR ADV2](#) [LC 38W 900MA FIXC SR ADV2](#) [LC 34W 800MA FIXC SC ADV2](#) [LC 44W 1050MA FIXC SC ADV2](#) [LC 38W 900MA 42V FIXC SRL ADV2](#) [PWM-40-36](#)