

Conductor marking collar - PMH 0:SYMBOLE - 0800446

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Conductor marking collar, yellow, horizontal: Symbols, mounting type: thread on, cable diameter range: 1.4 ... 2.5 mm, lettering field size: 3.2 x 2.6 mm

The figure shows a combination of upper case letters, symbols and figures in versions PMH -0, -2 and -4



Key Commercial Data

Packing unit	100 pc
Minimum order quantity	100 pc
Weight per Piece (excluding packing)	0.090 g
Custom tariff number	49119900
Country of origin	Czech Republic

Technical data

Dimensions

Length (b)	4.5 mm
Width (a)	3.2 mm
Cable diameter	1.4 mm ... 2.5 mm

Ambient conditions

Ambient temperature (operation)	-45 °C ... 70 °C
Ambient temperature (assembly)	> 10 °C

General

Note	Please specify the required marking with order: Minimum order per imprint: 1 packing unit
Color	yellow
Type	Profile
Components	free from silicone, halogen, and cadmium
Flammability rating according to UL 94	V0
Material	Ethylene-vinyl acetate (EVA)

Conductor marking collar - PMH 0:SYMBOLE - 0800446

Technical data

General

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Printing direction	horizontal
Printing	Symbols
Marking mounting type	thread on
Min. cross section	0.5 mm ²
Max. cross section	0.75 mm ²
AWG min	20
AWG max	16

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 10.0.1	27400401
eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27400401
eCl@ss 5.1	27400400
eCl@ss 6.0	27400400
eCl@ss 7.0	27400401
eCl@ss 8.0	27400401
eCl@ss 9.0	27400401

ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC001530
ETIM 5.0	EC001530
ETIM 6.0	EC001530
ETIM 7.0	EC001530

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504

Conductor marking collar - PMH 0:SYMBOLE - 0800446

Classifications

UNSPSC

UNSPSC 20.0	39131504
UNSPSC 21.0	39131504

Accessories

Accessories

Assortment box

Range box - SORTI 4/12 - 5020658



Assortment box, 12 compartments external dimensions 335 x 225 x 55 mm, material: Polystyrene

Mounting material

Alignment tool for cable markers - AFD-1 - 0800666



Threading pin, helps thread PMH onto the conductor; insert conductor into pin opening and slide collar on. For external conductor cross section: 2.0 - 2.5 mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)