


## Plastic label - US-EMLP-HA 24 (30X18/8) - 0803876

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plastic label, with bore hole, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 1 of 30 x 18 mm and 1 of 30 x 8 mm, Number of individual labels: 6



### Key Commercial Data

|                        |   |
|------------------------|---|
| Packing unit           | 10 pc   |
| Minimum order quantity | 10 pc   |
| GTIN                   | <br>4 055626 173351 |
| GTIN                   | 4055626173351   |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 66 mm |
| Width (a)  | 30 mm |

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -30 °C ... 80 °C  |
| Recommended storage conditions  | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

#### General

|   |                             |
|---|-----------------------------|
| Color   | white                       |
| Components  | Silicone-free               |
| Material  | PVC                         |
| RoHS compliant  | Yes                         |
| Wipe resistance   | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels   | 6                           |
| Number of individual labels per row                                 | 3                           |
| Adhesive  | Acrylic                     |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02        |

## Plastic label - US-EMLP-HA 24 (30X18/8) - 0803876

### Technical data

#### General

|  |                                     |
|--|-------------------------------------|
| Result   | Test passed                         |
| Test specification weathering-resistance           | Following ISO 4892-2:2013-03        |
| Test duration                                      | 96 h                                |
| Result of weather resistance test                  | Test passed                         |
| Salt spray test specification                      | DIN EN 60068-2-11:2000-02           |
| Test duration                                      | 96 h                                |
| Salt spray testing result                          | Test passed                         |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result of wipe resistance test                     | Test passed                         |
| Foil strength                                      | 500 µm                              |
| Marking mounting type                              | adhesive                            |

#### Standards and Regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

#### Drawings

# Plastic label - US-EMLP-HA 24 (30X18/8) - 0803876

Pictogram



## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 5.0    | 27149100 |
| eCl@ss 5.1    | 27149100 |
| eCl@ss 6.0    | 27149100 |
| eCl@ss 7.0    | 27149129 |
| eCl@ss 8.0    | 27149129 |
| eCl@ss 9.0    | 27400629 |

### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC001288 |
|----------|----------|

# Plastic label - US-EMLP-HA 24 (30X18/8) - 0803876

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 39131504 |
| UNSPSC 18.0 | 39131504 |
| UNSPSC 19.0 | 39131504 |
| UNSPSC 20.0 | 39131504 |
| UNSPSC 21.0 | 39131504 |

## Approvals

### Approvals

Approvals

CSA

Ex Approvals

### Approval details

|     |  |   |          |
|-----|--|---|----------|
| CSA |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 70191766 |
|-----|--|---|----------|

## Accessories

### Accessories

#### Magazine

Magazine - TMP-US-MAG1 - 0803341



Magazine, For THERMOMARK CARD and THERMOMARK PRIME, for accommodating US cards

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Labels and Industrial Warning Signs](#) category:*

*Click to view products by [Phoenix Contact](#) manufacturer:*

Other Similar products are found below :

[ESSW30-025](#) [FTP-020P0704](#) [QC101](#) [QC105](#) [QCC613](#) [QCC615](#) [132465](#) [142810](#) [15288](#) [15425](#) [18511](#) [HTS795-1](#) [30288](#) [1768021-2](#) [18432](#)  
[1878679-3](#) [2-1878614-6](#) [PTL-31-427-YL](#) [30239](#) [QC154](#) [QCC612](#) [30545](#) [35070](#) [WM-15-PK](#) [WM-20-PK](#) [5-1768021-6](#) [06770](#) [11197](#)  
[111852](#) [111932](#) [KMT-02513V-9](#) [06742](#) [8-1768039-4](#) [1878983-4](#) [06736](#) [B422 25X85MM](#) [PAXLBK10](#) [LAT-52-361-1](#) [PTL-20-486](#) [PTL-](#)  
[38-486](#) [PTLFT-01-425](#) [13903](#) [11237](#) [18389](#) [18341](#) [18603](#) [29904](#) [18519](#) [18524](#) [115110](#)