

Fuse insert - S 63 A/380 V - 0913100

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fuse insert, nominal current: 63 A, length: 36 mm, diameter: 15 mm, color: copper-colored

Your advantages

- ✓ Contains no lead, cadmium, chromium 6 (ROHS-compliant)
- ✓ NEOZED® fuse-links with gG characteristic for protecting lines and equipment
- ✓ Safe shutoff of impermissible overcurrents and short-circuit currents up to the nominal shutoff current
- ✓ Colored indicating pins on the butt contact show the operating state

Key Commercial Data

| | |
|--------------|---|
| Packing unit | 10 pc |
| GTIN |  4 017918 008208 |
| GTIN | 4017918008208 |

Technical data

General

| | |
|---|----------------|
| Color | copper-colored |
| Maximum power dissipation for nominal condition | 5.5 W |

Dimensions

| | |
|----------|-------|
| Length | 36 mm |
| Diameter | 15 mm |

General

| | |
|-----------------------|---------------------|
| Fuse | gL/gK NEOZED |
| Nominal current I_N | 63 A |
| Nominal voltage U_N | 400 V AC (250 V DC) |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -60 °C ... 85 °C |
|---------------------------------|------------------|

Fuse insert - S 63 A/380 V - 0913100

Technical data

Ambient conditions

| | |
|--|--|
| Ambient temperature (storage/transport) | -25 °C ... 55 °C (For a short time, not exceeding 24 h, -60 to +70 °C) |
| Permissible humidity (storage/transport) | 30 % ... 70 % |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27142002 |
| eCl@ss 4.0 | 27142000 |
| eCl@ss 4.1 | 27142000 |
| eCl@ss 5.0 | 27142000 |
| eCl@ss 5.1 | 27142000 |
| eCl@ss 6.0 | 27142000 |
| eCl@ss 7.0 | 27142002 |
| eCl@ss 8.0 | 27142002 |
| eCl@ss 9.0 | 27142002 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000899 |
| ETIM 3.0 | EC000899 |
| ETIM 4.0 | EC000899 |
| ETIM 5.0 | EC002704 |
| ETIM 6.0 | EC002704 |
| ETIM 7.0 | EC002704 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211813 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121412 |
| UNSPSC 12.01 | 39121412 |
| UNSPSC 13.2 | 39121627 |
| UNSPSC 18.0 | 39121627 |
| UNSPSC 19.0 | 39121627 |
| UNSPSC 20.0 | 39121627 |
| UNSPSC 21.0 | 39121627 |

Fuse insert - S 63 A/380 V - 0913100

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|--------------------------|
| EAC |  | RU C- DE.BL08.B.00724 |
|-----|---|--------------------------|

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Specialty Fuses](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[63NZ02GL](#) [714125](#) [722134](#) [F02A-4AS](#) [F02B-1A](#) [80NH00GR-6](#) [FWH-200A](#) [FWP-32A14F](#) [12LCT](#) [12TDLSJ63](#) [REN-3](#) [15.5CAVH2E](#)
[ECF-1](#) [ECF-2](#) [ECF-3](#) [ECF-4](#) [170M0213](#) [170M1369-D](#) [170M3809D](#) [BK/F02B-1A](#) [N-2-1/2](#) [N-3-2/10](#) [NITD2](#) [20D16](#) [KAA-3](#) [KAB-30](#)
[KAW-3](#) [2D16](#) [LKN-125B](#) [16D27SB](#) [16FC](#) [170M1564D](#) [170M2616](#) [170M2668](#) [170M4161](#) [170M4241](#) [170M4699](#) [ESD63](#) [ABS-30](#) [ABS-8](#)
[ACF-15](#) [ACF-30](#) [ACO-30](#) [F02A-10A](#) [SSD10](#) [200NH1M](#) [FWP-25A14FI](#) [FWP-40A14FI](#) [FWP-500A](#) [FWP-63A22FI](#)