

## Crimping pliers - CRIMPFOX VARIO 16S - 1108767

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Crimping pliers, type of contact: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, min. cross section: 6 mm<sup>2</sup>, max. cross section: 16 mm<sup>2</sup>, compression: square, black/green

### Your advantages

- Lateral conductor entry
- Proven high-quality technology
- "The original"
- Suitable for TWIN sleeves
- Unlockable pressure lock



### Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 1 pc  |
| GTIN         | <br>4 063151 016449 |
| GTIN         | 4063151016449   |

### Technical data

#### Dimensions

|            |        |
|------------|--------|
| Length (b) | 222 mm |
| Width (a)  | 76 mm  |
| Height (c) | 25 mm  |

#### General

|                    |                                    |
|--------------------|------------------------------------|
| Color              | black/green                        |
| Compression        | square                             |
| Type of contact    | Insulated and uninsulated ferrules |
| Designation        | Crimping position 1                |
| Max. cross section | 6 mm <sup>2</sup>                  |
| AWG max            | 10                                 |
| Designation        | Crimping position 2                |
| Max. cross section | 10 mm <sup>2</sup>                 |
| AWG max            | 8                                  |

# Crimping pliers - CRIMPFOX VARIO 16S - 1108767

## Technical data

### General

|                    |                     |
|--------------------|---------------------|
| Designation        | Crimping position 3 |
| Max. cross section | 16 mm <sup>2</sup>  |
| AWG max            | 6                   |
| Weight             | 582 g               |
| Min. cross section | 6 mm <sup>2</sup>   |
| Max. cross section | 16 mm <sup>2</sup>  |
| AWG min            | 10                  |
| AWG max            | 6                   |

## Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 9.0 | 21043811 |
|------------|----------|

## Approvals

Approvals

---

Approvals


EAC

---

Ex Approvals

---

## Approval details

|     |   |                          |
|-----|---|--------------------------|
| EAC |  | RU x-<br>DE.xx08.B.02974 |
|-----|---|--------------------------|

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Crimpers / Crimping Tools](#) category:*

*Click to view products by [Phoenix Contact](#) manufacturer:*

Other Similar products are found below :

[010-0096](#) [M225202-37](#) [6-1579015-5](#) [CT150-2-D02](#) [622-6441LF](#) [M322](#) [6-304052-1](#) [63456-0054](#) [63484-3701](#) [63800-8355](#) [63819-1875](#)  
[63819-2875](#) [63819-4475](#) [63823-3475](#) [63827-5375](#) [64001-0975](#) [64001-4175](#) [64005-0175](#) [662903-2](#) [690602-6](#) [7-1579001-9](#) [7-23471-1](#)  
[762637-1](#) [808714-1](#) [811242-5](#) [999-50-020083](#) [1-21002-3](#) [1-21002-7](#) [12085270](#) [1-21002-6](#) [1-21113-6](#) [1-22548-4](#) [125442-1](#)  
[DCE.91.073.BVC](#) [DCE.91.090.3MVM](#) [DCE.91.130.5MVU](#) [DCE.91.202.BVCM](#) [1338300-1](#) [1-354003-0](#) [1338301-1](#) [DF62/RE-MD](#) [142321](#)  
[1456088-1](#) [1490794-1](#) [1-45804-6](#) [1490357-2](#) [1490357-3](#) [AX100749](#) [1-59619-7](#) [1596970-1](#)