

FO patch cable - FOC-LC:PA-LC:PA-OM4:D01/2 - 1115624

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Multi-mode OM4 duplex jumper, LC-LC, UPC polishing, length 2 m

Your advantages

- ✓ Glass fiber optical, 8-shaped FO cable jumper
- ✓ Indoor use, suitable for fiber optics distribution and termination devices
- ✓ Made of halogen-free flame retardant material, RoHS compliant



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 063151 038984 |
| GTIN | 4063151038984 |
| Weight per Piece (excluding packing) | 21.000 g |
| Custom tariff number | 85447000 |
| Note | Made to Order (non-returnable) |

Technical data

Dimensions

| | |
|-----------------|--------|
| Length of cable | 2.00 m |
|-----------------|--------|

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (storage/transport) | -20 °C ... 60 °C |
|---|------------------|

Material

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Cable

| | |
|--------------------|----------------------|
| Cable type | Multimode fiberglass |
| Cable abbreviation | I-V(ZN)H |
| Cable structure | Figure 8 cable |

FO patch cable - FOC-LC:PA-LC:PA-OM4:D01/2 - 1115624

Technical data

Cable

| | |
|------------------------|---|
| External sheath, color | Violet |
| Cable weight | 5.30 kg/km |
| Outer sheath, material | LSZH |
| Halogen-free | According to IEC 60754-2 |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |
| Concentration of fumes | in accordance with IEC 61034 |

Standards and Regulations

| | |
|--|---|
| Concentration of fumes | in accordance with IEC 61034 |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |
| Halogen-free | According to IEC 60754-2 |
| Behavior in fire | No corrosive or toxic fumes |
| Flammability rating according to UL 94 | V0 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 8.0 | 27061801 |
| eCl@ss 9.0 | 27061003 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC001578 |
|----------|----------|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Cable Assemblies](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[7-21002-9](#) [MDM-25SH006F-A174](#) [MDM-25SH011F-A174](#) [FA04390-50-M-72-LC-N](#) [MLB 501 V RED](#) [MLB 501 V YELLOW](#) [MLN 1002,5](#)
[RED](#) [1-3636-600-5208](#) [1-5018030-0](#) [2061529-7](#) [21055-6](#) [3000005](#) [3-21053-2](#) [MLB 200/1 V BLACK](#) [MLB 2001 V RED](#) [MLB 2001 V](#)
[YELLOW](#) [MLB 501 V BLACK](#) [106284-7000](#) [5492011-5](#) [5492011-8](#) [5492011-9](#) [8-21007-5](#) [106386-4447](#) [2123909-4](#) [106273-0629](#)
[2125046-1](#) [2821236-3](#) [2821310-2](#) [2821310-3](#) [2821313-4](#) [FX2ERLNLNSNM0.5](#) [CF-980062-074](#) [FCBG410QD3C10](#) [CF-901200-394](#) [CF-](#)
[980062-073](#) [CF-980062-071](#) [CF-980062-075](#) [CF-980062-072](#) [17-300310-100](#) [MIKROE-3728](#) [FA04474](#) [1083665](#) [17-300870-23](#) [TCP-](#)
[Q151B-NNE22](#) [SPTMBP1PACDF003](#) [106272-2133](#) [106283-5304](#) [106284-1010](#) [111025-1210](#) [1115533](#)