

Coding profile - HC-MOD-K-CP - 1408562

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Coding profile for HC-MOD-K... housing




Product Description

Coding profile
Block with 8 pcs.



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 619301 |
| GTIN | 4046356619301 |

Technical data

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 85 °C |
|---------------------------------|------------------|

General

| | |
|--|--|
| Color | red |
| Material | PA |
| Flammability rating according to UL 94 | V2 |
| Assembly instructions | for sleeve housing HC-MOD-K-TMS-.../panel mounting base HC-MOD-K-AFS-... |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V2 |
|--|----|


Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Drawings

Coding profile - HC-MOD-K-CP - 1408562

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27440203 |
| eCl@ss 4.0 | 23090100 |
| eCl@ss 4.1 | 23090100 |
| eCl@ss 5.0 | 23090100 |
| eCl@ss 5.1 | 23090100 |
| eCl@ss 6.0 | 27269200 |
| eCl@ss 7.0 | 27440203 |
| eCl@ss 8.0 | 27440203 |
| eCl@ss 9.0 | 27440203 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC002311 |
| ETIM 6.0 | EC002311 |
| ETIM 7.0 | EC002311 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31161807 |
| UNSPSC 7.0901 | 31161807 |
| UNSPSC 11 | 31161807 |
| UNSPSC 12.01 | 31161807 |
| UNSPSC 13.2 | 27112301 |
| UNSPSC 18.0 | 27112301 |
| UNSPSC 19.0 | 27112301 |
| UNSPSC 20.0 | 27112301 |
| UNSPSC 21.0 | 27112301 |

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[647757-1](#) [6643411-1](#) [6646058-2](#) [6646137-1](#) [6646138-1](#) [6646479-1](#) [6646608-1](#) [6646786-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#)
[6651788-1](#) [696475-1](#) [702-32-01109](#) [703-25-02205](#) [73000005059](#) [73000005642](#) [765-15-0080A](#) [765-16-0080B](#) [765-18-0080D](#) [829992-1](#)
[902-77-02113](#) [PS00/A0620/6300](#) [129-1J](#) [1409400](#) [AN0024023](#) [E6374G1](#) [e6389g2](#) [157-43GW8](#) [MS3117-14AC](#) [1643543-1](#) [1650540-1](#)
[1651811-2](#) [1766260-1](#) [1766282-1](#) [1766966-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-W-L-C240-M40B](#) [NLS-2-R-C240-](#)
[M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [1986615-1](#) [2-1589900-8](#) [2199314-1](#) [KA8102](#) [9300480317](#) [SBS50BRN#6](#) [29131](#)