

Screw plug - A-EXSH-M40-68L-N-S - 1411111


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Screw plug, cable gland material: Nickel-plated brass, application: Ex, connecting thread: M40 x 1.5, color: silver



Key Commercial Data

| | |
|------------------------|---|
| Packing unit | 5 pc |
| Minimum order quantity | 5 pc |
| GTIN |  4 046356 922265 |
| GTIN | 4046356922265 |

Technical data

Dimensions

| | |
|----------------------------------|---------|
| Length | 24 mm |
| Length without connecting thread | 9 mm |
| Connecting thread diameter | 40 mm |
| Thread pitch | 1.5 mm |
| Wrench size, union nut | 46 mm |
| Hexagon angular dimension | 50.6 mm |
| Length of the connecting thread | 15 mm |

Ambient conditions

| | |
|---------------------------------|---|
| Degree of protection (IP) | IP66 (using the corresponding A-SEW-...P-W flat gasket) |
| | IP68 (using the corresponding A-SEW-...P-W flat gasket) |
| Ambient temperature (operation) | -60 °C ... 130 °C |

General

| | |
|-----------------------------|---|
| Note | This item must only be used with counter nut 1411246 A-INL-M40-N-S for the Ex e type of protection. |
| Cable gland material | Nickel-plated brass |
| Thread type connection side | M40 x 1.5 |

Screw plug - A-EXSH-M40-68L-N-S - 1411111

Technical data

General

| | |
|-----------------------------|--|
| Color | silver |
| Assembly instructions | Sealed to IP66/IP68 thanks to the use of the A-SEW-40-P-W flat gasket (item 1411286) |
| Standards/specifications | EN 60079-0, -1, -7 |
| | IEC 60079-0, -1, -7 |
| | EN 61241-0, -1 |
| | IEC 61241-0, -1 |
| Manufacturer | CMP |
| Manufacturer product number | 757DM55 |
| Manufacturer Designation | 757 M40 Exd/Exe N.PLTD HEX HD STOP PLUG |
| Suited for EX-applications | yes |

Standards and Regulations

| | |
|--------------------------|--|
| Standards/specifications | EN 60079-0, -1, -7 |
| | IEC 60079-0, -1, -7 |
| | EN 61241-0, -1 |
| | IEC 61241-0, -1 |
| ATEX | Sira 01ATEX1284U |
| | Sira 02ATEX1003X |
| | Ex II 2 GD Ex d IIC & Ex e II, Ex IM2 Ex d I, Ex e I |
| IECEX | IECEX SIR 07.0056X |
| | Ex d I / Ex e I / Ex d IIC / Ex e II, Ex tD A21 IP6X |


Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings

Screw plug - A-EXSH-M40-68L-N-S - 1411111

Dimensional drawing



Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 23111190 |
| eCl@ss 4.0 | 23111100 |
| eCl@ss 4.1 | 23111100 |
| eCl@ss 5.0 | 23111100 |
| eCl@ss 5.1 | 23111100 |
| eCl@ss 6.0 | 23111100 |
| eCl@ss 7.0 | 23111190 |
| eCl@ss 8.0 | 23111190 |
| eCl@ss 9.0 | 23111190 |

Screw plug - A-EXSH-M40-68L-N-S - 1411111

Classifications

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000032 |
| ETIM 5.0 | EC000032 |
| ETIM 6.0 | EC000032 |
| ETIM 7.0 | EC000032 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 31161501 |
| UNSPSC 18.0 | 31261502 |
| UNSPSC 19.0 | 31261502 |
| UNSPSC 20.0 | 31261502 |
| UNSPSC 21.0 | 31261502 |

Accessories

Accessories

Flat nut

Counter nut - A-INL-M40-N-S - 1411246



Counter nut, material: Brass, nickel-plated, for threads M40 x 1.5, color: silver

Seal

Flat gasket - A-SEW-40-P-W - 1411286



Flat gasket, material: Nylon, for threads M40, color: white

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Conduit Fittings & Accessories](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[M3231GAB](#) [M3231GAC](#) [M3231GAE](#) [M3231GL](#) [M3231GT](#) [VC-937-16/RED](#) [VC-562-16/RED](#) [VC-1125-16/RED](#) [DM0240-1/2A](#) [3408B](#)
[G6002](#) [M4340GAE](#) [C2016-P](#) [C2012-P](#) [3407B](#) [1660-P](#) [561-87BG11BLK](#) [561-75BG11B](#) [1.533.1201.50](#) [1.533.1601.51](#) [BVNV-P428](#) [BVBV-](#)
[P366](#) [2276](#) [2663-P](#) [3405B](#) [C2070-P](#) [3582V](#) [2643-P](#) [4975](#) [2644-P](#) [2955](#) [M50](#) [2404-P](#) [2723-P](#) [2291](#) [2133-P](#) [3048F](#) [VC12516](#) [RC156-0500](#)
[DM0523-1/2A](#) [1035A](#) [DMS0250-1A](#) [DMS0313-1A](#) [1040A](#) [1050A](#) [R1/8A](#) [DMPC0490-1/2A](#) [DMPC0521-1/2A](#) [DMPC0552-1/2A](#) [1070A](#)
[R1/2A](#)