

Power cable - SAC-3P- 5,0-547/MINFS - 1416550

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 3-position, PVC, yellow, free cable end, on Socket straight 7/8"-16UNF, Cable length: 5 m

Why buy this product

- Easy and safe: 100% electrically tested plug-in components
- High-performance: connectors and cables with a large conductor cross section for power supply

Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 STK |
| GTIN |  4 055626 221335 |
| GTIN | 4055626221335 |
| Weight per Piece (excluding packing) | 22.220 g |
| Custom tariff number | 85444290 |
| Country of origin | United States |
| Note | Made to Order (non-returnable) |

Technical data

Dimensions

| | |
|-----------------|-----|
| Length of cable | 5 m |
|-----------------|-----|

Ambient conditions

| | |
|---------------------------------|-----------------------------------|
| Ambient temperature (operation) | -20 °C ... 105 °C (Plug / socket) |
| Degree of protection | IP68 |

General

| | |
|-----------------------------|-------|
| Rated current at 40°C | 13 A |
| Rated voltage | 300 V |
| Number of positions | 3 |
| Insertion/withdrawal cycles | 100 |

Power cable - SAC-3P- 5,0-547/MINFS - 1416550

Technical data

General

| | |
|--------|-------------------------|
| Torque | 10 lb _F -in. |
| | 1.12 Nm |

Material

| | |
|--------------------------|----------|
| Contact material | CuZn |
| Contact surface material | AU |
| Contact carrier material | PVC |
| Material of grip body | PVC |
| Material, knurls | Aluminum |

Cable


| | |
|--|---|
| Cable type | ITC/PLTC |
| Cable abbreviation | 547 |
| AWG signal line | 18 |
| Conductor cross section signal conductor | 3 x AWG 18 |
| Conductor cross section voltage supply | 41 x AWG 34 |
| Wire colors | Black 1, blue 2, grey 3, brown 4, white 5 |
| External sheath, color | yellow |
| External cable diameter | 5.70 mm |
| Outer sheath, material | PVC |
| Conductor material | Bare Cu litz wires |
| Nominal voltage, cable | 300 V |
| Flame resistance | UL 1581, FT4 |
| Other resistance | UV resistant (720 h) UL 2256 |

Standards and Regulations

| | |
|------------------|------------------------------|
| Flame resistance | UL 1581, FT4 |
| Other resistance | UV resistant (720 h) UL 2256 |


Drawings

Dimensional drawing



7/8"-16UNF socket, straight


Schematic diagram



Pin assignment, socket, 7/8"-16UNF, 5-pos., view of female side

Power cable - SAC-3P- 5,0-547/MINFS - 1416550

Circuit diagram



Contact assignment of the 7/8" connector and the 7/8" socket

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Sensor Cables / Actuator Cables](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[1300070444](#) [43-10984](#) [M83513/19-F01CP](#) [704000D02F120](#) [MDM15SH001K](#) [MDM25PH003BF222](#) [802027107404-1](#) [885030A09M010](#)
[885030A09M020](#) [1200650174](#) [1200651332](#) [1200651713](#) [1200660171](#) [1200660208](#) [1200660343](#) [1200660804](#) [1200660845](#) [1200660926](#)
[1200660977](#) [1200661173](#) [1200661354](#) [120066-1712](#) [1200720053](#) [1200720099](#) [1200720153](#) [1200720172](#) [1200720217](#) [1200720226](#)
[1200720251](#) [1200720285](#) [1200720296](#) [1200720404](#) [1200730148](#) [1200730378](#) [1200800231](#) [1200860112](#) [1200860121](#) [1200860125](#)
[1200860337](#) [1200860365](#) [1200860420](#) [1200870046](#) [1200870123](#) [1200870248](#) [1200980102](#) [1200660181](#) [1200660183](#) [1200660827](#)
[1200660849](#) [1200661170](#)