

# Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Connector hood, application: Sensor/actuator box, connection method: M8 socket Metal, number of slots: 8, coding: A - standard, slot assignment: single, status display: No; master cable connection: Pluggable screw connection 180°, PUR/PVC, cable length: 10 m, shielding: no



## Key Commercial Data

|              |               |
|--------------|---------------|
| Packing unit | 1 pc          |
| GTIN         |               |
| GTIN         | 4017918967277 |

## Technical data

### General

|  |   |
|--|---|
| Rated voltage                            | 120 V AC  |
|  | 120 V DC  |
| Current carrying capacity per I/O signal | 2 A   |
| Current carrying capacity per slot       | 2 A   |
| Total rated current                      | 8 A   |
| Number of slots                          | 8   |
| Sensor/actuator connection system        | M8 socket   |
| Note                                     | NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties. |

### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Degree of protection            | IP65  |
|                                 | IP67  |
| Ambient temperature (operation) | -30 °C ... 80 °C                            |
|                                 | -40 °C ... 90 °C (for fixed installation)   |
|                                 | -5 °C ... 80 °C (for flexible installation) |

### Master cable connection data

# Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

## Technical data

### Master cable connection data

|                   |                            |
|-------------------|----------------------------|
| Connection method | Pluggable screw connection |
| Length of cable   | 10 m                       |

### Insulation material

|  |             |
|--|-------------|
| Housing material   | PBT         |
| Material of contact, master cable side                   | CU alloy    |
| Material of contact surface, master cable side           | Gold-plated |
| Material of the contact carrier on the master cable side | PA          |

### Pin assignment

|  |                       |
|--|-----------------------|
| Slot/position = Wire color or connection | 1 / 4 (A) = WH        |
|  | 2 / 4 (A) = GN        |
|  | 3 / 4 (A) = YE        |
|  | 4 / 4 (A) = GY        |
|  | 5 / 4 (A) = PK        |
|  | 6 / 4 (A) = RD        |
|  | 7 / 4 (A) = BK        |
|  | 8 / 4 (A) = VT        |
|  | 1-8 / 1 (+ 24 V) = BN |
|  | 1-8 / 3 (0 V) = BU    |

### Standards and Regulations

|                                  |     |
|----------------------------------|-----|
| Connection in acc. with standard | CUL |
|----------------------------------|-----|

### Cable

|                                     |   |
|-------------------------------------|---|
| Cable type                          | PUR/PVC black   |
| Cable type (abbreviation)           | PUR   |
| Cable abbreviation                  | LiYY11Y-HF  |
| UL AWM style                        | 20549   |
| Conductor cross section             | 8x 0.34 mm <sup>2</sup> (Signal line)                             |
|                                     | 2x 0.75 mm <sup>2</sup> (power line)                              |
| AWG signal line                     | 22  |
| AWG power supply                    | 18  |
| Conductor structure signal line     | 19x 0.15 mm   |
| Conductor structure, voltage supply | 42x 0.15 mm   |
| Core diameter including insulation  | 1.3 mm ±0.1 mm (Signal line)                                      |
|                                     | 1.8 mm ±0.1 mm (power line)                                       |
| Wire colors                         | brown, blue, white, green, yellow, gray, pink, red, black, violet |
| Overall twist                       | Wires twisted in layers   |
| External sheath, color              | black RAL 9005  |
| Inner sheath thickness              | ≥ 0.15 mm   |
| Outer sheath thickness              | ≥ 0.38 mm   |
| External cable diameter D           | 7.9 mm ±0.2 mm  |

# Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

## Technical data

### Cable

|   |  |
|---|--|
| Minimum bending radius, fixed installation    | 7.5 x D  |
| Minimum bending radius, flexible installation | 10 x D   |
| Number of bending cycles                      | 1500000  |
| Bending radius                                | 79 mm  |
| Traversing path                               | 2 m  |
| Traversing rate                               | 2 m/s  |
| Cable weight                                  | 92 kg/km   |
| Outer sheath, material                        | PUR  |
| Material, inner sheath                        | PVC  |
| Material conductor insulation                 | PVC  |
| Conductor material                            | Bare Cu litz wires   |
| Nominal voltage, cable                        | 300 V  |
| Test voltage, cable                           | 2000 V   |
| Special properties                            | Silicone-free  |
| Flame resistance                              | DIN EN 50265   |
| Resistance to oil                             | according to VDE 0472 Part 803                             |
| Other resistance                              | Highly resistant to acids, alkaline solutions and solvents |
| Ambient temperature (operation)               | -40 °C ... 90 °C (cable, fixed installation)               |
|   | -5 °C ... 80 °C (cable, flexible installation)             |

### Environmental Product Compliance

|            |   |
|------------|---|
| REACH SVHC | Lead 7439-92-1  |
| China RoHS | Environmentally Friendly Use Period = 50 years  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings

# Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

Cable cross section



PUR/PVC black [PUR]

## Classifications

eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27440108 |
| eCl@ss 4.0    | 27140800 |
| eCl@ss 4.1    | 27140800 |
| eCl@ss 5.0    | 27143400 |
| eCl@ss 5.1    | 27250300 |
| eCl@ss 6.0    | 27279200 |
| eCl@ss 7.0    | 27279219 |
| eCl@ss 8.0    | 27279219 |
| eCl@ss 9.0    | 27440108 |

# Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000200 |
| ETIM 3.0 | EC001856 |
| ETIM 4.0 | EC002585 |
| ETIM 5.0 | EC002585 |
| ETIM 6.0 | EC002585 |
| ETIM 7.0 | EC002585 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11     | 31261501 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 19.0   | 31251501 |
| UNSPSC 20.0   | 31251501 |
| UNSPSC 21.0   | 31251501 |

## Approvals


### Approvals


#### Approvals

UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized

#### Ex Approvals

### Approval details

|                    |   |   |               |
|--------------------|---|---|---------------|
| UL Recognized      |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 118976 |
| Nominal voltage UN |   | 24 V  |               |

|                    |   |   |               |
|--------------------|---|---|---------------|
| cUL Recognized     |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 118976 |
| Nominal voltage UN |   | 24 V  |               |

# Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

## Approvals

|     |  |               |
|-----|--|---------------|
| EAC |  | EAC-Zulassung |
|-----|--|---------------|

|     |  |                          |
|-----|--|--------------------------|
| EAC |  | RU C-<br>DE.BL08.B.00511 |
|-----|--|--------------------------|

|                  |  |  |
|------------------|--|--|
| cULus Recognized |  |  |
|------------------|--|--|

## Accessories

### Accessories

#### Labeled terminal marker

##### Marker for terminal blocks - UC-TMF 10 CUS - 0824662



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 10.2 mm, lettering field size: 9.6 x 5.1 mm, Number of individual labels: 48

##### Marker for terminal blocks - UCT-TMF 10 CUS - 0829679



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 10.2 mm, lettering field size: 9.4 x 4.7 mm, Number of individual labels: 36

##### Marker for terminal blocks - UC-TMF 10 YE CUS - 0824668



Marker for terminal blocks, can be ordered: by sheet, yellow, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 10.2 mm, lettering field size: 9.6 x 5.1 mm, Number of individual labels: 48

## Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

### Accessories

Marker for terminal blocks - UCT-TMF 10 YE CUS - 0829682



Marker for terminal blocks, can be ordered: by sheet, yellow, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 10.2 mm, lettering field size: 9.4 x 4.7 mm, Number of individual labels: 36

---

### Screwdriver tools

Philips screwdriver - SZK PZ2 VDE - 1206463



Screwdriver, PZ crosshead, VDE insulated, size: PZ 2 x 100 mm, 2-component grip, with non-slip grip

---

Tool - SAC BIT HOOD-W 24 - 1212486



Nut for assembling pressure nuts with 24 mm wrench size, for 4 mm hexagonal drive

---

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

---

Screw insert - SF-BIT-PZ 2-50 - 1212592



Screw bit, PZ crosshead, E6.3-1/4" drive, size: PZ 2 x 50 mm, hardened, suitable for holder according to DIN 3126-F6.3/ISO 1173

---

### Terminal marking

## Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

### Accessories

#### Marker for terminal blocks - UC-TMF 10 - 0818124



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into flat marker groove, for terminal block width: 10.2 mm, lettering field size: 9.6 x 5.1 mm, Number of individual labels: 48

#### Marker for terminal blocks - UCT-TMF 10 - 0829204



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snap into flat marker groove, for terminal block width: 10.2 mm, lettering field size: 9.4 x 4.7 mm, Number of individual labels: 36

#### Marker for terminal blocks - UC-TMF 10 YE - 0818687



Marker for terminal blocks, Sheet, yellow, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into flat marker groove, for terminal block width: 10.2 mm, lettering field size: 9.6 x 5.1 mm, Number of individual labels: 48

#### Marker for terminal blocks - UCT-TMF 10 YE - 0829207



Marker for terminal blocks, Sheet, yellow, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snap into flat marker groove, for terminal block width: 10.2 mm, lettering field size: 9.4 x 4.7 mm, Number of individual labels: 36

### Torque tool

#### Torque screwdriver - TSD-M 1,2NM - 1212224



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm



## Connector hood - SACB-C-H180- 8/3-10,0PUR-M8 - 1516344

### Accessories

Torque screwdriver - TSD 25 SAC - 1212315



Torque screwdriver, with preset torque of 2.5 Nm and 4 mm hexagonal drive for the pressure nut of the connector hood

---

Torque screwdriver - TSD-M 3NM - 1212225



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 1.2 - 3 Nm

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Sensor Cables / Actuator Cables](#) category:*

*Click to view products by [Phoenix Contact](#) manufacturer:*

Other Similar products are found below :

[60963](#) [60964](#) [703000D02F2002](#) [703001D02F0602](#) [703001D02F300](#) [704000D02F120](#) [773032K02F030](#) [802027107404-1](#) [802027213811-1](#)  
[804001A09M150](#) [805001A09M0502](#) [84914-0235](#) [84914-0237](#) [885030A09M020](#) [8R4J30E03C3003](#) [1200651332](#) [1200651713](#) [1200660844](#)  
[1200660845](#) [1200661173](#) [1200680071](#) [1200720053](#) [1200720081](#) [1200720099](#) [1200720217](#) [1200800231](#) [1200860125](#) [1200870123](#)  
[1200980102](#) [1200650267](#) [1200650298](#) [1200660183](#) [1200660782](#) [1200660849](#) [1200661295](#) [1200661297](#) [1200661342](#) [1200661343](#)  
[1200670080](#) [1200670220](#) [1200680331](#) [1200720252](#) [1200730184](#) [1200860344](#) [1200870359](#) [1200870643](#) [1200980008](#) [1200980031](#)  
[1210502211](#) [1210400542](#)