

# Contact insert - RC-1RS1NRM0000 - 1603305

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Contact insert, number of positions: 16+2+PE, type of contact: Socket, Crimp connection

The figure shows the 6-pos. product version



## **Key Commercial Data**

| Packing unit           | 1 pc            |
|------------------------|-----------------|
| Minimum order quantity | 10 pc           |
| GTIN                   | 4 046356 244800 |
| GTIN                   | 4046356244800   |

#### Technical data

## General

| Insertion/withdrawal cycles mechanical             | 50                   |
|--|----------------------|
| Direction of rotation of contact chamber numbering | Standard             |
| Coding   | N                    |
| Contact connection method                          | Crimp connection     |
| Type of contacts                                   | Socket               |
| Number of positions                                | 19                   |
| Contact diameter of power contacts                 | 1.5 mm               |
| Litz wire cross section of power contacts min.     | 0.75 mm²             |
| Litz wire cross section of power contacts max.     | 1 mm²                |
| Nominal current per power contact at 25°C          | 10 A                 |
| Contact diameter of signal contacts                | 1 mm                 |
| Litz wire cross section of signal contacts min.    | 0.25 mm <sup>2</sup> |
| Litz wire cross section of signal contacts max.    | 0.5 mm <sup>2</sup>  |
| Nominal current per signal contact at 25°C         | 8 A                  |

Material



# Contact insert - RC-1RS1NRM0000 - 1603305

### Technical data

### Material

| Insulator material | PA66                        |
|--------------------|-----------------------------|
| Contact material   | CuZn                        |
| Contact surface    | Nickel-plated, gold coating |

## Specifications according to DIN EN 61984:2001

| Nominal / operating voltage of power contacts  | 150 V  |
|--|--------|
| Rated surge voltage of power contacts          | 1.5 kV |
| Overvoltage category of power contacts         | II     |
| Degree of pollution of power contacts          | 3      |
| Nominal / operating voltage of signal contacts | 150 V  |
| Overvoltage category of signal contacts        | II     |
| Degree of pollution of signal contacts         | 3      |

### **Environmental Product Compliance**


| REACh SVHC | Lead 7439-92-1  |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings

## Schematic diagram



## Schematic diagram



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Phoenix Contact manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 1604232 1R3006A20M005 RF-12P1N8A90DU 41-40011 42-00006 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01088 43-01203 41-40013 42-00008 43-00343 43-01026 43-01162 43-01173 43-10000 XS3P-M421-2 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-16213 43-01338 XS2RD4265 XS2R-D426-1