

# Panel mounting base - TU-00000004100 - 1605881

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Panel mounting base, straight, Bayonet locking, M23, Flat gasket, 4xM3, shielded: yes, panel thickness max.: 2.5 mm



## Key Commercial Data

Packing unit	20 pc
GTIN	4 046356 255431
GTIN	4046356255431

### Technical data

#### General

Note	Order information: Order contact inserts separately
Type of locking	Bayonet locking
Contact connection method	Crimp connection
Type of contacts	Socket
Pg housing screw connection	none
Mounting type	4x M3
Ambient conditions	
Ambient temperature	-20 °C 125 °C
Degree of protection	IP67
Material	
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Gasket and O-ring material	FPM
Specifications according to DIN EN 61984:2001	
Installation height max.	2000 m
Environmental Product Compliance	
REACh SVHC	Lead 7439-92-1



## Panel mounting base - TU-00000004100 - 1605881


## Technical data

#### **Environmental Product Compliance**

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Drawings

#### Dimensional drawing





**Dimensional drawing** 

Installation dimensions

Dimensional drawing

### Approvals

Approvals

Approvals EAC
Ex Approvals
Approval details

EAC **EAC** B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by Phoenix Contact manufacturer:

Other Similar products are found below :

600X518037X6STD15PCR99B70A8R4000A16M0208R5000A16M00512009100021203580030120091000812009100111300140094130203-005413001400261300150099RF-12S1N8A90DU1-3637-600-52051612618210368364148R4006A16M01016042321R3006A20M005RF-12P1N8A80DURF-12P1N8A90DU41-4001142-0000642-010154-22279-44-22281-14-22284-943-0011343-0108843-0120341-4001342-0000843-012643-0116243-0117343-10000XS3P-M421-2600X518050XSACC-DSI-FS-5P-PG9-L180 SC8R5006A16M0208R5006A16M0058R4000A16M0106-22279-31605332N03FA03144130014007743-1621343-01338XS2RD4265