

## Plug-in connector - CIOC 4-18-LI - 1701359

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Plug component, Nominal current: 5 A, Number of positions: 4, Pitch: 2.54 mm, Connection method: Insulation displacement connection QUICKON, Color: Black, Contact surface: Gold

### Product Features

- ✓ Gold-plated contact system
- ✓ The CIOC 4-18-LI plug can be combined with -LIH or -LIV base strips for a horizontal or vertical PCB connection
- ✓ The CIOC plug-in plug range is complemented by a 4-pos. link plug with 2.54 mm pitch
- ✓ A plug-in tap at any point in the bus and power cable can be achieved using two CIOC 4-18-LI plugs



### Key commercial data

Packing unit	1 PCE
Minimum order quantity	100 PCE
GTIN	 4 046356 030465
Custom tariff number	85366990
Country of origin	JAPAN

### Technical data

#### Dimensions / positions

Pitch	2.54 mm
Dimension a	7.62 mm
Number of positions	4

#### Technical data

Range of articles	CIOC-LINK
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	5 A

# Plug-in connector - CIOC 4-18-LI - 1701359

## Technical data

### Technical data

Nominal voltage $U_N$	160 V
Nominal cross section	0.75 mm <sup>2</sup>
Maximum load current	5 A
Insulating material	PA/PBT
Inflammability class according to UL 94	V0

### Connection data

Conductor cross section AWG/kcmil min.	18
Conductor cross section AWG/kcmil max	18

## Classifications

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002638
ETIM 5.0	EC002638

### UNSPSC

UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409
UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260705
eCl@ss 7.0	27440309

## Approvals

### Approvals

---

### Approvals

UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized

# Plug-in connector - CIOC 4-18-LI - 1701359

## Approvals

Ex Approvals

Approvals submitted

### Approval details

UL Recognized	
mm <sup>2</sup> /AWG/kcmil	18
Nominal current I <sub>N</sub>	5 A
Nominal voltage U <sub>N</sub>	160 V

cUL Recognized	
mm <sup>2</sup> /AWG/kcmil	18
Nominal current I <sub>N</sub>	5 A
Nominal voltage U <sub>N</sub>	160 V

GOST	
------	--


GOST	
------	--

cULus Recognized	
------------------	--

## Drawings

## Plug-in connector - CIOC 4-18-LI - 1701359

Dimensioned drawing



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [I/O Connectors](#) category:*

*Click to view products by [Phoenix Contact](#) manufacturer:*

Other Similar products are found below :

[571763P](#) [58098-0628](#) [61-168618-12P](#) [D38999/20FJ24PA L/C](#) [D38999/20FJ29SB L/C](#) [72.250.1628.2](#) [72.250.2428.2](#) [74720-0505](#) [747680210](#)  
[76.350.0729.0](#) [76871-1403](#) [FCN-244F080-G/1](#) [FCN-260A9920](#) [FCN-268D024-G/2F#10X-R10](#) [MP-5T180MUNNA-005](#) [MP-5XRJ45UNNB-](#)  
[003](#) [PCS-E50FA](#) [PCS-XE26LKA](#) [PCS-XE26MA+](#) [PCS-XES68MS+](#) [G38A71314B](#) [91-569719-35R](#) [9776-18-6](#) [DX40-50P\(55\)](#) [1571250010](#)  
[157-22500-3](#) [MS3471L14-19P L/C](#) [171224-6031](#) [1888020-8](#) [91-569786-35H](#) [91-569786-35M](#) [91-644626-35P](#) [172501-4002](#) [172501-6002](#)  
[FCN-260C008-A/L0](#) [FCN-260C024-AL0](#) [FCN-268D008-G/1K](#) [2000314-1](#) [200331-1](#) [2007498-2](#) [PCR-E28LMDAG1+](#) [PCR-E36FC+](#) [PCS-](#)  
[E28FS+](#) [PCS-XE26SLFD+](#) [PCS-XE26SLFDT+](#) [G38A71214B](#) [HDRA-E68W1LFDTC-SL+](#) [HDR-E14MSG1+](#) [R88A-CNK81S](#) [CRT1-](#)  
[ATT02](#)