

Plug - PTPM 0,2/ 2-P-2,5 - 1780477


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PCB connector, nominal current: 2 A, rated voltage (III/2): 160 V, number of positions: 2, pitch: 2.5 mm, connection method: IDC fast connection, color: black, contact surface: Tin

Your advantages

- Can be plugged into THR and SMD base strips
- Spring-cage and pierce contact technology
- Miniature plug with 2.5 mm pitch



Key Commercial Data

Packing unit	250 pc
GTIN	 4 046356 536127
GTIN	4046356536127

Technical data

Dimensions

Pitch	2.5 mm
Dimension a	2.5 mm

General

Range of articles	PTPM 0,2/..-P
Number of positions	2
Connection method	IDC fast connection
Insulating material group	III
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	40 V
Rated voltage (III/2)	160 V
Rated voltage (II/2)	160 V

Plug - PTPM 0,2/ 2-P-2,5 - 1780477

Technical data

General

Connection in acc. with standard	EN-VDE
Nominal current I_N	2 A
Nominal cross section	0.14 mm ²
Maximum load current	2 A
Insulating material	PA/PC
Flammability rating according to UL 94	V0/V2

Connection data

Conductor cross section flexible min.	0.14 mm ²
Conductor cross section flexible max.	0.14 mm ²
Conductor cross section AWG min.	26
Conductor cross section AWG max.	26
Maximum AWG according to UL/CUL	26
Wire diameter incl. insulation	1 mm (Terminal block is tested with PVC insulation - other insulation materials available on request)

Standards and Regulations


Connection in acc. with standard	EN-VDE
	CUL
Flammability rating according to UL 94	V0/V2

Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Diagram



Dimensional drawing



Derating curve for: PTPM 0,2/...-P-2,5 with PTSM 0,5/...-HH-2,5-THR R..

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [734-104](#) [734-302](#) [8-141-P](#) [8426620000](#) [860505](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#)
[PVP02-5,00](#) [PVP03-3,50](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFH16150](#) [ELFP03110](#)
[ELFP10210](#) [ELFT06250](#) [ELVP03100](#) [1700101](#) [1700410](#) [1700425](#) [1702246](#) [1705229](#) [1710175](#) [1714537](#) [1717806](#) [1719600](#) [1728941](#)
[1734692](#) [1734795](#) [1736036](#) [1740194](#) [1740291](#) [1740628](#) [1740990](#) [1746952](#) [1750207](#) [1752441](#) [1752865](#) [1754115](#) [1754144](#) [1756913](#)
[1760051](#) [1760336](#)