

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Half screw connection Pg21, made of plastic, consisting of rubber seal with one hole and one pressure screw, for type 2 - 4 housings, cable [mm] 9 - 13



### Key Commercial Data

Packing unit	5 рс
GTIN	4 017918 145989
GTIN	4017918145989

### Technical data

### Dimensions

Length	30 mm
Wrench size, union nut	33 mm
External cable diameter	9 mm 13 mm

#### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-20 °C 100 °C

### General

Note	Adapter screw connections are available on request for large cable dimensions, from Pg16 to Pg21 and from Pg21 to Pg29
Type of the screw connection	Half screw connection
No. of conductors	1
Material, pressure screw	Polyamide
Seal material	TPE
Sealing material	TPE
Shielded	no
Thread type on seal side	Pg21
Tightening torque, union nut	7.50 Nm



### Technical data

### Standards and Regulations

Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	• The products are suitable for applications in plant, controller, and electrical device engineering.
	• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
	Assembled products may not be manipulated or improperly opened.
	• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
	When using the product in direct connection with third-party manufacturers, the user is responsible.
	• For operating voltages > 50 V AC, conductive connector housings must be grounded
	Ensure that the protective or functional ground has been properly connected.
	• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
	Observe the corresponding technical data. You will find information:     o On the product     o On the packing label     o In the supplied documentation     o Online at phoenixcontact.com/products under the product
	Only use tools recommended by Phoenix Contact
	• The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
	• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
	Operate the connector only when it is fully plugged in.
	• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
	Observe the minimum bending radius of the cable. Lay the cable without twisting it.

## Classifications

eCl@ss

eCl@ss 10.0.1	27144432
	09/12/2020 Page 2 / 4



## Classifications

eCl@ss

eCl@ss 4.0	27141200
eCl@ss 4.1	27141200
eCl@ss 5.0	27149100
eCl@ss 5.1	27149100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149109
eCl@ss 8.0	27149109
eCl@ss 9.0	27144432

### ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441
ETIM 6.0	EC000441
ETIM 7.0	EC000441

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	39121311
UNSPSC 18.0	39121311
UNSPSC 19.0	39121311
UNSPSC 20.0	39121311
UNSPSC 21.0	39121311

## Approvals

Approvals

Approvals

EAC

### Ex Approvals

Approval details



EHC

### Approvals

EAC

B.01687

Accessories

Accessories

Half screw connection

Cable gland - VC-K-KV-PG21-O - 1885363



Half screw connection made of plastic with rubber seal without hole or for individual holes

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Mounting & Accessories category:

Click to view products by Phoenix Contact manufacturer:

Other Similar products are found below :

 582603-1
 009333-000
 727844N003
 747
 809090N001
 843188-000
 8666
 967279N002
 DB-11
 1300840039
 1300900096
 1301800416

 1302264450
 1300830184
 1300830729
 1300900039
 1301580036
 1301850553
 1301860939
 1302261315
 1302264431

 1337706-2
 APA18-AK
 1724
 1-787307-1
 185491N001
 1868
 HP-6N
 C-202-C
 202C221-13-0
 CA7308-000
 8S23-75FR-CS8184
 2684
 9648

 3089
 988382-000
 A72821-000
 AA401
 173506-000
 1823
 202C292-13-0
 202C302-13-0
 2109
 300625
 3330
 3412
 356247-1
 M9142

 M9143
 M9143
 M9143
 M9143
 M9144
 M91