

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Half screw connection Pg16, made of metal, consisting of rubber seal with one hole and one pressure screw, for type 1 housings, cable [mm] 7 - 10.5



# **Key Commercial Data**

Packing unit	5 pc	
Minimum order quantity	5 pc	
GTIN	4 017918 146320	
GTIN	4017918146320	

#### Technical data

#### **Dimensions**

Length	39.5 mm
Wrench size, union nut	24 mm
External cable diameter	7 mm 10.5 mm

#### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C 125 °C

#### General

Note	Adapter screw connections are available on request for large cable dimensions, from Pg16 to Pg21 and from Pg21 to Pg29	
No. of conductors	1	
Housing material	Metal	
Material, pressure screw	Nickel-plated brass	
Seal material	TPE	
Cable seal material	TPE	
Sealing material	TPE	
Shielded	no	



# Technical data

### General

Thread type on seal side	Pg16
Tightening torque, union nut	7.50 Nm

# Standards and Regulations

Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.			
	WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.			
	WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.			
	The products are suitable for applications in plant, controller, and electrical device engineering.			
	When operating the connectors in outdoor applications, they must be separately protected against environmental influences.			
	Assembled products may not be manipulated or improperly opened.			
	Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).			
	When using the product in direct connection with third-party manufacturers, the user is responsible.			
	For operating voltages > 50 V AC, conductive connector housings must be grounded			
	Ensure that the protective or functional ground has been properly connected.			
	VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector			
	Observe the corresponding technical data. You will find information:     On the product     On the packing label     o In the supplied documentation     Online at phoenixcontact.com/products under the product			
	Only use tools recommended by Phoenix Contact			
	The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.			
	Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products			
	Operate the connector only when it is fully plugged in.			
	Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.			
	Observe the minimum bending radius of the cable. Lay the cable without twisting it.			

**Environmental Product Compliance** 



# Technical data

### **Environmental Product Compliance**

REACh SVHC	Lead 7439-92-1	
China RoHS	Environmentally Friendly Use Period = 50 years	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

### Classifications

### eCl@ss

eCl@ss 10.0.1	27144432
eCl@ss 4.0	27141200
eCl@ss 4.1	27141200
eCl@ss 5.0	27149100
eCl@ss 5.1	27149100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149109
eCI@ss 8.0	27149109
eCl@ss 9.0	27144432

#### **ETIM**

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441
ETIM 6.0	EC000441
ETIM 7.0	EC000441

#### **UNSPSC**

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	39121311
UNSPSC 18.0	39121311
UNSPSC 19.0	39121311
UNSPSC 20.0	39121311
UNSPSC 21.0	39121311

### Approvals

### Approvals



Approvals			
Approvals			
EAC			
Ex Approvals			
Approval details			
EAC	EAC		B.01687

#### Accessories

Accessories

Half screw connection - VC-M-KV-PG21- 0 - 1854983



Half screw connection made of metal with rubber seal without hole for sealing or for individual holes

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Mounting & Accessories category:

Click to view products by Phoenix Contact manufacturer:

Other Similar products are found below:

582603-1 009333-000 727844N003 747 809090N001 843188-000 8666 967279N002 DB-11 1300840039 1300900096 1301800416

1302264450 1300830184 1300830729 1300900039 1301580036 1301850553 1301860939 1302000074 1302261315 1302264431

1337706-2 APA18-AK 1724 1-787307-1 185491N001 1868 HP-6N C-202-C 202C221-13-0 CA7308-000 8S23-75FR-CS8184 2684 9648

3089 988382-000 A72821-000 AA401 173506-000 1823 202C292-13-0 202C302-13-0 2109 300625 3330 3412 356247-1 M9142

M9143