

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Half screw connection Pg16, made of metal, consisting of rubber seal with one hole and one pressure screw, for type 1 housings, cable [mm] 11.5 - 15.5



Key Commercial Data

Packing unit	5 pc
GTIN	4 017918 146047
GTIN	4017918146047

Technical data

Dimensions

Length	24.7 mm
Wrench size, union nut	24 mm
External cable diameter	11.5 mm 15.5 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C 125 °C

General

Note	Adapter screw connections are available on request for large cable dimensions, from Pg16 to Pg21 and from Pg21 to Pg29	
No. of conductors	1	
Housing material	Metal	
Material, pressure screw	Nickel-plated brass	
Seal material	TPE	
Cable seal material	TPE	
Sealing material	TPE	
Shielded	no	
Thread type on seal side	Pg16	



Technical data

General

htening torque, union nut 7.50 Nm			
Standards and Regulations			
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.		
	WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.		
	WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.		
	The products are suitable for applications in plant, controller, and electrical device engineering.		
	When operating the connectors in outdoor applications, they must be separately protected against environmental influences.		
	Assembled products may not be manipulated or improperly opened.		
	Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).		
	When using the product in direct connection with third-party manufacturers, the user is responsible.		
	For operating voltages > 50 V AC, conductive connector housings must be grounded		
	Ensure that the protective or functional ground has been properly connected.		
	VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector		
	Observe the corresponding technical data. You will find information: On the product On the packing label In the supplied documentation Online at phoenixcontact.com/products under the product		
	Only use tools recommended by Phoenix Contact		
	The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.		
	Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products		
	Operate the connector only when it is fully plugged in.		
	Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.		
	Observe the minimum bending radius of the cable. Lay the cable without twisting it.		

REACh SVHC	Lead 7439-92-1



Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Classifications

eCl@ss

eCl@ss 10.0.1	27144432
eCl@ss 4.0	27141200
eCl@ss 4.1	27141200
eCI@ss 5.0	27149100
eCl@ss 5.1	27149100
eCl@ss 6.0	27149100
eCI@ss 7.0	27149109
eCl@ss 8.0	27149109
eCl@ss 9.0	27144432

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441
ETIM 6.0	EC000441
ETIM 7.0	EC000441

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	39121311
UNSPSC 18.0	39121311
UNSPSC 19.0	39121311
UNSPSC 20.0	39121311
UNSPSC 21.0	39121311

Approvals

Approvals

Approvals

EAC



Αp	proval	s
----	--------	---

Ex Approvals

Approval details

EAC

EAC

B.01687

Accessories

Accessories

Half screw connection - VC-M-KV-PG21- 0 - 1854983



Half screw connection made of metal with rubber seal without hole for sealing or for individual holes

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by Phoenix Contact manufacturer:

Other Similar products are found below:

1218 1300980012 1300980105 DBZM-6828 1498 915 300623 5632NM 1124 1151 561-MP6P4WH 5534M 9000005073 52104486
5315817 N16 025 0112 1 N16 020 0112 1 M6106 7422 NG-9516 Gasket N16 016 0112 1 NG-9514 Gasket 52006151 2704 BM4940L
BM4950L 1.097.2012.50 1.152.1300.01 1.152.2000.50 1.152.2100.01 1.152.2500.50 1.152.4000.50 1.209.1218.70 1.209.6400.71

1.609.1100.01 1.609.2900.15 1.609.3200.52 1.609.3600.15 1.609.5000.51 1.676.2500.50 52103150 53112705 53112715 53112735

53119073 54115405 52004120 52001894 53018160 APGPG36BA