

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Half screw connection Pg16, made of plastic, consisting of rubber seal with several holes (1 x 3 mm/2 x 8 mm) and a pressure screw, for cable screw connection support VC-M-KV-PG16....



Key Commercial Data

Packing unit	5 рс
Minimum order quantity	5 рс
GTIN	4 0 1 7 9 1 8 1 7 6 5 1 8
GTIN	4017918176518

Technical data

Dimensions

Length	24 mm
Wrench size, union nut	27 mm
External cable diameter	2.5 mm 3 mm (Cable 1)

Ambient conditions

Degree of protection (IP)	IP65
Ambient temperature (operation)	-20 °C 100 °C

General

Type of the screw connection	Half screw connection
No. of conductors	3
Material, pressure screw	Polyamide
Seal material	TPE
Sealing material	TPE
Shielded	no
Thread type on seal side	Pg16
Tightening torque, union nut	5.00 Nm



Technical data


Standards and Regulations

Safety note	 WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property. WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible. 	
	• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.	
	• The products are suitable for applications in plant, controller, and electrical device engineering.	
	• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.	
	Assembled products may not be manipulated or improperly opened.	
	• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).	
	 When using the product in direct connection with third-party manufacturers, the user is responsible. 	
	For operating voltages > 50 V AC, conductive connector housings be grounded Ensure that the protective or functional ground has been properly connected.	
	• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector	
	Observe the corresponding technical data. You will find information: o On the product o On the packing label o In the supplied documentation o Online at phoenixcontact.com/products under the product	
	Only use tools recommended by Phoenix Contact	
	• The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.	
	• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products	
	Operate the connector only when it is fully plugged in.	
	• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.	
	Observe the minimum bending radius of the cable. Lay the cable without twisting it.	

Drawings



Dimensional drawing



Classifications

eCl@ss

eCl@ss 10.0.1	27144432
eCl@ss 4.0	27141200
eCl@ss 4.1	27141200
eCl@ss 5.0	27149100
eCl@ss 5.1	27149100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149109
eCl@ss 8.0	27149109
eCl@ss 9.0	27144432

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441



Classifications

ETIM

ETIM 6.0	EC000441
ETIM 7.0	EC000441

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	39121311
UNSPSC 18.0	39121311
UNSPSC 19.0	39121311
UNSPSC 20.0	39121311
UNSPSC 21.0	39121311

Approvals

Approvals

Approvals		
EAC		
Ex Approvals		

Approval details

EAC	EAC		B.01687
-----	-----	--	---------

Accessories

Accessories

Half screw connection

Cable gland - VC-K-KV-PG21-O - 1885363



Half screw connection made of plastic with rubber seal without hole or for individual holes



Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by Phoenix Contact manufacturer:

Other Similar products are found below :

 1218
 1300980012
 1300980105
 DBZM-6828
 1498
 915
 300623
 5632NM
 1124
 1151
 561-MP6P4WH
 5534M
 5525
 9000005073
 52104486

 5315817
 N16 025 0112 1
 N16 020 0112 1
 M6106
 7422
 NG-9516 Gasket
 N16 016 0112 1
 NG-9514 Gasket
 52006151
 2704
 BM4940L

 BM4950L
 1.097.2012.50
 1.152.0900.01
 1.152.1300.01
 1.152.2000.50
 1.152.2500.50
 1.152.4000.50
 1.209.1218.70

 1.209.6400.71
 1.609.1100.01
 1.609.2900.15
 1.609.3200.52
 1.609.3600.15
 1.609.5000.51
 1.676.1600.51
 1.676.2500.50
 52103150

 53112705
 53112715
 53112735
 53119073
 54115405