

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail housing for use in distribution boards in accordance with DIN 43880, Lower housing part with base latch, width: 107.6 mm, height: 89.7 mm, depth: 48.9 mm, cross connection: DIN rail connector (optional), color: light gray (7035)

Your advantages

- ✔ Item is from the BC product range
- ✔ Conforms to DIN EN 43880
- ✔ Tool-free mounting
- ✔ Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- ✔ Inflammability class V0 according to UL 94
- ✔ Variety of connection technologies
- ✔ Can be mounted on the DIN rail or the wall
- ✔ Optional with bus connector for DIN rail mounting



Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	
GTIN	4055626282114

Technical data

Item properties

Brief article description	Mounting base housing
Type	BC 107,6 UT HBUS KMGY
Order No.	2202951
Housing type	DIN rail housing for use in distribution boards in accordance with DIN 43880
Type	Lower housing part with base latch
Max. IP code to attain	IP20
Mounting type	DIN rail mounting

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Technical data

Item properties

Ventilation openings present	no
------------------------------	----

Dimensions

Width [w]	107.6 mm
Height [h]	89.7 mm
Depth [d]	48.9 mm

Material data

Housing material	Polycarbonate
Color (RAL)	light gray (7035)
Flammability rating according to UL 94	V0

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport)	95 %

PCB data

Number of PCB holders	9
PCB thickness	1.4 mm ... 1.8 mm
Mounting position	Vertical (horizontal DIN rail)
Type of PCB mount	Latching

Power dissipation, single housing at 20 °C

Ambient temperature	20 °C
Reduction factor	1
Mounting position	vertical
Power dissipation	13.08 W

Power dissipation, single housing at 30 °C

Ambient temperature	30 °C
Reduction factor	0.84
Mounting position	vertical
Power dissipation	11 W

Power dissipation, single housing at 40 °C

Ambient temperature	40 °C
Reduction factor	0.72
Mounting position	vertical
Power dissipation	9.4 W

Power dissipation, single housing at 50 °C

Ambient temperature	50 °C
Reduction factor	0.6

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Technical data

Power dissipation, single housing at 50 °C

Mounting position	vertical
Power dissipation	7.85 W

Power dissipation, single housing at 60 °C

Ambient temperature	60 °C
Reduction factor	0.48
Mounting position	vertical
Power dissipation	6.3 W

Mechanical strength/tumbling barrel

Specification	IEC 60068-2-31:2008-05
Height of fall	50 cm
Number of drop cycles	50

Vibration test

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.15 mm (10 - 58.1 Hz)
Acceleration	2g (58.1 - 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis

Shock

Specification	IEC 60068-2-27:2008-02
Pulse shape	Half-sine
Acceleration	15g
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)

Test for assessing the risk of fire (glow wire)

Specification	DIN EN 60695-2-11 (VDE 0471-2-11):2014-11
Temperature	850 °C
Time of exposure	30 s

Degrees of protection provided by housings (IP code)

Specification	IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
Result, degree of protection, IP code	IP20

General information

Type of note	Assembly instruction:
Note	Refer to the data sheet for the range in the download area.

Packaging information

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Technical data

Packaging information

Type of packaging	packed in cardboard
Pieces per package	10
Denomination packing units	Pcs.
Outer packaging type	Carton

Standards and regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 10.0.1	27182702
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Classifications

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031
ETIM 7.0	EC001031

UNSPSC

UNSPSC 13.2	31261501
UNSPSC 18.0	31261501
UNSPSC 19.0	31261501
UNSPSC 20.0	31261501
UNSPSC 21.0	31261501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01687
-----	--	---------

Accessories

Accessories

Mounting material

Base latch - FUSSRIEGEL 14,4 L30 SPERR OG - 2896998



Component housing, Base latch, width: 14.4 mm, height: 29.8 mm, depth: 5.9 mm, color: orange (2003)

Necessary add-on products

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Accessories

Upper part of housing - BC 107,6 OT U11 KMGY - 2896076



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, Installation depth connection technology: 11.1 mm, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Upper part of housing - BC 107,6 OT U22 KMGY - 2896089



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, Installation depth connection technology: 22.35 mm, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Electronic housing - RPI-BC 107,6 DEV-KIT KMGY P10 - 2202875



DIN rail housing for Raspberry Pi computers (suitable for Raspberry Pi A+, B+, B2, B3, B4); set consisting of upper part, cover and PCB retainer; housing in accordance with DIN 43880

Upper part of housing - BC 107,6 OT U11 BK - 2200721



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, Installation depth connection technology: 11.1 mm, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: black (9005)

Upper part of housing - BC 107,6 OT 2000 KMGY - 1050443



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Accessories

Upper part of housing - BC 107,6 OT 1121 BK - 1108020



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: black (9005)

Upper part of housing - BC 107,6 OT U11 RD3000 - 2203809



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm

Upper part of housing - BC 107,6 OT 1112 KMGY - 1086268



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Upper part of housing - BC 107,6 OT U11 BK VPE80 - 1006943



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: black (9005)

Upper part of housing - BC 107,6 OT 0C0C0C0C KMGY - 1046365



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Accessories

Upper part of housing - BC 107,6 OT 0C0C0C0C BK - 1066143



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: black (9005)

Upper part of housing - BC 107,6 OT 0101 KMGY MOQ80 - 1065104



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Upper part of housing - BC 107,6 OT U22 BK - 2203763



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: black (9005)

Upper part of housing - BC 107,6 OT 1121 KMGY - 2203260



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Upper part of housing - BC 107,6 OT 000C0C KMGY VPE80 - 1025418



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Accessories

Upper part of housing - BC 107,6 OT 2121 KMGY - 1038850



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Upper part of housing - BC 107,6 OT 0121 KMGY - 2202301



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Upper part of housing - BC 107,6 OT U22 GY 7045 - 2202269



DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 107.6 mm, height: 89.7 mm, depth: 54.85 mm, color: gray

DIN rail bus connectors - HBUS 107,6-16P-1S BK - 2896306



DIN rail connector, number of positions: 16, pitch: 2.54 mm, color: jet black

Pin strip - PSTD 0,65X0,65/9-2,54 - 2200700



Pin strip, number of positions: 18, pitch: 2.54 mm

Additional products

Mounting base housing - BC 107,6 UT HBUS KMGY - 2202951

Accessories

DIN rail bus connectors - HBUS 107,6-16P-1S BK - 2896306



DIN rail connector, number of positions: 16, pitch: 2.54 mm, color: jet black

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Enclosures, Boxes & Cases](#) *category:*

Click to view products by [Phoenix Contact](#) *manufacturer:*

Other Similar products are found below :

[585-R-WH-PK](#) [M-10-PLATED](#) [60221-01](#) [60566-01-000](#) [HPL-9VB BATT DOOR](#) [M18-PLTD](#) [M-21-PLATED](#) [63310-01-000](#) [6711GSKT](#)
[71884-29-028](#) [LH45-100 Black](#) [72868-510-000](#) [CNS-0000 Black](#) [72883-510-000](#) [CNS-0101 Black](#) [72906-510-000](#) [CNS-0407 Black](#) [73092-](#)
[510-000](#) [CNM-0101 Black](#) [73105-510-000](#) [CNL-0101 Black](#) [73108-510-000](#) [CNL-0303 Black](#) [73395-510-039](#) [CNS-0006 Bone](#) [74257-510-000](#)
[CNL-0004](#) [MDC-1183-PLAIN-ALUM](#) [MDC-1183-PTD](#) [MDC-13104-PTD](#) [MDC-321-PTD](#) [MDC-973-PTD](#) [76](#) [77153-01-028](#) [FLX6030](#)
[83535-01-508](#) [90026-501-000](#) [PS36-200](#) [116-508](#) [120-407](#) [120-910](#) [127-908](#) [130-008](#) [1301170079](#) [1322GSKTEP](#) [1325GSKT3](#) [1434-1210](#)
[EAS-500 \(BLACK ANO\)](#) [1804RP-RB-PK](#) [190-005](#) [2202307](#) [KAB3321 BLACK](#) [KAB3421](#) [2697466](#) [S52213](#) [2901123](#) [2901699](#) [A0645271](#)
[A20P20](#) [2106-IR](#) [PERF-850-PLN](#)