

Electronic housing - DCS 15 M C O SLV C 7035 - 2203190

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Display housing, 15", light gray, central window, front level, with ventilation slots, cutout for connection technology angle plate, and VESA mount consisting of two half shells with screws

Your advantages

- ✓ Display housings for mobile and stationary operator panels
- ✓ Integration of TFT display and membrane keypads
- ✓ Degree of protection: up to IP54
- ✓ Temperature range: -20°C to +50°C
- ✓ Shock-resistant ABS plastic
- ✓ Flammability rating UL 94-V0



Key Commercial Data

Packing unit	4 pc
GTIN	 4 0 5 5 6 2 6 3 7 8 4 4 2
GTIN	4055626378442

Technical data

Item properties

Type	DCS 15 M C O SLV C 7035
Order No.	2203190
Housing type	Display housing
Max. IP code to attain	IP54
Mounting type	VESA 75/100
Battery compartment	no
Wall fastening	VESA 75/100
Ventilation openings present	yes

Measurements

Width [w]	362 mm
-------------	--------

Electronic housing - DCS 15 M C O SLV C 7035 - 2203190

Technical data

Measurements

Height [h]	286 mm
Depth [d]	62 mm
Diagonal	15 in. (Window for display)
Dimensions	306 mm x 230 mm (Window for display, center position)

Material specifications

Color (RAL)	light gray (7035)
Flammability rating according to UL 94	V0
Housing material	ABS

Packaging information

Pieces per package	4
Denomination packing units	Pcs.


Standards and regulations

Flammability rating according to UL 94	V0
--	----

Drawings

Electronic housing - DCS 15 M C O SLV C 7035 - 2203190

Dimensional drawing



Classifications

eCl@ss

eCl@ss 10.0.1	27182702
eCl@ss 5.1	27180506
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031

Electronic housing - DCS 15 M C O SLV C 7035 - 2203190

Classifications

ETIM

ETIM 7.0	EC001031
----------	----------

Accessories

Accessories

Screwdriver tools

Philips screwdriver - SF-PH 0-60 - 1212558



Screwdriver, PH crosshead, size: PH 0 x 60, 2-component grip, with non-slip grip

Additional products

Seal - DCS 15,0 SEAL - 2203586



Sealing set, including cord and O-rings

Display - D T 15,0 XGA L - 2203553



TFT module 15", 1024 x 768 pixels, transmissive/color, LED backlight, white, interface: LVDS, 8 bit, operating temperature: -20 °C ... 70 °C

Seal - DCS D-SEAL 3,0MM - 2203749



Sealing strip, self-adhesive, for displays of the DCS housing series (roll: 100 m)

Electronic housing - DCS 15 M C O SLV C 7035 - 2203190

Accessories

Washer/ring - DCS 15,0 WIN 2,5 CLEAR - 2203598



Acrylic glass, satin-finished, frame printed black, for display 800x480

Mounting brackets - DCS ADAPT CONNECT - 2203750



Connection technology adapters

Connecting plate - HS MP VESA75/100 DCS - 1082303



VESA 75/100 connection plate with M5 mounting kit for DCS 15" display support, die cast aluminum, 80 g

Holder - HS EH-B 140,5 DCS - 1082302



140.5 mm housing attachment, for max. load 10 kg, with ball joint and fastening plate 60 mm, pivotable in 15° increments, for 30 mm wall/profile bracket, material: black glass-fiber reinforced polycarbonate PC, and black anodized aluminum, 342 g

Holder - HS WM-S 75 DCS - 1082304



75 mm wall bracket, pivotable, with four 6.5 mm mounting holes and mounting diameter of 30 mm for housing attachment, black glass-fiber reinforced polycarbonate PC, and aluminum, 306 g

Electronic housing - DCS 15 M C O SLV C 7035 - 2203190

Accessories

Holder - HS PM-S 40 DCS - 1082305



Profile console for 40 mm aluminum profile, pivotable with mounting kit, bracket for housing attachment diameter 30 mm, material: black glass-fiber reinforced polycarbonate PC, and aluminum, 270 g

Mounting set - DCS D-FIX 15,0 - 2203831



Mounting set including plate and screws, for display mounting

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Enclosures, Boxes & Cases](#) *category:*

Click to view products by [Phoenix Contact](#) *manufacturer:*

Other Similar products are found below :

[585-R-WH-PK](#) [M-10-PLATED](#) [60221-01](#) [60566-01-000](#) [HPL-9VB BATT DOOR](#) [M18-PLTD](#) [M-21-PLATED](#) [63310-01-000](#) [6711GSKT](#)
[71884-29-028](#) [LH45-100 Black](#) [72868-510-000](#) [CNS-0000 Black](#) [72883-510-000](#) [CNS-0101 Black](#) [72906-510-000](#) [CNS-0407 Black](#) [73092-](#)
[510-000](#) [CNM-0101 Black](#) [73105-510-000](#) [CNL-0101 Black](#) [73108-510-000](#) [CNL-0303 Black](#) [73395-510-039](#) [CNS-0006 Bone](#) [74257-510-000](#)
[CNL-0004](#) [MDC-1183-PLAIN-ALUM](#) [MDC-1183-PTD](#) [MDC-13104-PTD](#) [MDC-321-PTD](#) [MDC-973-PTD](#) [76](#) [77153-01-028](#) [FLX6030](#)
[83535-01-508](#) [90026-501-000](#) [PS36-200](#) [116-508](#) [120-407](#) [120-910](#) [127-908](#) [130-008](#) [1301170079](#) [1322GSKTEP](#) [1325GSKT3](#) [1434-1210](#)
[EAS-500 \(BLACK ANO\)](#) [1804RP-RB-PK](#) [190-005](#) [2202307](#) [KAB3321 BLACK](#) [KAB3421](#) [2697466](#) [S52213](#) [2901123](#) [2901699](#) [A0645271](#)
[A20P20](#) [2106-IR](#) [PERF-850-PLN](#)