

Membrane keypad - KP HCS T-MAX K45 C4 P16 - 2203571


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Membrane keypad, self-adhesive, silver conduction technology, 45 keys, embossed, 4 colors, connection cable: 77 mm, with crimp female connector RM 2.54 mm, operating temperature -20 °C ... 70 °C



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 055626 528670 |
| GTIN | 4055626528670 |

Technical data

Product properties

| | |
|-----------------------|------------------------------|
| Type | KP HCS T-MAX K45 C4 P16 |
| Order No. | 2203571 |
| Mounting type | adhesive |
| Number of positions | 16 |
| Number of keys | 45 (9 x 5) |
| Number of socket pins | 16 |
| Technology | Conductive silver technology |
| Embossing | Dome embossing 11 x 11 mm |

Dimensions

| | |
|------------|------------------------|
| Dimensions | 144 mm x 78 mm |
| Pitch | 2.54 mm |
| Length | 77 mm (Membrane cable) |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Ambient temperature (operation) | -40 °C ... 80 °C |

Packaging details

Membrane keypad - KP HCS T-MAX K45 C4 P16 - 2203571

Technical data

Packaging details

| | |
|----------------------------|------|
| Pieces per package | 1 |
| Denomination packing units | Pcs. |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27182702 |
| eCl@ss 5.1 | 27180506 |
| eCl@ss 6.0 | 27180800 |
| eCl@ss 7.0 | 27182702 |
| eCl@ss 8.0 | 27182702 |
| eCl@ss 9.0 | 27182702 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC001031 |
| ETIM 6.0 | EC001031 |
| ETIM 7.0 | EC001031 |

Accessories

Additional products

Electronic housing - HCS-T MAXI 1W C C C 7035 - 2203142



Handheld housing, T-Maxi, light gray, consisting of two half shells with screws, front 1.1 mm recessed, with window and keypad slot

Electronic housing - HCS-T MAXI 1W C 1 1 7035 - 2203143



Handheld housing, T-Maxi, light gray, consisting of two half shells, two front plates with screws, front 1.1 mm recessed, with window and keypad slot

Electronic housing - HCS-T MAXI 1W 5AA 1 1 7035 - 2203144



Handheld housing T-Maxi light gray, comprising two half shells, two front lenses, screws. Front 1.1 mm recessed, with window and keyboard slot Battery compartment cover and battery contacts, for 5 AA batteries

Membrane keypad - KP HCS T-MAX K45 C4 P16 - 2203571

Accessories

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Input Devices](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[80260-00](#) [81485-28](#) [81521-08](#) [FKB4720-103](#) [84250-26](#) [84980-04](#) [84S-AC1-000](#) [JD-0700EU-2](#) [JM-0800-2](#) [JW-T0100](#) [89498-13](#) [89758-05](#)
[89886-26](#) [89941-00](#) [G80-3000LSCEU-2](#) [MJ0FGGRY](#) [JM-0800-0](#) [84S-BB1-004](#) [81601-26](#) [UL21KMZQ](#) [G8011900LPMUS0](#) [G84-](#)
[4700LUCUS-0](#) [81485-26](#) [84105-13](#) [V400-W24 5M](#) [V400-W23 5M](#) [G84-5200LCMEU-2](#) [DT2257X20V00GRY](#) [V400-W23P 5M](#)
[VW3A8151R20U](#) [V400-W24 15M](#) [LT1332D](#) [V400-W24 10M](#) [V400-W24P 15M](#) [V400-WM0 1M](#) [V400-W24P 10M](#) [V400-W23P 10M](#)
[TCS-1492OP](#) [V400-W23 3M](#) [LT1372D](#) [LP1007EXXH00R](#) [DT2253X20V00BLK](#) [100133BX](#) [EZ08-230013](#) [81248-04](#) [89887-26](#) [90215-00](#)
[HB110C3NWBNA](#) [9700001201](#) [80260-08](#)