

## Front adapters - FLKM 50/4-FLK14/PA-S115 - 2288561

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




VARIOFACE front adapter, for Siemens SIMATIC® S5-115U, 4x 8 channels can be connected

The figure shows versions FLKM 50-PA-S115/P and FLKM 50/4-FLK14/PA-S115



### Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 2 pc  |
| GTIN         | <br>4 017918 057084 |
| GTIN         | 4017918057084   |

### Technical data

#### General

|                                    |  |
|------------------------------------|--|
| Max. permissible operating voltage | < 50 V AC  |
|                                    | 60 V DC  |
| Max. permissible current           | 0.5 A (per path)                                       |
|                                    | 4 A (per connection, supply via separate power supply) |
| Max. permissible total current     | 3 A (per Byte, for supply via connector)               |
| Mounting position                  | any  |

#### Ambient conditions

|   |                  |
|---|------------------|
| Ambient temperature (operation)         | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

#### Standards and Regulations

|                                  |                         |
|----------------------------------|-------------------------|
| Connection in acc. with standard | CUL                     |
| Standards/regulations            | IEC 60664               |
|                                  | IEC 60664A              |
|                                  | DIN VDE 0110            |
|                                  | DIN VDE 0160 (in parts) |

## Front adapters - FLKM 50/4-FLK14/PA-S115 - 2288561

### Technical data

#### Standards and Regulations

|                      |    |
|----------------------|----|
| Degree of pollution  | 2  |
| Overvoltage category | II |

#### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Terminal Block Tools & Accessories](#) category:*

*Click to view products by [Phoenix Contact](#) manufacturer:*

Other Similar products are found below :

[00171430102](#) [00171420102](#) [600HL](#) [600RJ-07](#) [600RJ-11](#) [600RJ-14](#) [600RJS-10](#) [600RJS-12](#) [600RJS-15](#) [600RJS-21](#) [601RJ-09](#) [602SP](#) [602Z](#)  
[604J](#) [CSTSPC1-2](#) [7B941-7](#) [88943-2100](#) [QC102](#) [1437403-6](#) [1437403-9](#) [1437403-8](#) [1453128-1](#) [147832-1](#) [EC0037-000](#) [MT2/H--](#) [MT6/H-N](#)  
[MT6/V-GRND](#) [MT8/H-51-60](#) [BC2-12](#) [BCC-1-8/10](#) [EP2.5/4UN/BG](#) [1707755](#) [1735590](#) [1755480](#) [1789281](#) [1840227](#) [1840230](#) [2-1437402-1](#)  
[JA2-03](#) [JB1-03/J](#) [JB2-04](#) [JB2-05](#) [JB2-07](#) [JB2-09/J](#) [PARALLELJUMPERLINK](#) [JS601](#) [2204082](#) [2302463](#) [2305949](#) [8PCV-BUSHING](#)