

Touch panel - WP 3070W - 2400253

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 17.8 cm/7" TFT-display (analog resistive (polyester)), 800 x 480 Pixel(s) (WVGA), 262144 colors, ARM® Cortex®-A8, 1000 MHz, 2x USB host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Debian GNU/Linux and user software: Firefox Browser. (bus system: without)

Similar figure

Why buy this product

- ✓ For operational purposes only - the browser is the only interaction interface
- ✓ Flexible, thanks to open web standard and free choice of web server and visualization software
- ✓ No security updates are required for JAVA or Flash plug-ins thanks to HTML5
- ✓ HTML5-compatible browser integrated as standard in all devices
- ✓ Visualization of self-programmed JavaScript applications possible
- ✓ Display available in sizes from 14.5 cm (5.7") to 39.05 cm (15.4")
- ✓ Energy efficient due to LED backlighting
- ✓ Secure communication, thanks to SSL-encrypted data transmission



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626065168

Technical data

Dimensions

External dimension, width	203 mm
External dimension, height	147 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	195 mm
Installation dimension, height	139 mm
Installation dimension, depth	42 mm
Note regarding installation dimension	Installation cutout

Touch panel - WP 3070W - 2400253

Technical data

Display

Display	17.8 cm/7" TFT
Screen resolution	800 x 480 Pixel(s) (WVGA)
Backlighting	LED
Display backlight MTBF	40000 h
Touch technology	analog resistive (polyester)
Colors	262144 colors

Computer data

Processor	ARM® Cortex®-A8, 1000 MHz
Operating systems	Debian GNU/Linux
User software	Firefox Browser
RAM	512 MB RAM
	1 MB SRAM
Mass storage	NAND-Flash, 1 GB
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x USB host 2.0
Bus system	without
Slots	1x SD
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)

General

Material front plate	Aluminum (natural anodized)
Housing material	Steel sheet, zinc-plated
Mounting type	Front installation
Weight	800 g

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
	NEMA 4X
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	20 % ... 85 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Device supply

Supply voltage	24 V DC
Supply voltage range	18 V DC ... 30 V DC
Typical current consumption	typ. 0.4 A
Power consumption	typ. 9.6 W
Power supply unit	24 V DC ±20 %

Touch panel - WP 3070W - 2400253

Technical data

Standards and Regulations

Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 15;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed


Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approval details

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 205795
-----------	---	---	---------------

cUL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 205795
------------	---	---	---------------

cULus Listed			
--------------	---	--	--

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
 Flachsmarktstr. 8
 32825 Blomberg
 Germany
 Tel. +49 5235 300
 Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[1927221](#) [1936102](#) [3240366](#) [3240367](#) [1014246](#) [1014236](#) [1014240](#) [1014290](#) [1014293](#) [1806193](#) [1842254](#) [1768260](#) [1716373](#) [1648030](#)
[1579051](#) [1014235](#) [1014239](#) [1014229](#) [1212378](#) [0201391](#) [CRIMPFOX 16 S](#) [CRIMPFOX 25R](#) [CRIMPFOX 6H](#) [CRIMPFOX LC](#)
[CRIMPFOX-RCI 6-M](#) [7001438](#) [ETD-BL-1T-F-300S](#) [E/U](#) [MCR-4CLP-I-I-00](#) [MCR-DAC 8-I- 4-BUS](#) [MINI MCR-SL-R-UI](#) [FL EPA WMS](#)
[FLK 50/EZ-DR/ 400/KONFEK/S](#) [FLKM-D15 SUB/B](#) [FLS PB M12 DO 8 M12-2A](#) [PCV 6-16/ 2-G1-10 16](#) [921053](#) [PR1-RSC3-LV-120AC/21](#)
[PSM-ME-RS232/RS232-P](#) [PSM-SET-FSMA/4-KT](#) [PSM-STRIP-FC/PROFIB](#) [PSR-SCP- 24DC/TS/SDI8/SDIO](#) [PSR-SPP- 24DC/TS/M](#) [PT](#)
[2X2- 5DC-ST](#) [PT 4-FSI/F-LED 12](#) [1203534](#) [1206308](#) [1201455](#) [1207585](#) [QUINT-PS-100-240AC/24DC/40](#)