

Touch panel - TP 3150S - 2400458

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 38.1 cm/15" TFT-display (analog resistive (polyester)), 1024 x 768 pixel(s) (XGA), 65536 colors, Arm® Cortex®-A8, 800 MHz, 2x USB host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Windows® Embedded Compact 7 and user software: Visu+ / AX OPC Server. (bus system: without)


Similar figure

Your advantages

- ✓ Easy installation, low installation depth, and compact design
- ✓ Short startup time
- ✓ Visu+ RT and AX OPC server integrated as standard in all devices
- ✓ Easy IP address allocation and active connection monitoring thanks to PROFINET-Device according to Conformance Class B
- ✓ Display available in sizes from 14.5 cm (5.7") to 39.05 cm (15.4")
- ✓ Versatile communication options, even with third-party systems, thanks to numerous drivers and interfaces
- ✓ Energy efficient due to LED backlighting
- ✓ Acoustic warning from alarms via integrated buzzer (85 dB)



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 055626 055923 |
| GTIN | 4055626055923 |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|---|--|
| Outer dimensions: width, height, depth | 400 mm x 329 mm x 5 mm (Dimensions of the front plate) |
| Installation dimensions: width, height, depth | 372 mm x 301 mm x 55 mm (Installation cutout) |

Display

| | |
|--------------|-----------------|
| Display type | 38.1 cm/15" TFT |
|--------------|-----------------|

Touch panel - TP 3150S - 2400458

Technical data

Display

| | |
|------------------------|--|
| Screen resolution | 1024 x 768 Pixel(s) (XGA) |
| Touch technology | analog resistive (polyester) |
| Brightness | 480 cd/m ² typical (adjustable) |
| Backlighting | LED |
| Display backlight MTBF | 50000 h |
| Colors | 65536 colors |
| Reading angle left | 80 ° |
| Reading angle right | 80 ° |
| Reading angle top | 65 ° |
| Reading angle bottom | 80 ° |

Computer data

| | |
|-------------------------|---|
| Processor | Arm [®] Cortex [®] -A8, 800 MHz |
| Operating system | Windows [®] Embedded Compact 7 |
| User software | Visu+ |
| | AX OPC Server |
| RAM | 512 MB RAM |
| Mass storage | Flash, 1 GB |
| Network | 1 x Ethernet (10/100 Mbps), RJ45 |
| Interfaces | 2x USB Host 2.0 |
| Bus system | without |
| Slots | 1x SD |
| Realtime clock | Yes (battery-backed) |
| Service life of battery | 5 years (typical) |

General

| | |
|----------------------|-----------------------------|
| Material front plate | Aluminum (natural anodized) |
| Housing material | Steel sheet, zinc-plated |
| Mounting type | Front installation |
| Weight | 3000 g |

Ambient conditions

| | |
|--|--------------------------------|
| Degree of protection | IP65 (front), IP20 (back) |
| | NEMA 4X |
| Ambient temperature (operation) | 0 °C ... 50 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 85 % (non-condensing) |
| Permissible humidity (storage/transport) | 20 % ... 85 % (non-condensing) |
| Vibration (operation) | DIN EN 60068-2-6 |
| Shock | DIN EN 60068-2-27 |

Device supply

| | |
|----------------|---------|
| Supply voltage | 24 V DC |
|----------------|---------|

Touch panel - TP 3150S - 2400458

Technical data

Device supply

| | |
|-----------------------------|---------------------|
| Supply voltage range | 18 V DC ... 30 V DC |
| Typical current consumption | 0.6 A |
| Power consumption | typ. 14.4 W |
| Power supply unit | 24 V DC ±20 % |

Standards and Regulations

| | |
|-----------------------|-------------------|
| Shock | DIN EN 60068-2-27 |
| Vibration (operation) | DIN EN 60068-2-6 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 15; |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27330201 |
| eCl@ss 4.0 | 27330200 |
| eCl@ss 4.1 | 27330200 |
| eCl@ss 5.0 | 27330200 |
| eCl@ss 5.1 | 27330200 |
| eCl@ss 6.0 | 27242300 |
| eCl@ss 7.0 | 27242302 |
| eCl@ss 8.0 | 27242302 |
| eCl@ss 9.0 | 27330201 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC001412 |
| ETIM 5.0 | EC001412 |
| ETIM 6.0 | EC001412 |
| ETIM 7.0 | EC001412 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 43211904 |
| UNSPSC 18.0 | 43211904 |
| UNSPSC 19.0 | 43211904 |
| UNSPSC 20.0 | 43211904 |
| UNSPSC 21.0 | 43211904 |

Touch panel - TP 3150S - 2400458

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approval details

| | | | |
|-----------|--|---|---------------|
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 205795 |
|-----------|--|---|---------------|

| | | | |
|------------|--|---|---------------|
| cUL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 205795 |
|------------|--|---|---------------|

| | | | |
|--------------|--|--|--|
| cULus Listed | | | |
|--------------|--|--|--|

Accessories

Accessories

Battery module

Battery / accumulator - HMI BATTERY - 2701383

Lithium battery



Mounting material

Mounting material - HMI SCB MOUNTING KIT 4 - 2701384



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

Touch panel - TP 3150S - 2400458

Accessories

Mounting material - HMI SCB MOUNTING KIT 6 - 2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

Mounting material - HMI SCB MOUNTING KIT 8 - 2701387



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

Operating stylus

Touch pen - TOUCH PEN - 2701379



Touch pen for analog-resistive HMIs, silver coated. Delivery includes self-adhesive pen holder.

Parameterization memory

Program / configuration memory - SD FLASH 2GB - 2988162



Program and configuration memory, for extending the internal flash memory, pluggable, 2 GB.

PCB plug

Printed-circuit board connector - MC 1,5/ 3-STF-3,5 BD:1-3 - 1751312



PCB connector, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 3, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin

Touch panel - TP 3150S - 2400458

Accessories

Protective foil

Protective foil - 15,0" DISPLAY PROTECTIVE FOIL - 2701378

Protective film set comprising 10 pieces of film for a 15" display. Including a squeegee to apply film and instructions.



Storage medium

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [TFT Displays & Accessories](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[F3ET2-005-150](#) [HDA430T-3G1H](#) [NB7W-KBA04](#) [NB-ATT01](#) [NB5Q-ATT01](#) [NB5Q-KBA04](#) [NB-CN001](#) [OAI-80038AA-2008-A](#) [315-U004B15300](#) [UMSH-8596MD-34T \(REV D\)](#) [TCG121WXLRXVNNANX35](#) [EIC-LCD-1080P](#) [T-55619GD065J-LW-ABN](#)
[TCG104SVLPEANN-AN30](#) [NL6448BC33-70](#) [NL6448BC20-30D](#) [NL10276BC16-06](#) [NL192108AC10-01D](#) [NL12880BC20-05BD](#)
[NL8060BC26-35BA](#) [NL8060BC31-50F](#) [TM070DDHG03-40](#) [PTPW16-070WV1S02](#) [PTPW17-070WV1S02](#) [PTPW16-084SV1S02](#)
[MTD0300ECP06DF-1](#) [DEM 320240T VMX-PW-N \(A-TOUCH\)](#) [DEM 480128B TMH-PW-N \(A-TOUCH\)](#) [DEM 480272P VMX-PW-N \(C-TOUCH\)](#) [DEM 480272Q VMX-PW-N \(A-TOUCH\)](#) [DEM 480272Q VMX-PW-N \(C-TOUCH\)](#) [DEM 640480E TMH-PW-N \(A-TOUCH\)](#)
[DEM 800480K1 TMH-PW-N \(A-TOUCH\)](#) [DEM 800480K1 TMH-PW-N \(C-TOUCH\)](#) [DEM 800480K2 TMH-PW-N \(A-TOUCH\)](#) [DEM 800480K3 TMH-PW-N \(C-TOUCH\)](#) [DEM 800480K4 TMH-PW-N \(A-TOUCH\)](#) [DEM 800480K4 TMH-PW-N \(C-TOUCH\)](#) [4DLCD-35480320-CTP-IPS](#) [4DLCD-35480320-IPS](#) [4DLCD-35480320-RTP-IPS](#) [4DLCD-50800480-CTP-IPS](#) [RFA6400E-AWH-DNG](#) [RFA6400E-AWH-MNN](#) [RFE430V-AZW-DNS](#) [RFF70VA2-1IW-DHS](#) [RFH700A8-AYH-MNN](#) [RFK101VF-1YH-LHG](#) [RFS390C-AIW-DNN](#) [RFS390C-AIW-DNS](#)