

Touch panel - WP 15T - 2700935

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Touch panel with 38.1 cm/15" TFT-display (analog resistive (polyester)), 1024 x 768 pixel(s) (XGA), 65536 colors, Arm9™, 200 MHz, 2x USB host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Windows CE 5.0 and user software: MicroBrowser. (bus system: without)

Your advantages

- Short startup time
- Easy installation, low installation depth, and compact design
- Micro browser (WebVisit client) integrated as standard in all devices
- Display available in sizes from 8.9 cm (3.5") to 38.1 cm (15")
- Easy device replacement - the visualization project is saved on the PLC (web server)
- Energy efficient due to LED backlighting



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 665711 |
| GTIN | 4046356665711 |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|---|--|
| Outer dimensions: width, height, depth | 400 mm x 329 mm x 5 mm (Dimensions of the front plate) |
| Installation dimensions: width, height, depth | 374 mm x 303 mm x 60 mm |

Display

| | |
|-------------------|--|
| Display type | 38.1 cm/15" TFT |
| Screen resolution | 1024 x 768 Pixel(s) (XGA) |
| Touch technology | analog resistive (polyester) |
| Brightness | 480 cd/m ² typical (adjustable) |

Touch panel - WP 15T - 2700935

Technical data

Display

| | |
|------------------------|--------------|
| Backlighting | LED |
| Display backlight MTBF | 50000 h |
| Colors | 65536 colors |

Computer data

| | |
|------------------|----------------------------------|
| Processor | Arm9™, 200 MHz |
| Operating system | Windows® CE 5.0 |
| User software | MicroBrowser |
| RAM | 64 MB SDRAM |
| Mass storage | Flash, 32 MB |
| Network | 1 x Ethernet (10/100 Mbps), RJ45 |
| Interfaces | 2x USB Host 2.0 |
| Bus system | without |

General

| | |
|----------------------|-----------------------------|
| Material front plate | Aluminum (natural anodized) |
| Housing material | Steel sheet, zinc-plated |
| Mounting type | Front installation |
| Weight | 2300 g |

Ambient conditions

| | |
|--|--------------------------------|
| Degree of protection | IP65 (front), IP20 (back) |
| | NEMA 4X |
| Ambient temperature (operation) | 0 °C ... 50 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 85 % (non-condensing) |
| Permissible humidity (storage/transport) | 20 % ... 85 % (non-condensing) |
| Vibration (operation) | DIN EN 60068-2-6 |
| Shock | DIN EN 60068-2-27 |

Device supply

| | |
|-----------------------------|---------------|
| Typical current consumption | 1 A |
| Power consumption | typ. 24 W |
| Power supply unit | 24 V DC ±20 % |

Standards and Regulations

| | |
|-----------------------|-------------------|
| Shock | DIN EN 60068-2-27 |
| Vibration (operation) | DIN EN 60068-2-6 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 15; |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Touch panel - WP 15T - 2700935

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27330201 |
| eCl@ss 4.0 | 27330200 |
| eCl@ss 4.1 | 27330200 |
| eCl@ss 5.0 | 27330200 |
| eCl@ss 5.1 | 27330200 |
| eCl@ss 6.0 | 27242300 |
| eCl@ss 7.0 | 27242302 |
| eCl@ss 8.0 | 27242302 |
| eCl@ss 9.0 | 27330201 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001435 |
| ETIM 4.0 | EC001412 |
| ETIM 5.0 | EC001412 |
| ETIM 6.0 | EC001412 |
| ETIM 7.0 | EC001412 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43232401 |
| UNSPSC 13.2 | 43211904 |
| UNSPSC 18.0 | 43211904 |
| UNSPSC 19.0 | 43211904 |
| UNSPSC 20.0 | 43211904 |
| UNSPSC 21.0 | 43211904 |

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / EAC-RoHS / EAC / cULus Listed

Ex Approvals

Approval details

Touch panel - WP 15T - 2700935

Approvals

| | | | |
|--------------|--|---|---------------------------|
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 205795 |
| cUL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 205795 |
| EAC | | | RU *- DE.A*30.B.00238 |
| EAC-RoHS | | | RU* - DE*35.B.00394/20 |
| EAC | | | EAC-Zulassung |
| cULus Listed | | | |

Accessories

Accessories

Battery module

Battery / accumulator - HMI BATTERY - 2701383

Lithium battery



Mounting material

Touch panel - WP 15T - 2700935

Accessories

Mounting material - HMI WALL MOUNTING KIT - 2701380

HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.



Mounting material - HMI SCB MOUNTING KIT 4 - 2701384

HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.



Mounting material - HMI SCB MOUNTING KIT 6 - 2701385

HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.



Mounting material - HMI SCB MOUNTING KIT 8 - 2701387

HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.



Operating stylus

Touch pen - TOUCH PEN - 2701379

Touch pen for analog-resistive HMIs, silver coated. Delivery includes self-adhesive pen holder.



PCB plug

Touch panel - WP 15T - 2700935

Accessories

Printed-circuit board connector - MSTB 2,5/ 3-STF BD:1-3 - 1896381

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 3, pitch: 5 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin



Protective foil

Protective foil - 15,0" DISPLAY PROTECTIVE FOIL - 2701378

Protective film set comprising 10 pieces of film for a 15" display. Including a squeegee to apply film and instructions.



Storage medium

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Displays & Accessories](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[LTC-2721WC](#) [LTC-4624JD](#) [LTC-4627WC](#) [LTC-571P](#) [LTM-8522G](#) [LTP-4323P](#) [LTP-747G](#) [LTS-3361JG-06](#) [ELS-316SYGWA/S530-E2](#)
[1668](#) [HT-F196NB-5323](#) [IPD2131-27](#) [SA03-12EWA](#) [LDQ-N514RI](#) [LDS-A3506RD](#) [LDS-A3926RI](#) [SC03-12HDB](#) [SI-B9T151550WW](#) [SI-](#)
[B9V171550WW](#) [SLC-3PF-WL](#) [SLDN-32M-G](#) [1624](#) [LTC-2623WC](#) [LTC-4627JD](#) [LTD-322G](#) [LTD-482PC](#) [LTP-1057AHR](#) [LTP-1457AKR](#)
[LTP-3784G-01](#) [LTS-313AP](#) [LTS-4812SKR-P](#) [LTS-547AE](#) [LTS-6780P](#) [446010401-3](#) [HV-7W30-6829](#) [DA43-11GWA](#) [LDD-A516RI-17](#)
[LDD-E305RI](#) [LDQ-N3402RI](#) [LDQ-N3606RI](#) [LDT-M2804RI](#) [86004CB830](#) [LTP-3862JD](#) [LTP-2088AKD](#) [LTD-6740P](#) [LTS-6880Y](#) [LDS-](#)
[SMC3002RISUGTR](#) [LTC-2623E](#) [CC25-12YWA](#) [LDM-6432-P3-UR-1](#)