

Installation remote bus cable - IBS INBC METER/E - 2723152


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



By the meter, Installation remote bus cable, INTERBUS, shielded, PVC/PVC, black RAL 9005, 9-wire (3 x 2 x 0.22 mm² + 3 x 1 mm²), color single wire: green-yellow, white-brown, gray-pink, red, blue, green/yellow, for underground runs



Key Commercial Data

Packing unit	1 M
GTIN	 4 017918 141288
GTIN	4017918141288

Technical data

General data

Number of positions	9
Alternative short product description	Installation remote bus cable

Cable

Signal type/category	INTERBUS
Cable structure	3 x 2 x 0.22 mm ² + 3 x 1 mm ²
Conductor cross section	3x 2x 0.22 mm ² (Data) 3x 1 mm ² (Supply)
Conductor structure signal line	7x 0.20 mm
Conductor structure, voltage supply	14x 0.30 mm
Core diameter including insulation	1 mm (Data) 1.7 mm (Supply)
Wire colors	green-yellow, white-brown, gray-pink, red, blue, green/yellow
Twisted pairs	2 cores to the pair
Overall twist	3 pairs and 3 wires to form the core
Shielding	Tinned copper braided shield
External sheath, color	black RAL 9005
Inner sheath thickness	0.9 mm

Installation remote bus cable - IBS INBC METER/E - 2723152

Technical data

Cable

External cable diameter D	9.7 mm ±0.3 mm
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	15 x D
Outer sheath, material	PVC
Material, inner sheath	PVC
Material conductor insulation	PE
Conductor material	Bare Cu litz wires
Insulation resistance	≥ 5 GΩ*km (Data)
	≥ 5 GΩ*km (Supply)
Loop resistance	≤ 186.00 Ω/km (Data)
	≤ 19.50 Ω/km (Supply)
Cable capacity	≤ 60 nF/km (At 800 Hz)
Wave impedance	110 Ω ±20 Ω (at 64 kHz)
	95 Ω ±15 Ω (at >1 MHz)
Near end crosstalk attenuation (NEXT)	≥ 61 dB (at 772 kHz)
	≥ 59 dB (with 1 MHz)
	≥ 55 dB (at 2 MHz)
	≥ 50 dB (at 4 MHz)
	≥ 46 dB (at 8 MHz)
	≥ 44 dB (at 10 MHz)
	≥ 41 dB (at 16 MHz)
	≥ 40 dB (at 20 MHz)
Attenuation	≤ 10 dB/km (at 256 kHz)
	≤ 25 dB/km (at 772 kHz)
	≤ 28 dB/km (with 1 MHz)
	≤ 69 dB/km (at 4 MHz)
	≤ 12 dB/km (at 10 MHz)
	≤ 15.5 dB/km (at 16 MHz)
	≤ 17.2 dB/km (at 20 MHz)
Signal speed	0.66 c
Coupling resistance	< 250.00 mΩ/m (at 30 MHz)
Nominal voltage, cable	250 V (Peak value, not for high-power applications)
	450 V (Supply)
Test voltage Core/Core	1500 V _{rms}
Test voltage Core/Shield	1000 V _{rms}
Flame resistance	according to VDE 0472, Part 804, test type B
	according to IEC 60332-1
Ambient temperature (operation)	-30 °C ... 70 °C (cable, fixed installation)
	-5 °C ... 70 °C (cable, flexible installation)

Environmental Product Compliance

Installation remote bus cable - IBS INBC METER/E - 2723152

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27060390
eCl@ss 4.0	24010400
eCl@ss 4.1	24010400
eCl@ss 5.0	19030300
eCl@ss 5.1	19030300
eCl@ss 6.0	27061800
eCl@ss 7.0	27061801
eCl@ss 8.0	27061801
eCl@ss 9.0	27061801

ETIM

ETIM 2.0	EC000304
ETIM 3.0	EC000830
ETIM 4.0	EC000830
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	26121604
UNSPSC 18.0	26121604
UNSPSC 19.0	26121604
UNSPSC 20.0	26121604
UNSPSC 21.0	26121604

Approvals

Approvals

Approvals

INTERBUS CLUB / EAC-RoHS

Installation remote bus cable - IBS INBC METER/E - 2723152

Approvals

Ex Approvals

Approval details

INTERBUS CLUB	113/27.05.97
---------------	--------------

EAC-RoHS		RU D- DE.HB35.B.00371
----------	---	--------------------------

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antennas](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[GAN30084EU](#) [930-033-R](#) [GW17.07.0250E](#) [1513563-1](#) [EXE902SM](#) [APAMPG-117](#) [MAF94383](#) [W3908B0100](#) [W6102B0100](#) [YE572113-30RSMM](#) [108-00014-50](#) [66089-2406](#) [A09-F8NF-M](#) [A09-F5NF-M](#) [RGFRA1903041A1T](#) [W3593B0100](#) [W3921B0100](#) [SIMNA-868](#) [SIMNA-915](#) [SIMNA-433](#) [W1044](#) [W1049B090](#) [A75-001](#) [WTL2449CQ1-FRSMM](#) [CPL9C](#) [EXB148BN](#) [0600-00060](#) [TRA9020S3PBN-001](#) [GD5W-28P-NF](#) [MA9-7N](#) [GD53-25](#) [GD5W-21P-NF](#) [EXB144SM](#) [C37](#) [MAF94051](#) [P1744](#) [MA9-5N](#) [EXD420PL](#) [B1322NR](#) [QWFTB120](#) [MAF94271](#) [MAF94300](#) [GPSMB301](#) [FG4403](#) [AO-AGSM-OM54](#) [5200232](#) [MIKROE-2349](#) [WCM.01.0111](#) [MIKROE-2393](#) [MIKROE-2352](#)