

I/O module - IBS IP CDIO/R 24-12/4/8-SF - 2730077

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Digital input/output module, for use on robots, IP65 protection, 12 inputs, 24 V DC, 4-wire connection technology and 4 outputs, 24 V DC, 0.5 A/2 A, 3-wire connection technology, connection of additional signals on the back of the module

The figure shows version IBS IP CDIO/R 24-8

Product Description

The IBS IP CDIO/R 24... modules are available as an input/output unit for the robot concept. The metal housing allows them to be used in welding applications. The module can be used directly on the welding transformer if it is mounted on a terminal box. The modules are connected via a 17-pin circular connector. In addition to the INTERBUS and power supply lines, this connector also carries two further signal lines for constant current regulation (CCR) and for secondary circuit monitoring (SCM). These signals are looped in on the underside of the .../SF devices and are needed at the welding current controller for control and monitoring tasks. Two module types are available: The IBS IP CDIO/R 24-8 ... module has 8 channels that can be used either as inputs or as outputs. The IBS IP CDIO/R 24-12/4/8 .. module has 12 inputs and 4 outputs.

Your advantages

- 12 digital inputs
- 4 digital outputs
- Diagnostic and status indicators



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4017918437312

Technical data

Ambient conditions

Degree of protection	IP65
----------------------	------

Interfaces

Interface	Installation remote bus
-----------	-------------------------

Power supply

Residual ripple	3.6 V _{pp}
-----------------	---------------------

I/O module - IBS IP CDIO/R 24-12/4/8-SF - 2730077

Technical data

Electrical isolation

Test section	Supply voltage US1; sensor supply 500 V AC 50 Hz 1 min.
	Supply voltage US2 500 V AC 50 Hz 1 min.
	Bus logic, incoming and outgoing remote bus 500 V AC 50 Hz 1 min.

Inputs

Number of inputs	12
Connection technology	4-wire
Input voltage	24 V DC
Input voltage range "0" signal	-30 V ... 5 V
Input voltage range "1" signal	13 V ... 30 V

Outputs

Number of outputs	4
Connection technology	3-conductor (shielded)
Type of protection	Short-circuit protection, polarity reversal protection

General

Weight	800 g
--------	-------

Standards and Regulations

Connection in acc. with standard	CUL
----------------------------------	-----

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Classifications

eCl@ss

eCl@ss 10.0.1	27242604
eCl@ss 4.0	27250300
eCl@ss 4.1	27250300
eCl@ss 5.0	27250300
eCl@ss 5.1	27242600
eCl@ss 6.0	27242600
eCl@ss 7.0	27242604
eCl@ss 8.0	27242604
eCl@ss 9.0	27242604

ETIM

ETIM 2.0	EC001430
ETIM 3.0	EC001599
ETIM 4.0	EC001599
ETIM 5.0	EC001599
ETIM 6.0	EC001599

I/O module - IBS IP CDIO/R 24-12/4/8-SF - 2730077

Classifications

ETIM

ETIM 7.0	EC001599
----------	----------

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	32151602
UNSPSC 18.0	32151602
UNSPSC 19.0	32151602
UNSPSC 20.0	32151602
UNSPSC 21.0	32151602

Accessories

Accessories

Circular connector (cable-side)

Cable connector - TGGM/CDIO/17-ST - 1667895



INTERBUS remote bus connectors, straight, with contacts 12x 1597862, 5x 1602996, with IP68 cable gland Pg16, pin contact insert

Cable connector - TGGM/CDIO/17-BU - 1667905



INTERBUS remote bus connector, straight, with contacts 12x 1599600, 5x 1602998, with IP68 cable gland Pg16, socket contact insert

Cable connector - TWGM/CDIO/17-ST - 1667950



INTERBUS remote bus connector, angled, with contacts, male contact insert

I/O module - IBS IP CDIO/R 24-12/4/8-SF - 2730077

Accessories

Cable connector - TWGM/CDIO/17-BU - 1667963



INTERBUS remote bus connector, angled, with contacts, female contact insert

Protective cap

Protective cap - MSK 2 - 1665907



M23 metal sealing cap, for unoccupied M23 connectors, with steel wire

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Modules](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[70L-IDC5S](#) [70L-OAC-L](#) [70Z3289-4](#) [G21960000700](#) [G21960002700](#) [G34960002700](#) [G88104401](#) [OACU](#) [C4SWOUT](#) [PB16H](#)
[G34960001700](#) [G3TA-OA101SZ-1](#) [DC24](#) [G77-S](#) [G78-16-E](#) [5607189](#) [DA5](#) [ODC-24A](#) [IDC5P](#) [FC6A-N16B1](#) [6421](#) [70MRCQ32-HL](#)
[G3TAOD201SDC24](#) [C200H-LK201-V1](#) [G3TA-OA202SZ-US](#) [DC12](#) [GT1-OD16](#) [GT1-AD04CST](#) [B7AM-6BS](#) [70GRCQ24-HS](#) [6422](#)
[84110410](#) [GT1-OD16MX](#) [G7VC-OC16-B7](#) [70MRCK24-DIN](#) [6202](#) [6402](#) [PI/NI-2D/24](#) [FC6A-J2C1](#) [FC6A-KC1C](#) [FC6A-R081](#) [FC6A-](#)
[J8CU1](#) [GP32900003700](#) [641-480-5022](#) [PB16H](#) [84145010](#) [84110210](#) [FRUSB1601](#) [PCL-720+-BE](#) [FRRJ451601](#) [AP24MX3DB25F](#) [ADAM-](#)
[5053S-AE](#)