

## ECO link - PB ECO LINK - 2741480

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PROFIBUS ECO Link, RS-232 (V.24) PROFIBUS converter, incl. software for PC

### Product Description

The PROFIBUS master simulator is a simple and universal tool for the exchange of data with PROFIBUS slaves from almost all manufacturers via PROFIBUS-DP. The PROFIBUS master simulator can exchange data with numerous PROFIBUS slaves even without device master file, type file, and PROFIBUS master data. Of course, the PROFIBUS-DP master simulator also enables the use of device master files to start data exchange with PROFIBUS slaves. It is also possible to address PROFIBUS slaves. The PROFIBUS master simulator also provides the option of searching a PROFIBUS line to detect all connected devices and of displaying the result in graphical form. Output data can be transmitted consistently. When using the keyboard, it is possible to keep the outputs set for as long as the mouse button is pressed. The interface converter is supplied with voltage by the PROFIBUS interface itself. This makes it ideal for mobile use in a laptop or notebook. The interface converter is simply connected between PROFIBUS and the RS-232 cable. The PROFIBUS master simulator is a testing device and a startup tool for PROFIBUS slaves and is therefore not suitable for controlling automation processes. The interface converter for connection between the RS-232 interface of the PC and PROFIBUS is supplied as standard with the PROFIBUS master simulator. A connecting cable to the PC is also supplied together with the software itself on floppy disks.



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 190859
GTIN	4017918190859

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Ambient conditions

Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

#### Data interfaces

Interface	PROFIBUS (in acc. with DIN 19245, part 3)
Connection method	9-pos. D-SUB male

# ECO link - PB ECO LINK - 2741480

## Technical data

### Data interfaces

Interface	RS-232
Connection method	9-pos. D-SUB socket
Transmission speed	19200 bit (baud)
User interface	PROFIBUS-DP master simulator software

### Power supply

Typical current consumption	< 60 mA (from the AS-i network)
Supply voltage	5 V (from AS-i PROFIBUS gateway)
Power dissipation	max. 0.3 W

### General

Weight	50 g
--------	------

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 4.0	27250302
eCl@ss 4.1	27250281
eCl@ss 5.0	27259205
eCl@ss 5.1	27242600
eCl@ss 6.0	27242600
eCl@ss 7.0	27242608
eCl@ss 8.0	27242608
eCl@ss 9.0	27242608

### ETIM

ETIM 2.0	EC000313
ETIM 3.0	EC000313
ETIM 4.0	EC002584
ETIM 5.0	EC001604
ETIM 6.0	EC001604

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	32151602
UNSPSC 19.0	32151602

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub Standard Connectors](#) category:*

*Click to view products by [Phoenix Contact](#) manufacturer:*

Other Similar products are found below :

[56F711-015](#) [012-9507-004](#) [LV242999-142T12](#) [015-0341-000](#) [015-0372-005](#) [015-0372-008](#) [015-8755-001](#) [020419-0104](#) [012-0467-000](#) [012-9507-034](#) [012-9507-114](#) [020745-0008](#) [609-25P](#) [CT2-14S-2PCA34](#) [CT2-18-11PCAU](#) [CT6-10SL-3SC](#) [CT6-10SL-4SC](#) [CT6-14S-2SC](#) [CT6E14SA7SC](#) [M83513/01-FC](#) [M83723/76W24619 L/C](#) [M85049/48-3-2F](#) [6STD09PCM99B70X](#) [6STD09SCM99B30X](#) [6STD09SCT99S40X](#) [6STD15PCT99S40X](#) [6STD15SCM99B30X](#) [6STD15SCT99S40X](#) [6STF09PCM05B70X](#) [7-135760-9](#) [MC11E-10-6SN](#) [747552-3](#) [MD1-21PS](#) [MDM-15SCBRM7-F222](#) [MDM96517-699](#) [MDM96521-744](#) [MDVB1-21SL1](#) [MIK0-1-7SH003](#) [MIKQ6-7SH076](#) [MIKQ7-7PH077](#) [MIKQ7-7PH11](#) [MIKQ7-7PH32](#) [MJSV-28SL61](#) [MKJ4A1F14-55S](#) [8-135760-3](#) [8STD09PCM99B30X](#) [PG-KV/PV-16-GROM-SEALING](#) [GDA15P](#) [GDAY15PB](#) [980-0000-170](#)