

Surge protection device - TTC-6-1X2-M-24DC-PT-I - 2906726

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Surge protection with integrated status indicator and knife disconnection for a 2-wire floating signal circuit, e.g., 0(4) ... 20 mA current loop.

Why buy this product

- ✓ Space-saving installation due to the narrow overall width of 6.2 mm
- ✓ Signaling without additional auxiliary power, thanks to the mechanical status indicator
- ✓ Quick and tool-free installation of surge protective devices, thanks to Push-in connection technology
- ✓ Optional remote signaling module monitors up to 40 items, without additional wiring
- ✓ Signal circuits easily interrupted for maintenance work, thanks to vertical knife disconnection
- ✓ Safe behavior in the event of overload, thanks to the integrated disconnect device



Key Commercial Data

| | |
|--------------|---------------|
| Packing unit | 1 pc |
| GTIN | |
| GTIN | 4055626134581 |

Technical data

Dimensions

| | |
|--------|---------------------------------|
| Height | 105.8 mm |
| Width | 6.2 mm +0.1 mm |
| Depth | 83.5 mm (incl. DIN rail 7.5 mm) |

Ambient conditions

| | |
|---|--|
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Altitude | ≤ 4000 m (amsl (above mean sea level)) |
| Degree of protection | IP20 |

Surge protection device - TTC-6-1X2-M-24DC-PT-I - 2906726

Technical data

General

| | |
|--|--|
| Housing material | PBT |
| Flammability rating according to UL 94 | V-0 |
| Color | traffic grey A RAL 7042 |
| Mounting type | DIN rail: TH 35 - 7.5 mm |
| Type | DIN rail module, one-piece |
| Direction of action | Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground |

Protective circuit

| | |
|---|---|
| IEC test classification | C1 |
| | C2 |
| | C3 |
| | D1 |
| Nominal voltage U_N | 24 V DC |
| Maximum continuous voltage U_C | 30 V DC |
| Rated current | 600 mA (40 °C) |
| Operating effective current I_C at U_C | $\leq 5 \mu\text{A}$ |
| Residual current I_{PE} | $\leq 1 \mu\text{A}$ |
| Nominal discharge current I_n (8/20) μs (line-line) | 5 kA |
| Nominal discharge current I_n (8/20) μs (line-earth) | 5 kA |
| Pulse discharge current I_{imp} (10/350) μs (line-line) | 0.5 kA |
| Pulse discharge current I_{imp} (10/350) μs (line-earth) | 0.5 kA |
| Total discharge current I_{total} (8/20) μs | 10 kA |
| Voltage protection level U_p (line-line) | $\leq 55 \text{ V}$ (C1 - 1 kV/500 A) |
| | $\leq 65 \text{ V}$ (C2 - 10 kV / 5 kA) |
| | $\leq 50 \text{ V}$ (C3 - 25 A) |
| | $\leq 55 \text{ V}$ (C3 - 100 A) |
| Voltage protection level U_p (line-earth) | $\leq 750 \text{ V}$ (C1 - 1 kV/500 A) |
| | $\leq 750 \text{ V}$ (C2 - 10 kV / 5 kA) |
| | $\leq 700 \text{ V}$ (C3 - 25 A) |
| | $\leq 750 \text{ V}$ (C3 - 100 A) |
| Voltage protection level U_p static (line-line) | $\leq 50 \text{ V}$ (C1 - 1 kV/500 A) |
| | $\leq 65 \text{ V}$ (C2 - 10 kV / 5 kA) |
| Voltage protection level U_p static (line-earth) | $\leq 750 \text{ V}$ (C1 - 1 kV/500 A) |
| | $\leq 750 \text{ V}$ (C2 - 10 kV / 5 kA) |
| Response time t_A (line-line) | $\leq 1 \text{ ns}$ |
| Response time t_A (line-earth) | $\leq 100 \text{ ns}$ |
| Input attenuation aE, sym. | typ. 0.3 dB ($\leq 250 \text{ kHz}$ / 150 Ω) |
| Cut-off frequency f_g (3 dB), sym. in 150 Ohm system | typ. 940 kHz |
| Capacity (line-line) | typ. 2.2 nF |
| Resistance in series | 1.65 $\Omega \pm 20 \%$ |

Surge protection device - TTC-6-1X2-M-24DC-PT-I - 2906726

Technical data

Protective circuit

| | |
|---------------------------------|-----------------|
| Surge protection fault message | optical |
| Max. required back-up fuse | 630 mA (FF) |
| Impulse durability (line-line) | C1 - 1 kV/500 A |
| | C2 - 10 kV/5 kA |
| | C3 - 100 A |
| Impulse durability (line-earth) | C1 - 1 kV/500 A |
| | C2 - 10 kV/5 kA |
| | C3 - 100 A |
| | D1 - 500 A |
| Pulse reset time (line-line) | ≤ 700 ms |
| Pulse reset time (line-earth) | ≤ 1500 ms |

Additional technical data

| | |
|--|------------|
| Max. total discharge current $I_{total\ max} (8/20) \mu s$ | 20 kA (1x) |
|--|------------|

Connection data

| | |
|----------------------------------|---|
| Connection method | Push-in connection |
| Stripping length | 8 mm |
| Conductor cross section flexible | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross section solid | 0.2 mm ² ... 4 mm ² |
| Conductor cross section AWG | 24 ... 12 |

Standards and Regulations

| | |
|--------------------------|--|
| Standards/specifications | IEC 61643-21 2000 + corrigendum 2001 + A1:2008, modified + A2:2012 |
| | EN 61643-21 2001 + A1:2009 + A2:2013 |

Environmental Product Compliance


| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

Drawings

Pictogram




Diagram




Surge protection device - TTC-6-1X2-M-24DC-PT-I - 2906726

Dimensional drawing



Circuit diagram



Approvals

Approvals

Approvals

UL Listed / CSA / CSAus / DNV GL / cCSAus

Ex Approvals

Approval details

| | | | |
|-----------|--|---|---------------|
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 138168 |
| CSA | | http://www.csagroup.org/services-industries/product-listing/ | 70136717 |
| CSAus | | http://www.csagroup.org/services-industries/product-listing/ | 70136717 |
| DNV GL | | http://exchange.dnv.com/tari/ | TAE000027G |
| cCSAus | | http://www.csagroup.org/services-industries/product-listing/ | |

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Surge Suppressors](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[GUS1](#) [GUS12](#) [BSPM1A600D600LVR](#) [2800521](#) [29-2053](#) [GUS11](#) [GUS2](#) [GUS3](#) [30460](#) [SRA64C060X](#) [PC642C015](#) [1810-15-A3](#) [2713175](#)
[4B06B-EC1-150LF](#) [SRA6LC](#) [BPMA75D100LV](#) [CX06M](#) [CCTV1](#) [GUS13](#) [GUS14](#) [GUS5](#) [GUS6](#) [VAL-MS 320/3+0-FM](#) [VAL-US-](#)
[120/40/1+1-FM](#) [VAL-US-120/65/1+1-FM](#) [VAL-US-480D/30/3+0-FM](#) [VAL-US-120/40/1+0-FM](#) [LP-STRL-NFF](#) [LP-STRL-DFE](#) [GUS22](#)
[0804111](#) [5053609](#) [5053201](#) [SPD2-150-1P0](#) [SPD2-550-1P0](#) [6720005416](#) [6720005417](#) [1-2191595-2](#) [STC-CAT6-P0E-I](#) [SPD2-350-1P0](#) [FLT-](#)
[CP-350-ST](#) [TTC-6P-3-HF-F-M-12DC-UT-I](#) [SMTPA200](#) [2800989](#) [2906776](#) [2906810](#) [2906847](#) [2906848](#) [2906851](#) [2910332](#)