

## Cable - CAB-DSUB37M/OE/22/S/ 3M - 2909623

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled shielded round cable; connection 1: Single wires (37-position) (The wires are marked and fitted with ferrules); connection 2: D-SUB pin strip (1x 37-position); cable length: 3 m

### Your advantages

- Individual wire marking: 1, 2, 3, 4, etc.
- Individual wires fitted with ferrules
- Screw connection: 2 UNC 4-40 screws
- Open end at one end
- D-SUB socket or pin strip at one end
- 1:1 connection

### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	
GTIN	4055626682181

### Technical data

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

#### General

Max. permissible operating voltage	125 V AC
	125 V DC
Max. current carrying capacity per path	2 A
Length of cable	3 m
External cable diameter	11.7 mm
Single wire, cross section	0.36 mm <sup>2</sup>

# Cable - CAB-DSUB37M/OE/22/S/ 3M - 2909623

## Technical data

### General

Single wire, cross section [AWG]	22
Shielding	yes
	Overall foil and braid shield

### Connection data

Connection name	Field level
Connection method	D-SUB pin strip
Number of connections	1
Number of positions	37

### Connection data 2

Connection name	Controller level
Connection method	Single wires
Number of positions	37
Note	The wires are marked and fitted with ferrules

### Supported controller

Controller	universal
------------	-----------

### Color code

Connector 1 = connector 2 (optional) = wire color	D-SUB37 (1) = black
	D-SUB37 (2) = white
	D-SUB37 (3) = red
	D-SUB37 (4) = green
	D-SUB37 (5) = orange
	D-SUB37 (6) = blue
	D-SUB37 (7) = white-black
	D-SUB37 (8) = red-black
	D-SUB37 (9) = green-black
	D-SUB37 (10) = orange-black
	D-SUB37 (11) = blue-black
	D-SUB37 (12) = black-white
	D-SUB37 (13) = red-white
	D-SUB37 (14) = green-white
	D-SUB37 (15) = blue-white
	D-SUB37 (16) = black-red
	D-SUB37 (17) = white-red
	D-SUB37 (18) = orange-red
	D-SUB37 (19) = blue-red
	D-SUB37 (20) = red-green
	D-SUB37 (21) = orange-green
	D-SUB37 (22) = black-white-red
	D-SUB37 (23) = white-black-red

## Cable - CAB-DSUB37M/OE/22/S/ 3M - 2909623

### Technical data

#### Color code

	D-SUB37 (24) = red-black-white
	D-SUB37 (25) = green-black-white
	D-SUB37 (26) = orange-black-white
	D-SUB37 (27) = blue-black-white
	D-SUB37 (28) = black-red-green
	D-SUB37 (29) = white-red-green
	D-SUB37 (30) = red-black-green
	D-SUB37 (31) = green-black-orange
	D-SUB37 (32) = orange-black-green
	D-SUB37 (33) = blue-white-orange
	D-SUB37 (34) = black-white-orange
	D-SUB37 (35) = white-red-orange
	D-SUB37 (36) = orange-white-blue
	D-SUB37 (37) = white-red-blue

### Classifications

#### eCl@ss

eCl@ss 10.0.1	27242220
eCl@ss 5.0	27242200
eCl@ss 5.1	27242200
eCl@ss 6.0	27249200
eCl@ss 7.0	27249205
eCl@ss 8.0	27249205
eCl@ss 9.0	27242220

#### ETIM

ETIM 5.0	EC000237
ETIM 6.0	EC000237
ETIM 7.0	EC000237

### Accessories

#### Accessories

##### Marker carrier cable

Cable marker carrier - KME - 0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable binders, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

## Cable - CAB-DSUB37M/OE/22/S/ 3M - 2909623

### Accessories

---

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub Cables](#) category:*

*Click to view products by [Phoenix Contact](#) manufacturer:*

Other Similar products are found below :

[1200980218](#) [1200980067](#) [RB09P09P-006](#) [RB09P09P-012](#) [RB15P15P-006](#) [RB25P25P-006](#) [RB37P37P-024](#) [172-0906](#) [SHD15P15S-012](#)  
[SHD15P15S-036](#) [SHD15P15S-060](#) [ACL-10137-2MM](#) [RB09P09P-024](#) [319285-3](#) [RS422-OM2](#) [SHD26P26S-060](#) [SHD44P44S-036](#) [73-](#)  
[6210MM-6](#) [C200H-CN320-EU](#) [49725A 060S2](#) [73231-1321](#) [SDB-50AFFM-SL7A02](#) [49760A 060S2](#) [HDB-26AFFM-SL7A02](#) [30-9503P](#) [30-](#)  
[9522P](#) [73-6220MM-6](#) [1200980058](#) [1200980066](#) [1200980078](#) [1200980052](#) [1200980093](#) [1200980028](#) [1200980021](#) [1200980127](#) [SDB-](#)  
[09AFFM-SL7A02](#) [BB-LDVYCBL](#) [83421-9286](#) [MLDM2L-21P-6K7-18B](#) [KSFD1](#) [MM-2J2-021-SS1-41WN](#) [HDB-78AMMM-SL7A05](#) [SDB-](#)  
[37AMMM-SL7A03](#) [SDB-15AFFM-SL7A05](#) [ACC-500-163-R](#) [172-1910](#) [2900907/21.4](#) [VS-25-DSUB-20-LI-2,0](#) [VS-25-DSUB-20-LI-5,0](#) [VS-](#)  
[09-DSUB-201-LI-0,4-AC](#)