

Adapter - FLKM-1771-WG/S7-531-7NF/I/0,5M - 2910097


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Migration adapter for converting Allen Bradley PLC-5 (1771-WG) to Siemens SIMATIC® S7-1500 front connector. 1771-IFE / 1771-IFF to 6ES7 531-7NF10-0AB0 conversion (current measurement), cable length: 0.5 m

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 426723
GTIN	4055626426723

Technical data

Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Maximum altitude	≤ 2000 m (Above sea level)
Permissible humidity (operation)	95 % (non-condensing)
Degree of protection	IP20
	≥ IP54 (Installation location)

General

Max. permissible operating voltage	264 V AC/DC
Mains frequency	50/60 Hz
Max. permissible current	2 A (per path)
Max. permissible total current	42 A
Mounting position	any
Nominal operating mode	100% operating factor

Connection data

Connection name	Allen-Bradley PLC-5 [#]
Connection method	Plug connection

Adapter - FLKM-1771-WG/S7-531-7NF/I/0,5M - 2910097

Technical data

Connection data 2

Connection name	S7-1500-Adapter
Connection method	Plug connection
Number of connections	1

Cable

Single wire, cross section	0.5 mm ²
External diameter	9.6 mm
Length of cable	0.5 m
Outer sheath, material	PVC
External sheath, color	blue
Insulation	Polyvinyl chloride (PVC)

Supported controller

Controller	Allen-Bradley® 1771 (PLC5)
- suitable I/O card	1771-IFE
	1771-IFF
Controller	SIEMENS S7-1500
- suitable I/O card	6ES7 531-7NF10-0AB0

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27242292
eCl@ss 5.0	27249290
eCl@ss 5.1	27249290
eCl@ss 6.0	27249200
eCl@ss 7.0	27249290
eCl@ss 8.0	27249290
eCl@ss 9.0	27242292

ETIM

ETIM 4.0	EC002584
ETIM 5.0	EC002584
ETIM 6.0	EC002584
ETIM 7.0	EC002584

Adapter - FLKM-1771-WG/S7-531-7NF/I/0,5M - 2910097

Approvals





Approvals

Approvals

UL Listed / cUL Listed / EAC / cULus Listed

Ex Approvals

Approval details

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
cUL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
EAC			RU C- DE.A*30.B00767
cULus Listed			

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminal Block Interface Modules](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[73-551-6002I](#) [GCN1MX25B](#) [DIN-50P-01](#) [DIN-68H-01](#) [DIN-96DI-01](#) [2291901](#) [2295185](#) [2907794](#) [2M10FCL](#) [FLKM-2I/O](#) [FLKM-4I/O](#)
[2281759](#) [2906251](#) [2907808](#) [5601749](#) [5541962](#) [1776613-1](#) [GCN1-004A](#) [ADAM-3920R-AE](#) [060-6827-06](#) [2311030](#) [2287708](#) [XW2C-20G6-](#)
[IO16](#) [GCN1-T](#) [MACX](#) [MCR-VAC](#) [5775235](#) [ADAM-3956-BE](#) [XW6T-COM2.5X20YL](#) [XW6T-COM1.5X8BL](#) [XW6T-COM1.5X16BL](#)
[XW6T-COM1.5X20YL](#) [XW6T-COM1.5X16YL](#) [XW6T-COM1.5X20RD](#) [XW6T-COM1.5X20BL](#) [XW6T-COM2.5X8BL](#) [1976610000](#) [UM](#)
[45-D50SUB/B/ZFKDS](#) [5541234](#) [410-261](#) [902056](#) [2906243](#) [2906915](#) [2907706](#) [ADAM-3909-AE](#) [ADAM-3920-AE](#) [ADAM-3925-AE](#)
[ADAM-3937-BE](#) [ADAM-3950-AE](#) [ADAM-3951-BE](#) [ADAM-3968-AE](#)