

FO patch cable - FL SM PATCH 1,0 LC-ST - 2989242

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Assembled fiber optic cable, break-out cable, fiberglass single mode 9/125 µm (OS2, Low Water Peak Fiber), connector: LC/B-FOC(ST®), degree of protection: IP20, for installation in cable ducts or control cabinets, length: 1 m




Your advantages

- ✓ Single-mode patch cable for indoor installation
- ✓ Ideal for use in distributor systems and for connecting termination devices
- ✓ 2.8 mm single elements made from halogen-free and flame-retardant material



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 354752 |
| GTIN | 4046356354752 |

Technical data

Cable type

| | |
|--------------------|------------------------|
| Cable abbreviation | I-V(ZN)H |
| Cable type | Single-mode fiberglass |
| Fixed cable length | 1.00 m |
| Cable weight | 15.80 kg/km |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -5 °C ... 70 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |
| Ambient temperature (installation) | -5 °C ... 50 °C |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |

External sheath

| | |
|------------------------|--------|
| Outer sheath, material | FRNC |
| External sheath, color | yellow |

FO patch cable - FL SM PATCH 1,0 LC-ST - 2989242

Technical data

External sheath

| | |
|---|-----------------------------|
| External sheath, strain relief elements | Non-metallic, aramide fiber |
| External diameter max. | 5.7 mm |
| External diameter min. | 2.8 mm |

Single wire

| | |
|-------------------------------------|------------------------------|
| Single wires, quantity | 2 |
| Individual wire, diameter | 900 µm |
| Single wire, strain relief elements | Non-metallic, aramide fibers |

Mechanical properties

| | |
|---------------------------------------|------------|
| Bending radius short term/long term | 30 mm |
| Bending radius, long-term | 60 mm |
| Lateral pressure, long-term | 60.00 N/cm |
| Tensile strength short-term/long-term | 600 N |
| Cable, attenuation | 0.38 dB/km |
| | 0.28 dB/km |

General

| | |
|---|-------------|
| Conductor length | 1.00 m |
| Cable weight | 15.80 kg/km |
| Transmission characteristics (category) | OS2 |
| Transmission speed | 10 Gbps |
| Degree of protection | IP20 |

Behavior in fire

| | |
|------------------------|------------------------------|
| Flame resistance | according to DIN 60332-1-2 |
| | IEC 60332-3-22 (Cat. A) |
| Concentration of fumes | in accordance with IEC 61034 |
| Halogen-free | According to IEC 60754-2 |
| Behavior in fire | No corrosive or toxic fumes |
| | 0.36 MJ/m |

Attenuation

| | |
|---------|------------|
| 1300 nm | 0.38 dB/km |
| 1550 nm | 0.28 dB/km |

Standards and Regulations

| | |
|------------------------|---|
| Concentration of fumes | in accordance with IEC 61034 |
| Flame resistance | according to DIN 60332-1-2 |
| | IEC 60332-3-22 (Cat. A) |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |
| Halogen-free | According to IEC 60754-2 |
| Behavior in fire | No corrosive or toxic fumes |
| | 0.36 MJ/m |

FO patch cable - FL SM PATCH 1,0 LC-ST - 2989242

Technical data

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27061003 |
| eCl@ss 4.0 | 27250500 |
| eCl@ss 4.1 | 27250500 |
| eCl@ss 5.0 | 27259200 |
| eCl@ss 5.1 | 27259200 |
| eCl@ss 6.0 | 27259200 |
| eCl@ss 7.0 | 27259207 |
| eCl@ss 8.0 | 27061003 |
| eCl@ss 9.0 | 27061003 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001263 |
| ETIM 3.0 | EC001263 |
| ETIM 4.0 | EC002607 |
| ETIM 5.0 | EC001263 |
| ETIM 6.0 | EC001263 |
| ETIM 7.0 | EC001263 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121607 |
| UNSPSC 7.0901 | 26121607 |
| UNSPSC 11 | 26121607 |
| UNSPSC 12.01 | 26121607 |
| UNSPSC 13.2 | 26121607 |
| UNSPSC 18.0 | 26121607 |
| UNSPSC 19.0 | 26121607 |
| UNSPSC 20.0 | 26121607 |
| UNSPSC 21.0 | 26121607 |

Approvals

Approvals

FO patch cable - FL SM PATCH 1,0 LC-ST - 2989242

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|--|---------|
| EAC | | B.01687 |
|-----|--|---------|

Accessories

Accessories

Adapter

Fiber optic coupling - FL COUPLER SC-DUPLEX - 2901788



Coupling, SC duplex/SC duplex, compatible with multi-mode and single mode glass fibers, PCF, and polymer fibers

Data plug

Fiber optic coupling - PSM-SET-BFOC-LINK/2 - 2799429



Coupling; set consisting of 2 couplings for connecting B-FOC plugs

Fiber optic coupling - FL SM PATCH COUPLER LC-LC - 2700313



Coupling, LC/LC, can be used for single mode glass fibers

Fiber optics connector (device side)

FO patch cable - FL SM PATCH 1,0 LC-ST - 2989242

Accessories

SC-RJ female insert - VS-SCRJ-GOF-BU/BU - 1652978



SC-RJ socket insert, duplex, for VS-A-F-IP67 panel mounting frame, can be used for fiberglass (multi-mode and single mode), PCF, and polymer fibers

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Cable Assemblies](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[7-21002-9](#) [760-1518](#) [FA04390-50-M-72-LC-N](#) [MLB 501 V RED](#) [MLB 501 V YELLOW](#) [1-3636-600-5208](#) [2061529-7](#) [1-6693182-0](#)
[1754898-1](#) [21055-6](#) [FXBSCSCE2LM002](#) [3000005](#) [3-21053-2](#) [MLB 200/1 V BLACK](#) [5492011-6](#) [106284-7000](#) [5492011-5](#) [5492011-8](#)
[5492011-9](#) [8-21007-5](#) [2123524-2](#) [2123524-1](#) [106386-4447](#) [DFSM-SCSC-2M](#) [2123909-4](#) [2123909-8](#) [106273-0629](#) [2125046-1](#) [2821236-3](#)
[2821310-2](#) [2821310-3](#) [2821313-4](#) [FX2ERLNLNSNM0.5](#) [CF-980062-074](#) [CF-901200-394](#) [CF-980062-073](#) [CF-980062-071](#) [CF-980062-075](#)
[CF-980062-072](#) [17-300310-100](#) [2821236-2](#) [2821313-1](#) [G-FC-FC-S-002.0-DX-A-18-Y](#) [G-E2A-E2A-S-003.0-SX-A-18-Y](#) [956-322-502214](#)
[FA04474](#) [1083665](#) [1111540](#) [1111843](#) [1115533](#)