

Spiral tube - WG-S HF 40 - 3241113


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Spiral hose, for easy bundling and guiding of cables and conductors, offers protection against slight mechanical strain

RoHS

Key Commercial Data

| | |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 25 M |
| Minimum order quantity | 25 M |
| GTIN |  4 046356 717427 |
| GTIN | 4046356717427 |

Technical data

Dimensions

| | |
|--------------------|----------------|
| Length (b) | 25 m |
| Width (a) | 40 mm |
| Inner diameter (f) | 6.5 mm |
| Cable diameter | 7 mm ... 40 mm |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -50 °C ... 85 °C |
| Ambient temperature (assembly) | -20 °C ... 60 °C |

General

| | |
|----------------------------------------|--------------------------------|
| Color | transparent |
| Type | Continuous strip |
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | HB |
| Material | PE |

Standards and Regulations

| | |
|----------------------------------------|----|
| Flammability rating according to UL 94 | HB |
|----------------------------------------|----|

Spiral tube - WG-S HF 40 - 3241113

Technical data

Environmental Product Compliance

| | |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27430302 |
| eCl@ss 4.0 | 27140600 |
| eCl@ss 4.1 | 27140600 |
| eCl@ss 5.0 | 27140600 |
| eCl@ss 5.1 | 27140600 |
| eCl@ss 6.0 | 27400700 |
| eCl@ss 7.0 | 27430302 |
| eCl@ss 8.0 | 27430302 |
| eCl@ss 9.0 | 27430302 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000012 |
| ETIM 4.0 | EC000046 |
| ETIM 5.0 | EC002604 |
| ETIM 6.0 | EC002604 |
| ETIM 7.0 | EC002604 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211812 |
| UNSPSC 7.0901 | 39121411 |
| UNSPSC 11 | 39121411 |
| UNSPSC 12.01 | 39121708 |
| UNSPSC 13.2 | 39131712 |
| UNSPSC 18.0 | 39131712 |
| UNSPSC 19.0 | 39131712 |
| UNSPSC 20.0 | 39131712 |
| UNSPSC 21.0 | 39131712 |

Accessories

Accessories

Cutting tools

Spiral tube - WG-S HF 40 - 3241113

Accessories

Cable-cutting tool - CUTFOX-ES - 1212621



Electrician's scissors, high cutting performance thanks to micro-serrated cutting area, suitable for copper, aluminum, Kevlar fibers, and plastic, two-component non-slip soft-grip handles, ergonomic design, adjustable screw joint

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Spiral Wraps, Sleeves, Tubing & Conduit](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[601203-000](#) [CTA-0053](#) [8426-11](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-104-24](#) [120-113-16B](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#)
[120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-116-1-1-20BP](#) [120-116-1-1-32BE](#) [120-117-40](#) [120-123-06](#) [120-123-10](#) [120-123-14](#) [120-123-16](#)
[120-125-12BL](#) [120-125-12R](#) [120-125-16](#) [120-125-16R](#) [120-125-16Y](#) [120-125-20R](#) [120-125-24Y](#) [120-125-28](#) [120-125-28R](#) [120-125-32](#)
[120-125-32R](#) [120-125-40](#) [120-125-56](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-14](#) [120-126-16](#) [120-126-16BL](#) [120-](#)
[126-20](#) [120-126-20BL](#) [120-126-20R](#) [120-126-24](#) [120-126-28](#) [120-126-32](#) [120-126-40BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#)