

Socket - EM-DUO 120/15/SWA - 5604433

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Rail-mounted switched socket where switch controls auxiliary connections. For mounting on 35 mm DIN rails per EN 60715. Housing color: ivory. Receptacle style: USA. Connection type: screw.



Key Commercial Data

| | |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| GTIN | |
| GTIN | 4046356685184 |
| Weight per Piece (excluding packing) | 280.000 g |
| Custom tariff number | 85366990 |
| Country of origin | United States |

Technical data

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
|---------------------------------|------------------|

General

| | |
|-----------------------------|--------------|
| Nominal voltage U_N | 125 V AC |
| Nominal current I_N | 15 A |
| For country-specific use in | USA |
| | Canada |
| | Japan |
| | Mexico |
| | Saudi Arabia |
| | Taiwan |

Socket - EM-DUO 120/15/SWA - 5604433

Technical data

General

| | |
|-----------------------|-----------|
| | Venezuela |
| Color | ivory |
| Insulating material | PVC 94 V0 |
| Standards/regulations | UL 508 |
| | CSA 22.2 |

Connection data

| | |
|---------------------------------------|---------------------|
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 6 mm ² |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 4 mm ² |
| Conductor cross section AWG min. | 30 |
| Conductor cross section AWG max. | 10 |
| Connection method | Screw connection |
| Stripping length | 8 mm |
| Screw thread | M3 |

Standards and Regulations

| | |
|-----------------------|----------|
| Standards/regulations | UL 508 |
| | CSA 22.2 |

Environmental Product Compliance

| | |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27142305 |
| eCl@ss 4.0 | 27142300 |
| eCl@ss 4.1 | 27142300 |
| eCl@ss 5.0 | 27142300 |
| eCl@ss 5.1 | 27142300 |
| eCl@ss 6.0 | 27142300 |
| eCl@ss 7.0 | 27142305 |
| eCl@ss 8.0 | 27142305 |
| eCl@ss 9.0 | 27142305 |

Socket - EM-DUO 120/15/SWA - 5604433

Classifications

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001325 |
| ETIM 4.0 | EC001663 |
| ETIM 5.0 | EC001663 |
| ETIM 6.0 | EC001663 |
| ETIM 7.0 | EC001663 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30212010 |
| UNSPSC 7.0901 | 39121610 |
| UNSPSC 11 | 39121610 |
| UNSPSC 12.01 | 39121610 |
| UNSPSC 13.2 | 39121406 |
| UNSPSC 18.0 | 39121406 |
| UNSPSC 19.0 | 39121406 |
| UNSPSC 20.0 | 39121406 |
| UNSPSC 21.0 | 39121406 |

Approvals


Approvals

Approvals

UL Listed / cUL Listed / cULus Listed


Ex Approvals


Approval details

| | | | |
|----------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 238705 |
| Nominal voltage UN | 120 V | | |
| Nominal current IN | 15 A | | |
| mm ² /AWG/kcmil | 30-10 | | |

Socket - EM-DUO 120/15/SWA - 5604433

Approvals

| | | | |
|----------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| cUL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 238705 |
| Nominal voltage UN | | 120 V | |
| Nominal current IN | | 15 A | |
| mm ² /AWG/kcmil | | 30-10 | |

| | |
|--------------|-----------------------------------------------------------------------------------|
| cULus Listed |  |
|--------------|-----------------------------------------------------------------------------------|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [AC Power Plugs & Receptacles](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[739W-X2/03-BACK1](#) [739W-X2/40](#) [85447L](#) [D38999/26WG16HA](#) [1300190002](#) [1300190008](#) [1300190014](#) [1301460003](#) [1301520016](#)
[1300190011](#) [1300190021](#) [1300190023](#) [1301410085](#) [1301440049](#) [1301440073](#) [1301520008](#) [22806](#) [26W47](#) [929662-1](#) [27W81](#) [29W08MB](#)
[GDM 3-17](#) [26W](#) [26W76BLK](#) [27W47](#) [27W48](#) [28W81](#) [29W47MB](#) [HDR-E14FG1+](#) [30-9717-25](#) [5604067](#) [5604434](#) [5604777](#) [5604436](#)
[929665-1](#) [22801](#) [25W47](#) [701W-15/06](#) [701W-20/27](#) [GM 207-3 NBR BLASSBRAUN/LIGHT BROWN](#) [27T76](#) [29T48](#) [739W-20/XX](#)
[1301520018](#) [1301440092](#) [1301410084](#) [1300190032](#) [1300190022](#) [1300190015](#) [1300190013](#)