

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Ethernet Switch, 8 TP RJ45 ports, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function

Why buy this product

- Auto negotiation and autocrossing detection simplifies installation and setup
- Local diagnostic indicators with LEDs
- Security options with cable locking
- Relay contact for alarm processing of voltage states
- RJ45 ports support a transmission speed of 10/100 Mbps; fiber optic ports support 100 Mbps



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 STK |
| GTIN |  4 017918 952204 |
| GTIN | 4017918952204 |
| Weight per Piece (excluding packing) | 427.800 g |
| Custom tariff number | 85176200 |
| Country of origin | Taiwan |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|--------|---------|
| Width | 135 mm |
| Height | 94.3 mm |
| Depth | 30 mm |

Ambient conditions

| | |
|----------------------|------|
| Degree of protection | IP20 |
|----------------------|------|

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Technical data

Ambient conditions

| | |
|--|--|
| Ambient temperature (operation) | 0 °C ... 55 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing) |
| Air pressure (operation) | 86 kPa ... 108 kPa (up to 1500 m above mean sea level) |
| Air pressure (storage/transport) | 66 kPa ... 108 kPa (up to 3500 m above mean sea level) |

Interfaces

| | |
|---------------------------|---------------------------------------|
| Interface 1 | Ethernet (RJ45) |
| No. of ports | 8 (RJ45 ports) |
| Connection method | RJ45 |
| Note on connection method | Auto negotiation and autocrossing |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission speed | 10/100 Mbps |
| Transmission length | 100 m (per segment) |
| Signal LEDs | Data receive, link status |
| Interface 4 | Potential-free signaling contact |
| Connection method | Plug-in/screw connection via COMBICON |

Function

| | |
|----------------------------------|---|
| Basic functions | Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode |
| Status and diagnostic indicators | LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port |
| Signal contact control voltage | 24 V DC (typical) |

Network expansion parameters

| | |
|---|--|
| Cascading depth | Network, linear, and star structure: any |
| Maximum conductor length (twisted pair) | 100 m |

Supply voltage

| | |
|-----------------------------|--|
| Supply voltage | 24 V DC (redundant) |
| Residual ripple | 3.6 V _{PP} (within the permitted voltage range) |
| Supply voltage range | 18.5 V DC ... 30.2 V DC |
| Typical current consumption | typ. 200 mA (at U _S = 24 V DC) |
| | 95 mA (at U _S = 24 V DC: >VC 14) |

General

| | |
|------------------|--------------|
| Mounting type | DIN rail |
| Type AX | Block design |
| Net weight | 427.8 g |
| Housing material | Aluminum |

Standards and Regulations

| | |
|-------------------------------|--|
| Electromagnetic compatibility | Conformance with EMC Directive 2004/108/EC |
|-------------------------------|--|

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Technical data

Standards and Regulations

| | |
|---|---|
| Developed in acc. with standard | IEC 61000-6.2 |
| Test standard | IEC 61000-4-2 (ESD) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-3 (immunity to radiated interference) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-4 (burst) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-5 (surge) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-6 (immunity to conducted interference) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-8 (immunity to magnetic fields) |
| Test result | Criterion A |
| Test standard | EN 55022 (emitted interference) |
| Test result | Criterion A |
| Type of test | Shock in acc. with EN 60068-2-27/IEC 60068-2-27 |
| Test result | Operation: 25g, 11 ms duration, semi-sinusoidal shock impulse |
| Noise emission | EN 61000-6-4 |
| Noise immunity | EN 61000-6-2:2005 |
| Vibration (storage/transport) | 5g, 150 Hz, in acc. with IEC 60068-2-6 |
| Free from substances that could impair the application of coating | In acc. with VW specification |
| Vibration (operation) | In acc. with IEC 60068-2-6: 5g, 150 Hz |
| UL, USA/Canada | Class I, Div. 2, Groups A, B, C, D |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250501 |
| eCl@ss 4.1 | 27250501 |
| eCl@ss 5.0 | 27250501 |
| eCl@ss 5.1 | 27250501 |
| eCl@ss 6.0 | 19170106 |
| eCl@ss 7.0 | 19170106 |
| eCl@ss 8.0 | 19170106 |
| eCl@ss 9.0 | 19170106 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000734 |
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 5.0 | EC000734 |

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Classifications

ETIM

| | |
|----------|----------|
| ETIM 6.0 | EC000734 |
|----------|----------|

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201410 |
| UNSPSC 13.2 | 43222612 |

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / EAC / KC / cULus Listed

Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approval details

| | | | |
|-----------|---|---|---------------|
| UL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
|-----------|---|---|---------------|

| | | | |
|------------|---|---|---------------|
| cUL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
|------------|---|---|---------------|

| | | | |
|-----|---|--|---------------|
| EAC |  | | EAC-Zulassung |
|-----|---|--|---------------|

| | | | |
|-----|---|--|--------------------------|
| EAC |  | | RU *- DE.A*30.B.01735 |
|-----|---|--|--------------------------|

| | | | |
|----|---|---|--------------------------|
| KC |  | http://rra.go.kr/eng2/index.jsp | KCC-REI- PCK- FL28327 |
|----|---|---|--------------------------|

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Approvals

cULus Listed



Accessories

Accessories

Data cable by the meter

Cable - FL CAT5 HEAVY - 2744814



CAT5-SF/UTP cable (J-02YS(ST)C HP 2 x 2 x 24 AWG), heavy-duty installation cable, 2 x 2 x 0.22 mm², solid conductor, shielded, outer sheath: 7.8 mm diameter, inner sheath: 5.75 mm ± 0.15 mm diameter

Network cable - FL CAT5 FLEX - 2744830



CAT5-SF/UTP cable (J-LI02YS(ST)C H 2 x 2 x 26 AWG), light-duty, flexible installation cable 2 x 2 x 0.14 mm², stranded, shielded, outer sheath: 5.75 mm ± 0.15 mm diameter

Plug

RJ45 connector - FL PLUG RJ45 GR/2 - 2744856



RJ45 connector, shielded, with bend protection sleeve, 2 pieces, gray for straight cables, for assembly on site. For connections that are not crossed, it is recommended that you use the connector set with gray bend protection sleeve.

RJ45 connector - FL PLUG RJ45 GN/2 - 2744571



RJ45 connector, shielded, with bend protection sleeve, 2 pieces, green for crossed cables, for assembly on site. For connections that are crossed, it is recommended that the connector set with green bend protection sleeves is used.

Universal tools

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Accessories

Assembly tool - FL CRIMPTOOL - 2744869



Crimping pliers, for assembling the RJ45 plugs FL PLUG RJ45..., for assembly on site

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[CRIMPFOX 25R](#) [CRIMPFOX 6S-F](#) [CRIMPFOX LC](#) [CRIMPFOX-RCI 6-M](#) [CRIMPFOX ZA 2](#) [ETD-BL-1T-F-300S](#) [E/U](#) [MCR-1CLP-I-I-00](#)
[MCR-4CLP-I-I-00](#) [MINI-BAT/12DC/1.6AH](#) [FLK 50/EZ-DR/ 400/KONFEK/S](#) [FLKM-D15 SUB/B](#) [PCV 6-16/ 2-G1-10 16](#) [PSM-STRIP-](#)
[FC/PROFIB](#) [PSR-SCP- 24DC/TS/SDI8/SDIO](#) [PSR-SPP- 24DC/TS/M](#) [PT 4-FSI/F-LED 12](#) [1203534](#) [1205516](#) [1212208](#) [1212511](#) [1212637](#)
[HC-B 16-SD-FQ/FS](#) [HC-B 48-AMLD](#) [HC-B 48-TFL-96/O1STM32S](#) [1207650](#) [1212095](#) [1212641](#) [RAD-CON-MCX-N-SS](#) [RAD-OUT-4A-I](#)
[RAD-OUT-8D-REL](#) [RF-17P2N8A90DU](#) [DFLK-D25 SUB/S](#) [DFLK-D 9 SUB/B](#) [1400782](#) [1400786](#) [1401236](#) [1401348](#) [1401828:0021](#)
[1403782](#) [1403956](#) [1404026](#) [1406005](#) [1406049](#) [1406138](#) [1406150](#) [1406295](#) [1406303](#) [AI SORTI BOX ANT](#) [1400773](#)