

Accessories - MCC 0,5-MP AU 0,14-0,5 R - 1013420


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimp contact, type of contact: Female connector, connection method: Crimp connection, contact surface: Gold, Conductor cross section flexible: 0.14 ...0.5 mm², type of packaging: Taped on roll

RoHS

Key Commercial Data

Packing unit	5000 pc
Minimum order quantity	5000 pc
GTIN	 4 055626 492506
GTIN	4055626492506
Weight per Piece (excluding packing)	0.060 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General

Conductor cross section flexible min.	0.14 mm ²
Max. conductor cross section, flexible	0.5 mm ²

Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	27260700
eCl@ss 4.1	27260700

Accessories - MCC 0,5-MP AU 0,14-0,5 R - 1013420

Classifications

eCl@ss

eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440309
eCl@ss 8.0	27440204
eCl@ss 9.0	27440204

ETIM

ETIM 5.0	EC000796
ETIM 6.0	EC000796
ETIM 7.0	EC000796

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	--	---------

Accessories

Accessories

Crimping tool

Crimping pliers - CRIMPFOX-P CC 0.75 L - 1064998



Crimping pliers, for COMBICON crimp connectors with cross section: 0.14 ... 0.75 mm². Unlockable pressure lock, precise parallel crimping, front entry, B crimp, incl. 2 positioning aids

Additional products

Accessories - MCC 0,5-MP AU 0,14-0,5 R - 1013420

Accessories

Printed-circuit board connector - MCC 0,5/ 2-ST-2,54 - 1012266



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 2, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - MCC 0,5/ 3-ST-2,54 - 1012267



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 3, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - MCC 0,5/ 4-ST-2,54 - 1012268



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 4, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - MCC 0,5/ 5-ST-2,54 - 1012269



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 5, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - MCC 0,5/ 6-ST-2,54 - 1012270



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 6, pitch: 2.54 mm, connection method: Crimp connection, color: black

Accessories - MCC 0,5-MP AU 0,14-0,5 R - 1013420

Accessories

Printed-circuit board connector - MCC 0,5/ 7-ST-2,54 - 1012271

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 7, pitch: 2.54 mm, connection method: Crimp connection, color: black



Printed-circuit board connector - MCC 0,5/ 8-ST-2,54 - 1012272

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 8, pitch: 2.54 mm, connection method: Crimp connection, color: black



Printed-circuit board connector - MCC 0,5/ 9-ST-2,54 - 1012273

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 9, pitch: 2.54 mm, connection method: Crimp connection, color: black



Printed-circuit board connector - MCC 0,5/10-ST-2,54 - 1012274

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 10, pitch: 2.54 mm, connection method: Crimp connection, color: black



Printed-circuit board connector - MCC 0,5/11-ST-2,54 - 1012276

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 11, pitch: 2.54 mm, connection method: Crimp connection, color: black



Accessories - MCC 0,5-MP AU 0,14-0,5 R - 1013420

Accessories

Printed-circuit board connector - MCC 0,5/12-ST-2,54 - 1012277

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 12, pitch: 2.54 mm, connection method: Crimp connection, color: black



Printed-circuit board connector - MCC 0,5/13-ST-2,54 - 1012278

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 13, pitch: 2.54 mm, connection method: Crimp connection, color: black



Printed-circuit board connector - MCC 0,5/14-ST-2,54 - 1012279

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 14, pitch: 2.54 mm, connection method: Crimp connection, color: black



Printed-circuit board connector - MCC 0,5/15-ST-2,54 - 1012281

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 15, pitch: 2.54 mm, connection method: Crimp connection, color: black



Printed-circuit board connector - MCC 0,5/16-ST-2,54 - 1012282

PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 16, pitch: 2.54 mm, connection method: Crimp connection, color: black



Accessories - MCC 0,5-MP AU 0,14-0,5 R - 1013420

Accessories

Printed-circuit board connector - DMCC 0,5/ 2-ST-2,54 - 1027603



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 2, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/ 3-ST-2,54 - 1027605



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 3, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/ 4-ST-2,54 - 1027606



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 4, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/ 5-ST-2,54 - 1027607



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 5, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/ 6-ST-2,54 - 1027608



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 6, pitch: 2.54 mm, connection method: Crimp connection, color: black

Accessories - MCC 0,5-MP AU 0,14-0,5 R - 1013420

Accessories

Printed-circuit board connector - DMCC 0,5/ 7-ST-2,54 - 1027609



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 7, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/ 8-ST-2,54 - 1027610



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 8, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/ 9-ST-2,54 - 1027611



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 9, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/10-ST-2,54 - 1027612



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 10, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/11-ST-2,54 - 1027613



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 11, pitch: 2.54 mm, connection method: Crimp connection, color: black

Accessories - MCC 0,5-MP AU 0,14-0,5 R - 1013420

Accessories

Printed-circuit board connector - DMCC 0,5/12-ST-2,54 - 1027614



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 12, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/13-ST-2,54 - 1027615



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 13, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/14-ST-2,54 - 1027616



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 14, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/15-ST-2,54 - 1027617



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 15, pitch: 2.54 mm, connection method: Crimp connection, color: black

Printed-circuit board connector - DMCC 0,5/16-ST-2,54 - 1027618



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, Nominal cross section: 0.75 mm², number of positions: 16, pitch: 2.54 mm, connection method: Crimp connection, color: black

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminal Block Tools & Accessories](#) category:

Click to view products by [Phoenix Contact](#) manufacturer:

Other Similar products are found below :

[600HL](#) [600RJ-07](#) [600RJ-11](#) [600RJ-14](#) [600RJS-10](#) [600RJS-12](#) [600RJS-15](#) [600RJS-17](#) [600RJS-18](#) [600RJS-21](#) [601RJ-09](#) [602SP](#) [602Z](#) [604J](#)
[CSTSPC1-2](#) [88943-2100](#) [QC102](#) [1437403-6](#) [1437403-9](#) [1437403-8](#) [147832-1](#) [MT2/H--](#) [MT6/H-N](#) [MT6/V-GRND](#) [MT8/H-51-60](#) [BC2-12](#)
[BCC-1-8/10](#) [EP2.5/4UN/BG](#) [1840227](#) [1840230](#) [JA2-03](#) [JB1-03/J](#) [JB2-04](#) [JB2-05](#) [JB2-07](#) [JB2-09/J](#) [PARALLELJUMPERLINK](#) [JS601](#)
[2302463](#) [2305949](#) [8PCV-BUSHING](#) [91.201.1](#) [9200768](#) [2778.0](#) [281-421](#) [2MP/J](#) [2MV-06](#) [1705126](#) [2006-CBLK](#) [FLRP/SKBD](#)